

CONTRACT SPECIFICATIONS

Exterior Modifications for Tinsley Manor

Anniston Housing Authority
Anniston, Alabama

TDA 441B

TDA Architects, LLC

The logo for TDA Architects, LLC features the letters 'TDA' in a large, outlined, serif font. The text 'TDA Architects, LLC' is written in a smaller, solid, sans-serif font across the middle of the 'TDA' letters.

INDEX TO SPECIFICATIONS

Exterior Modifications for Tinsley Manor

Anniston Housing Authority Anniston, Alabama

PROJECT DIRECTORY

ADDENDA (when issued)

BIDDING AND CONTRACT REQUIREMENTS

Advertisement for Bids

Instructions to Bidders for Contracts Public and Indian Housing Programs - HUD 5369 (10/2002)

Representations, Certifications, and Other Statements of Bidders - HUD 5369-A (11/1992)

General Conditions of the Contract for Construction - HUD 5370 (11/2006)

Supplemental General Conditions - HUD 4238-N

Bid Form

Form of Bid Bond (7460-8 Rev-1)

Previous Participation Certification - HUD 2530 (05/2001)

Non-Collusive Affidavit

Form of Performance Bond (7460-8 Rev-1)

Form of Payment Bond (7460-8 Rev-1)

Form of Contract - HUD 4238-F

Wage Rates

Section 3 Clause

Form of Advertisement of Completion

HUD CONSTRUCTION FORMS: (not included)

The following HUD construction forms shall be used by the Contractor during construction. A copy of these forms may be obtained from the Architect's office.

Form HUD-5282	Certificate from Contractor - Appointing Officer or Employee to Supervise Payment of Employees
Form HUD-5371	Request for Acceptance of Subcontractor
Form HUD-5372	Construction Progress Schedule
Form HUD-5378	Construction Report
Form HUD-51000a	Schedule of Amounts for Contract Payments
Form HUD-51001	Periodic Estimate for Partial Payment
Form HUD 51002	Schedule of Change Orders
Form HUD-51003	Schedule of Material Stored
Form HUD-51004	Summary of Materials Stored

TECHNICAL SPECIFICATIONS

INDEX OF DRAWINGS

T1	Title Sheet
N1	Notes
C1	Code Compliance
S1	Site Plan
A1	Building Type 'A' First Floor
A2	Building Type 'A' Second Floor
A3	Building 'A' Porch Framing
A4	Building 'A' Roof Plan
A5	Building Type 'A' Elevations
A6	Building Type 'A' Elevations
A7	Building Type 'B' First Floor
A8	Building Type 'B' Second Floor
A9	Building 'B' Porch Framing & Details
A10	Building 'B' Roof Plan
A11	Building Type 'B' Elevations
A12	Building Type 'B' Elevations

DIVISION 1 - GENERAL REQUIREMENTS

00750	- Supplemental General Conditions
01010	- Summary
01045	- Cutting & Patching
01140	- Work Restrictions
01330	- Submittal Procedures
01400	- Quality Requirements
01600	- Product Requirements
01700	- Execution Requirements
01731	- Cutting & Patching
01732	- Selective Demolition

DIVISION 2 – SITEWORK

DIVISION 3 – CONCRETE

03300	– Cast in Place Concrete
-------	--------------------------

DIVISION 4 – MASONRY

(See drawings)

DIVISION 5 – METAL - (not applicable)

DIVISION 6 - WOOD & PLASTICS

06100	- Rough Carpentry
06200	- Finish Carpentry

DIVISION 7 - THERMAL & MOISTURE PROTECTION

07200	– Insulation
07311	- Asphalt Shingles
07460	- Vinyl Siding & Aluminum Trim
07620	- Sheet Metal Flashing & Trim
07900	- Joint Sealers

DIVISION 8 - DOORS, WINDOWS, & GLASS - (not applicable)

DIVISION 9 - FINISHES

09900 - Painting

DIVISION 10 - SPECIALTIES - (not applicable)

DIVISION 11 - EQUIPMENT - (not applicable)

DIVISION 12 – FURNISHINGS - (not applicable)

DIVISION 13 - SPECIAL CONSTRUCTION - (not applicable)

DIVISION 14 - CONVEYING SYSTEMS - (not applicable)

DIVISION 15 - MECHANICAL - (not applicable)

DIVISION 16 - ELECTRICAL - (not applicable)

PROJECT DIRECTORY

OWNER:

Anniston Housing Authority
Gregg Fortner, Executive Director
Doug Brooks, Contract Manager
500 Glen Addie Avenue
Anniston, Alabama 36202
(256) 236-1575 telephone
(256) 236-3981 facsimile

ARCHITECT:

TDA Architects, LLC
Steven P. Taylor
125 West Columbus Street
Dadeville, Alabama 36853
(205) 823-2969 telephone
steve@tdaarchitectsllc.com

ADVERTISEMENT FOR BIDS

The Anniston Housing Authority will receive bids for: **Exterior Modifications for Tinsley Manor, Anniston Housing Authority, Anniston, Alabama**, until **2:00 p.m.** local time on **Wednesday, April 17th, 2024**, at the Housing Authority central office located at 500 Glen Addie Avenue, Anniston, Alabama 36202 at which time and place all will be opened and read aloud.

Scope of work will include (but is not limited to): Major exterior renovations to include (but not limited to); new porch structures, and limited site improvements.

Contract documents, including drawings and technical specifications, may be obtained by contacting the following:

Owner: The Anniston Housing Authority
Attention: Mr. Gregg Fortner, Executive Director
Attention: Mr. Doug Brooks, Construction Manager
500 Glen Addie Avenue
Anniston, AL 36202
(256) 236-1575 telephone / (256) 236-3981 facsimile

Architect: TDA Architects, LLC
Attn: Steven Taylor, Architect
125 West Columbus Street
Dadeville, AL 36853
205-823-2969 / 205542-5315 ph.
steve@tdaarchitectsllc.com

Interested Bidders are required to review the complete version of the Contract Documents, posted on the Housing Authority's website at www.annistonhousing.org. Anyone interested in bidding the Project must contact the Architect at the above email address.

Gregg Fortner, Executive Director
The Anniston Housing Authority

Advertise on the following dates: March 23rd, 27th, 30th, and April 3rd, 2024.

SUPPLEMENTAL GENERAL CONDITIONS

1. Reference Clause 10, (HUD 5369) - Assurance of Completion, Subparagraph (a)., Item (1):
 - (1) A performance bond and a payment bond in a penal sum of 100 percent (100%) of the contract price are required for execution of the contract. Separate bonds for performance and payment are required.
2. Reference Clause 27, (HUD 5370) - Payments, Subparagraph (f) Change to Read:
 - (f) Except as otherwise provided in State law, the PHA/IHA shall retain ten (10) percent of the amount of progress payments until completion and acceptance of all work under the contract.

BID FORM

Exterior Modifications for Tinsley Manor
Anniston, Alabama
Anniston Housing Authority

Proposal of _____

(hereinafter called "Bidder") (a/an _____ corporation/a partnership/an individual
(State) (Strike out inapplicable terms)

doing business as _____) to

Anniston Housing Authority (hereinafter called "Owner").

Gentlemen:

The Bidder, in compliance with your invitation for bids for the **Exterior Modifications for Tinsley Manor, Anniston, Alabama**. The Bidder, having examined the plans and specifications with related documents and the site of the proposed work, and being familiar with all of the conditions surrounding the construction of the proposed project including the availability of materials and labor, hereby proposes to furnish all labor, materials, and supplies, and to construct the project in accordance with the Contract Documents, within the time set forth therein, and at the prices stated below. These prices are to cover all expenses incurred in performing the work required under the Contract Documents, of which this proposal is a part.

Bidder hereby agrees to commence work under this contract on or before a date to be specified in written "Notice to Proceed" of the Owner and to fully complete the project within **90** consecutive calendar days thereafter as stipulated in the specifications. Bidder further agrees to pay as liquidated damages, the sum of **\$100** for each consecutive calendar day thereafter as hereinafter provided in Paragraph 33 of "General Conditions of the Contract for Construction" HUD-5370 (11-92).

Bidder acknowledges receipt of the following addenda:

Addendum No. _____ Dated _____ Addendum No. _____ Dated _____
Addendum No. _____ Dated _____ Addendum No. _____ Dated _____
Addendum No. _____ Dated _____ Addendum No. _____ Dated _____

BASE PROPOSAL: Bidder agrees to perform all of the work as described in the specifications and shown on the plans for each site as follows:

TOTAL BASE BID: _____
_____ (\$ _____).

(Amounts shall be shown in both words and figures. In case of discrepancy, amount shown in words shall govern.)

ALTERNATE PROPOSALS: (N/A)

UNIT PRICES: (N/A)

Bidder understands that the Owner reserves the right to reject any or all bids and to waive any informalities in the bidding.

The bidder agrees that this bid shall be good and may not be withdrawn for a period of sixty (60) calendar days after the scheduled closing time for receiving bids.

Upon receipt of written notice of the acceptance of this bid, Bidder will execute the formal contract and deliver to the owner the Performance Bond, Labor, and Material Payment Bond and proof of required insurance coverage within 10 days of notification as required by Clause 9 "Instruction to Bidders for contracts Public and Indian Housing Programs" HUD-5369 (10/2002).

The bid security attached in the sum of _____ (\$ _____) is to become the property of the Owner in the event the contract and bond are not executed within the time above set forth, as liquidated damages for the delay and additional expense to the Owner caused thereby.

Respectfully Submitted:

NOTE: If bidder is a corporation, set forth the legal name of the corporation together with the signature of the officer or officers authorized to sign contracts on behalf of the corporation; if bidder is a partnership, set forth the name of the firm together with the signature of the partner or partners authorized to sign contracts on behalf of the partnership.

AL. G.C. LICENSE NO.: _____ PHONE NO.: _____

CONTRACTOR: _____

BUSINESS ADDRESS: _____

CITY: _____ STATE: _____ ZIP: _____

BIDDER'S SIGNATURE: _____ DATE: _____

(Seal if Bid is by a Corporation)

BID BOND

KNOW all by these presents, that we _____ as Principal,

 (Contractor)
 hereinafter called the Principal, and _____ a corporation

 (Bonding Company)
 duly organized under the laws of the _____ as Surety, hereinafter called the

 (State Organized)
 Surety, are held and firmly bound unto Anniston Housing Authority for the sum of
 _____ Dollars (\$ _____)
 for the payment of which sum well and truly to be made, the said Principal and the said Surety bind
 ourselves, our heirs, executors, administrators, successors, and assigns, jointly and severally, firmly
 by these presents.

WHEREAS, the Principal has submitted a bid for Exterior Modifications for Tinsley Manor,
 Anniston, Alabama .

NOW, therefore, if the Anniston Housing Authority shall accept the bid of the Principal and the
 Principal shall enter into a contract with the Anniston Housing Authority in accordance with the
 terms of such bid, and give such bond or bonds as may be specified in the bidding or Contract
 documents with good and sufficient surety for the faithful performance of such contract and for the
 prompt payment of labor and material furnished in the prosecution thereof, or in the event of the
 failure of the Principal to enter such Contract and give such bond or bonds, if the Principal shall pay
 the Anniston Housing Authority the difference not to exceed the penalty hereof between the
 amount hereof between the amount specified in said bid and such amount hereof between the
 amount specified in said bid and such larger amount for which the Anniston Housing Authority
 may in good faith contract with another party to work covered by said bid or an appropriate required
 amount as specified in the Invitation for Bids, then this obligation shall be null and void, otherwise to
 remain in full force and effect.

BID BOND
(continued)

Signed and sealed this _____ day of _____, 2024.

(Principal) (Seal)

(Witness)

(Title)

(Witness)

(Bonding Company)

BY: _____

**NON-COLLUSIVE AFFIDAVIT
(Contractor's form)**

State of _____

County of _____

_____, being first duly sworn, deposes and says that he is _____, the party making the foregoing proposal or bid,
(a partner or officer of the firm, etc.)

that such proposal or bid is genuine and not collusive or sham; that said bidder has not colluded, conspired, connived or agreed, directly or indirectly, with any bidder or person, to put in a sham bid or to refrain from bidding, and has not in any manner, directly or indirectly, sought by agreement or collusion, or communication or conference, with any person, to fix the bid price of affiant or of any other bidder, or to fix overhead, profit or cost element of said bid price, or of that of any other bidder, or to secure any advantage against **Anniston Housing Authority** of any
(Local Housing Authority)

person interested in the proposed contract and that all statements in said proposal or bid are true.

(Bidder, if the bidder is individual;
Partner, if the bidder is a partnership;
Officer, if the bidder is a corporation)

Notary Public

Subscribed and sworn to before me this _____ day of _____, 2024.

My commission expires _____.

**NON-COLLUSIVE AFFIDAVIT
(Subcontractor's form)**

State of _____

County of _____

_____, being first duly sworn, deposes and says that he is _____, the party making the foregoing proposal or bid,
(a partner or officer of the firm, etc.)

that such proposal or bid is genuine and not collusive or sham; that said bidder has not colluded, conspired, connived or agreed, directly or indirectly, with any bidder or person, to put in a sham bid or to refrain from bidding, and has not in any manner, directly or indirectly, sought by agreement or collusion, or communication or conference, with any person, to fix the bid price of affiant or of any other bidder, or to fix overhead, profit or cost element of said bid price, or of that of any other bidder, or to secure any advantage against **Anniston Housing Authority** of any
(Local Housing Authority)
person interested in the proposed contract and that all statements in said proposal or bid are true.

(Bidder, if the bidder is individual;
Partner, if the bidder is a partnership;
Officer, if the bidder is a corporation)

Notary Public

Subscribed and sworn to before me this _____ day of _____, 2024.

My commission expires _____.

PERFORMANCE BOND

Bond No. _____.

KNOW all by these presents that _____

(Here insert full name and address or legal title of Contractor)

as Principal, hereinafter called Contractor, and _____,
(Bonding Company)

a corporation duly organized under the laws of the state of _____, a Surety,
(State Organized)

hereinafter called Surety, are held and firmly bound unto the **Anniston Housing Authority**,
as Obligee, in the amount of _____ Dollars
(\$ _____), for the payment whereof Contractor and Surety bind themselves, their heirs,
executors, administrators, successors, and assigns, jointly and severally, firmly by these presents.

WHEREAS, Contractor has by written agreement dated _____, 2024, entered into a
contract with the **Anniston Housing Authority** for **Exterior Modifications for Tinsley Manor,**
Anniston, Alabama in accordance with drawings and specifications prepared by TDA Architects,
LLC, 125 West Columbus Street, Dadeville AL 36853, which contract is by reference made a part
hereof, and is hereinafter referred to as the Contract.

NOW, therefore, the condition of this obligation is such that, if Contractor shall promptly and faithfully
perform said Contract then this obligation shall be null and void; otherwise it shall remain in full
force and effect. The Surety hereby waives notice of any such alteration or extension of time made
by the **Anniston Housing Authority**, and its obligation is not affected by any such alteration or
extension provided the same is within the scope of the Contract. Whenever Contractor shall be,
and is declared by, the **Anniston Housing Authority**, to be in default under the Contract, the
Anniston Housing Authority, having performed the **Anniston Housing Authority**

obligations thereunder, the Surety may promptly remedy the default or shall promptly:

- 1) Complete the Contract in accordance with its terms and conditions; or
- 2) Obtain a bid or bids for completing the Contract in accordance with its terms and conditions,
and upon determination by the **Anniston Housing Authority**, and the Surety jointly of the
lowest responsive, responsible bidder, arrange for a Contract between such bidder and
the **Anniston Housing Authority**, and make available as work progresses (even though

there should be a default or succession of defaults under the contract or contracts of completion arranged under this paragraph) sufficient funds to pay the cost of completion less the balance of the contract price; but not exceeding, including other costs and damages for which the Surety may be liable hereunder, the amount set forth in the first paragraph hereof. The term, "balance of the contract price," as used in this paragraph, shall mean the total amount payable by the **Anniston Housing Authority**, to Contractor under the Contract and any amendments thereunto, less the amount property paid the **Anniston Housing Authority** by the Contractor. No right of action shall accrue on this bond to or for the use of any person or corporation other than the **Anniston Housing Authority** successors of the **Anniston Housing Authority**.

Signed and sealed this _____ day of _____, 2024.

(Witness)

(Principal) (Seal)

(Title) (Bonding Company)

(Witness)

BY: _____
(Attorney-in-Fact)

LABOR AND MATERIAL PAYMENT BOND

Bond No. _____

KNOW all by these presents that _____

_____ as
(Here insert full name and address or legal title of Contractor)

Principal, hereinafter called Principal, and _____, a
corporation duly organized under the laws of the state of _____, as Obligee,
(State Organized)

hereinafter called the **Anniston Housing Authority** for the use and benefit of claimants as
herein below defined, in the amount of _____ Dollars (\$ _____)

for the payment whereof Principal and Surety bind themselves, their heirs, executors,
administrators, successors and assigns, jointly and severally, firmly by these presents.

WHEREAS, Principal has by written agreement dated _____, 2024, entered into a
contract with the **Anniston Housing Authority** for **Exterior Modifications for Tinsley Manor,
Anniston, Alabama**

(Describe project and insert project number)

in accordance with drawings and specifications prepared by TDA Architects, LLC, 125 West
Columbus Street, Dadeville, Alabama 36853, which contract is by reference made a part hereof,
and is hereinafter referred to as the Contract.

NOW, therefore, the condition of this obligation is such that, if promptly make payment to all claim-
ants as hereinafter defined, for all labor and material used or reasonably required for use in the
performance of the Contract, then this obligation shall be void; otherwise it shall remain in full force
and effect, subject, however, to the following conditions:

- 1) A claimant is defined as one having a direct contract with the Principal or with a subcontractor of the Principal for labor, material, or both, used or reasonably required for use in the performance of the Contract, labor and material being construed to include that part of water, gas, power, light, heat, oil, gasoline, telephone service, or rental of equipment directly applicable to the Contract.
- 2) The above-named Principal and Surety hereby jointly and severally agree with the **Anniston Housing Authority** that every claimant as herein defined, who has not been paid in full before the expiration of a period of ninety (90) days after the date on which the last of such claimant's work or labor was done or performed, or materials were furnished by such claimant, may sue on this bond for the use of such claimant, prosecute the suit to final judgment for such sum or sums

as may be justly due claimant, and have execution thereon. The **Anniston Housing Authority** shall not be liable for payment of any costs or expenses of any such suit.

- 3) No suit or action shall be commenced herein under by any claimant:
 - a) Unless claimant, other than one having a direct contract with the Principal, shall have given written notice to any two of the following: the Principal, the **Anniston Housing Authority**, or the Surety above named, within ninety (90) days after such claimant did or furnished the last of the materials for which said claim is made, stating with substantial accuracy the amount claimed and the name of the party to whom the materials were furnished, or for whom the work or labor was done or performed. Such notice shall be personally served or served by mailing the same by registered mail or certified mail, postage prepaid, in an envelope addressed to the Principal at any place the Principal maintains an office or conducts its business.
 - b) After the expiration of one (1) year following the date on which the last of the labor was performed or material was supplied by the party bringing suit.
 - c) Other than in a court of competent jurisdiction for the county or district in which the construction contract was to be performed.
- 4) The amount of this bond shall be reduced by and to the extent of any payment or payments made in good faith herein under, inclusive of the payment or payments made in good faith herein under, inclusive of the payment by Surety of mechanics; liens which may be filled or record against said improvement, weather or not claim for the amount of such lien be presented under the against this bond.

Signed and sealed this _____ day of _____, 2024.

(Witness)

(Principal) (Seal)

(Title) (Bonding Company)

(Witness)

BY: _____
(Attorney-in-Fact)

CONTRACT

THIS AGREEMENT, made this _____ day of _____, **2024**, by and between **Anniston Housing Authority**, herein called "Owner", acting herein through its **Contracting Officer**, and _____, a corporation of _____, County of _____, and State of _____, herein called "Contractor".

WITNESSETH: That for and in consideration of the payments and agreements hereinafter mentioned, to be made and performed by the OWNER. The CONTRACTOR hereby agrees with the OWNER to commence and complete the construction described as follows:

**Exterior Modifications for
Tinsley Manor**

**Anniston, Alabama
Anniston Housing Authority**

hereinafter called the Project, for the sum of _____ dollars (**\$ _____**) and all extra work in connection therewith, under the terms as stated in the General and Special Conditions of the Contract; and at its own proper cost and expense to furnish all materials, supplies, machinery, equipment, tools, superintendence, labor, insurance, and other accessories and services necessary to complete the said project in accordance with the conditions and prices stated in the Proposal, the General Conditions, Supplemental General Conditions and Special Conditions of the Contract, the plans, which include all maps, plats, blue prints, and other drawings and printed or written explanatory matter thereof, the specifications and contract documents therefore as prepared by **TDA Architects, LLC.**, herein entitled the Architect/Engineer.

The CONTRACTOR hereby agrees to commence work under this contract on or before a date to be specified in a written "Notice to Proceed" by the OWNER and to fully complete the project within **270** consecutive calendar days thereafter. The CONTRACTOR further agrees to pay, as liquidated damages, the sum of **\$ 100** per day thereafter as hereinafter provided in Paragraph 17 of "Instructions to Bidders".

The OWNER agrees to pay the CONTRACTOR in current funds for the performance of the contract, subject to additions and deductions, as provided in the General Conditions of the Contract, and to make payments on account thereof as provided in Paragraph 8, "Payments to Contractor," of the General Conditions.

IN WITNESS WHEREOF, the parties to those present have executed this contract in three (3) counterparts, each of which shall be deemed an original, in the year and day first above mentioned.

(Seal)

Attest:

(Secretary)

(Witness)

Anniston Housing Authority
(Owner)

By: _____
Gregg Fortner

Executive Director
(Title)

(Seal)

(Secretary)

(Witness)

(Contractor)

By: _____

President
(Title)

(Address)

NOTE: Secretary of the Owner should attest. If Contractor is a corporation, Secretary should attest.

**FORM OF
ADVERTISEMENT OF COMPLETION**

Legal Notice

In accordance with Section 16, Title 50 Code of Alabama, 1940, notice is hereby given that
_____ Contractor(s) have completed
the Contract for (Construction, Reconstruction, Alteration, Equipment, or Improvements) of

(insert location data in County of City)

for **The Anniston Housing Authority**, Owner(s), and have made request for final settlement of
said Contract.

Contractor(s)

SECTION 3 CLAUSE

All Section 3 covered contracts shall include the following clause (referred to as the Section 3 clause):

- A. The work to be performed under this contract is subject to the requirements of Section 3 of the Housing and Urban Development Act of 1968, as amended, 12 U.S.C. 1701u (Section 3). The purpose of Section 3 is to ensure that employment and other economic opportunities generated by HUD assistance or HUD-assisted projects covered by Section 3 shall, to the greatest extent feasible, be directed to low- and very low-income persons, particularly persons who are recipients of HUD assistance for housing.
- B. The parties to this contract agree to comply with HUD's regulations in 24 CFR part 135, which implement Section 3. As evidenced by their execution of this contract, the parties to this contract certify that they are under no contractual or other impediment that would prevent them from complying with the part 135 regulations.
- C. The contractor agrees to send to each labor organization or representative of workers with which the contractor has a collective bargaining agreement or other understanding, if any, a notice advising the labor organization or workers' representative of Section 3 clause, and will post copies of the notice in conspicuous places at the work site where both employees and applicants for training and employment positions can see the notice. The notice shall describe the Section 3 preference, shall set forth minimum number and job titles subject to hire, availability of apprenticeship and training positions, the qualifications for each; and the name and location of the person (s) taking applications for each of the positions; and the anticipated date the work shall begin.
- D. The contractor agrees to include this Section 3 clause in every subcontract subject to compliance with regulations in 24 CFR part 135, and agrees to take appropriate action, as provided in an applicable provision of the subcontract or in this Section 3 clause, upon a finding that the subcontractor is in violation of the regulation in 24 CFR part 135. The contractor will not subcontract with any subcontractor where the contractor has notice or knowledge that the subcontractor has been found in violation of the regulations in 24 CFR part 135.
- E. The contractor will certify that any vacant employment positions, including training positions, that are filled (1) after the contractor is selected but before the contract is executed, and (2) with persons other than those to whom the regulations of 24 CFR part 135 require employment opportunities to be directed, were not filled to circumvent the contractor's obligations under 24 CFR part 135.
- F. Noncompliance with HUD's regulations in 24 CFR part 135 may result in sanctions, termination of this contract for default, and debarment or suspension from future HUD assisted contracts.

AHA has identified two ways that contractors and consultants may choose to satisfy Section 3 requirements.

- A. Direct employment of qualified candidates (preferred method of participation)
AHA promotes family self-sufficiency and strongly encourages the direct hiring of qualified residents from the communities (Public Housing, Housing Choice Voucher and by Tax Credit residents) impacted by work awarded to contractors and subcontractors. All developers, general contractors and /or subcontractors shall ensure that 30% of new hires will be Section 3 residents.
- B. Contribution to AHA Section 3 Resident Training Fund.
Smaller contractors and consultants may contribute to AHA's Section 3 training fund in an amount based on the Resident Hiring Scale contained in AHA Section 3 Policy. The current hiring scale is a minimum \$250 or a maximum 1.5% of the labor dollars.

**SECTION 00750
SUPPLEMENTARY GENERAL CONDITIONS**

PART 1 - GENERAL

1.1 SUMMARY

- A. The following supplements modify, delete and/or add to the General Conditions, Section 00700. The paragraphs or subparagraphs modified herein shall be added thereto, amended, voided, or superseded as herein instructed.

PART 2 - SPECIFIC MODIFICATIONS

2.1 PARAGRAPH 1 - DEFINITIONS:

- A. Revise subparagraph 1 (h) as follows:
 - 1. "(h) The terms "LHA", "PHA", "HA", "LA", "Local Authority", or "Housing Authority" are synonymous with the term "Owner" and shall mean THE ANNISTON HOUSING AUTHORITY, as organized under applicable State law."

2.2 PARAGRAPH 2 - Contractor's Responsibility for Work:

- A. Add to Subparagraph 2(e) the following sentences as condition to fitting and coordination of work.
 - 1. "Contractor shall be responsible for proper fitting of all work for coordination of operations of all trades, subcontractors, or material men employed by him engaged upon the Work. He shall be prepared to guarantee to each of his subcontractors the dimensions required for fitting of their work to all surrounding work, and shall do all cutting, fitting, adjusting, and patching as necessary to make the several parts of the Work come together properly and to fit the work to receive, or be received by, that of other contractors."
- B. Add subparagraph 2(i) as to mutual responsibility of contractors.
 - 1. "(i) If, through acts or neglect on the part of the Contractor, any other contractor or subcontractor shall suffer loss or damage on the work. The agreement or arbitration, if such other contractor will so settle. If such other contractor or subcontractor shall assert any claim against the Owner on account of any damages alleged to have been so sustained, the Owner shall notify the Contractor, who shall defend, at his own expense, any suit based upon such claim and pay all costs and expenses in connection therewith."

2.3 Paragraph 3 - Architect's Duties, Responsibilities and Authority:

- A. Add Subparagraph (d) as follows:
 - 1. "(d) The Architect does not have the authority to stop the work or any part thereof. Only the PHA/LA has the authority to stop the work or any part thereof. If the Contractor stops work due to an observation or report by the Architect, he does so at his sole discretion and neither the PHA/LA nor the Architect shall be liable for any delays or costs resulting therefrom."

2.4 Paragraph 8 - Differing Site Conditions:

- A. Add Subparagraph 8(e) to clarify responsibility for live utilities and other property:
 - 1. "(e) Contractor shall assume all responsibility for damage to any property upon, or passing through, the site but excluded from the Work or not owned by the Owner, such as utility lines or like items. Where disconnections of underground services are required to be made at street mains, Contractor shall, at his own expense, restore paving, curb, gutter, etc., over such cuts in accordance with local regulations."

2.5 Paragraph 9 - Specifications and Drawings for Construction:

- A. "(j) The Owner will furnish, free of charge, to the Contractor five (5) copies of the Drawings and Project Manual. Additional copies requested by the Contractor will be furnished at the cost of reproduction, plus shipping and handling."

2.6 Paragraph 11 - Materials and Workmanship:

- A. Revise Subparagraph 11(a) beginning with the second sentence as follows:
1. "Specific reference in the Technical specifications to article, device, product, material, fixture, form or type, or construction by trade name, make or catalog number shall be interpreted as a mandatory work requirement except where substitutions are specifically allowed or the Technical Specifications are not proprietary in nature. Substitutions for the mandatory items will only be considered if submitted to the Architect at least fifteen (15) days prior to the date of the bid opening. Requests for approval of substitutions in written form and include such detailed information as to provide for a complete comparison of the products. All approved substitutions will be listed by addenda. Only the specified products or those substitutions listed by addenda shall be used in the preparation of the Contractors bid proposal and incorporated into the Work. The approval of substitutions shall be at the sole discretion of the Architect."
- B. Revise the first sentence of Subparagraph 11(b) to read as follows:
1. "When requesting approval for a substitution prior to bid opening, the Contractor shall....."

2.7 Paragraph 12 - Permits and Codes:

- A. "(b) The Contractor shall secure and pay for all permits, fees, licenses, and utility charges for this project necessary for the proper execution and completion of the work. The utility charges shall include all tap-on charges, meter charges, and any other fees or charges required by any utility company or public agency which sets such fees to accomplish all work required by these Contract Documents. Where the Owner can arrange for the issuance of all or part of these permits, fees and licenses without cost to the Contractor, the Contract amount will be reduced accordingly."

2.8 Paragraph 25 - Contract Period:

- A. (a) The following chart shows rain days anticipated in **Anniston, Alabama** each year. These days are included in the time allowed for completion. Only rain days in addition to these will be considered as a time extension to the contract for "unusually severe weather" as provided for in Paragraph 32(b)(1)(x) of the General Conditions.

<u>Month</u>	<u>Rain Days</u>
January	11
February	10
March	11
April	09
May	09
June	10
July	12
August	10
September	08
October	06
November	09
December	10

- B. (b) If the Contractor falls more than thirty (30) days behind in his work, as shown on his progress schedule, and cannot demonstrate, to the satisfaction of the Owner, an effective recover schedule, the Owner reserves the right to terminate his contract under Article 32 of the General Conditions. Refer to Section 01310 for requirements of the Progress Schedule.

2.9 Paragraph 27 - Payments:

- A. Add Subparagraph (l) as follows:
1. "(l) Along with each progress payment, the Contractor shall submit a revised progress schedule as specified in Section 01310. Payment request will not be processed without this schedule attached."

2.10 Paragraph 33 - Liquidated Damages:

- A. Add Subparagraph 33(a)(1) and (2) to establish amount of liquidated damages.
 - 1. "(1) Since the actual amount of damages for any delay in completion are impossible to determine, the Contractor and his sureties hereby agree to be liable for and shall pay to the Owner the sums hereinafter stipulated as fixed, agreed and liquidated damages, for each calendar day of delay until the Work is completed or accepted."
 - 2. "(2) \$75.00 applicable to all work per calendar day per building for each building not completed and accepted by the date established for completion of each phase, by the phasing plan of the Contract Documents."

2.11 Paragraph 36 - Insurance:

- A. Revise Subparagraph 36(a)(2) to require Commercial General Liability Insurance in the amount of \$1,000,000.00.
- B. Revise Subparagraph 36(a)(3) to require Automobile Liability Insurance in the amount of \$500,000.00.

2.12 Paragraph 50 - Communications:

- A. Add Paragraph 50: Communications, with Subparagraphs (a), (b), (c), and (d) as follows:
 - 1. "(a) All notices, demands, request, instructions, approvals, proposals and claims must be in writing."
 - 2. "(b) Any notice to, or demand upon, the Contractor shall be sufficiently given if delivered at the Office of the Contractor (or at such office as he may designate in writing to the Owner), or deposited in the United States mail in a sealed, postage-prepaid envelope, or if delivered with charges prepaid to any telegraph company for transmission, in each case addressed to such office."
 - 3. "(c) All papers required to be delivered to the Owner shall, unless otherwise specified in writing to the Contractor, be delivered to:
THE ANNISTON HOUSING AUTHORITY
500 GLEN ADDIE AVENUE
ANNISTON, ALABAMA 36202
ATTN.: CONTRACTING OFFICER
And any notice to, or demand upon, the Owner shall be sufficiently given so delivered, or deposited in the United States mail in a sealed postage prepaid envelope, or delivered with charges prepaid to any telegraph company for transmission to said person at such address, or to such other representatives that the Owner may subsequently specify in writing to the Contractor for such purpose."
 - 4. "(d) Any such notice shall be deemed to have been given as of the time of actual delivery or (in case of mailing) when the same should have been received in due course of post, or in the case of telegrams, at the time of actual receipt, as the case may be."

2.13 Paragraph 51 - Taxes:

- A. Add Paragraph 51 - Taxes, as follows:
 - 1. "39. Taxes: The Contractor shall include applicable taxes in his bid proposal and the Contract Sum."

2.14 Add Paragraph 52 - Equal Employment:

- A. "52. Add provisions for Equal Employment Opportunity, as enumerated in Exhibit "A" following this Section."

END OF SECTION 00750

**SECTION 01010
SUMMARY**

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 1 Specification Sections, apply to this Section.

1.2 WORK COVERED BY CONTRACT DOCUMENTS

- A. Project Identification: Modifications for Tinsley Manor, Anniston Housing Authority.
 - 1. Project location: Anniston, Alabama.
 - 2. Owner: Anniston Housing Authority
500 Glen Addie Avenue
Anniston, Alabama 36202
- B. Architect Identification: The Contract Documents, dated June 10, 2022, were prepared for the Project by: TDA Architects, LLC.
- C. Owner's Representative: The Owner's Representative will be Mr. Doug Brooks, Contract Manager.
- D. The Work consists of the major interior and exterior renovations to include (but not limited to); ceiling replacement, subfloor replacement, HVAC replacement, roof replacement, new porch structures, and limited site improvements.

1.3 PROJECT DESCRIPTION

- A. Tinsley Manor:
 - 1. See drawings.

1.4 CONTRACT

- A. Project will be constructed under a general construction contract.

1.5 WORK SEQUENCE

- A. The Work shall be conducted while the existing apartments are unoccupied. Work shall commence on the Notice to Proceed date and shall be completed within the allowed time frame.

1.6 USE OF PREMISES

- A. General: Contractor shall have limited use of premises for construction operations, including use of Project site, during construction period.

1.7 SPECIFICATION FORMATS AND CONVENTIONS

- A. Specification Format: The Specifications are organized into Divisions and Sections using the 16-division format and CSI/CSC's "MasterFormat" numbering system.
 - 1. Section Identification: The Specifications use section numbers and titles to help cross-referencing in the Contract Documents. Sections in the Project Manual are in numeric sequence; however, the sequence is incomplete. Consult the table of contents at the beginning of the Project Manual to determine numbers and names of sections in the Contract Documents.
- B. Specification Content: The Specifications use certain conventions for the style of language and the intended meaning of certain terms, words, and phrases when used in particular situations. These conventions are as follows:
 - 1. Abbreviated Language: Language used in the Specifications and other Contract Documents is abbreviated. Words and meanings shall be interpreted as appropriate. Words implied, but not stated, shall be inferred as the sense requires. Singular words shall be interpreted as plural and plural words shall be interpreted as singular where applicable as the context of the Contract Documents indicates.

2. Imperative mood and streamlined language are generally used in the Specifications. Requirements expressed in the imperative mood are to be performed by Contractor. Occasionally, the indicative or subjunctive mood may be used in the Section Text for clarity to describe responsibilities that must be fulfilled indirectly by Contractor or by others when so noted.
 - a. The words "shall," "shall be," or "shall comply with," depending on the context, are implied where a colon (:) is used within a sentence or phrase.

PART 2 - PRODUCTS - (Not Applicable)

PART 3 - EXECUTION - (Not Applicable)

END OF SECTION 01010

**SECTION 01140
WORK RESTRICTIONS**

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 1 Specification Sections, apply to this Section.

1.2 USE OF PREMISES

A. Use of Site: Work can be initiated and completed upon receipt of a notice to proceed. The Owner will designate areas on the site for storage of materials. The Contractor shall be responsible for any security measures related to work in progress or storage of materials

1. Limits: Confine construction operations to those portions of the site for which work is indicated to take place. The Contractor may execute the work at any time during the construction period. This work must be coordinated with the Owner. All measures shall be taken to protect the health and safety of the residents during all work.
2. Resident Occupancy: Buildings turned over to the Contractor will be unoccupied. Allow for resident occupancy of other buildings on the site.
3. Driveways and Entrances: Keep driveways and entrances serving premises clear and available to Owner, Owner's employees, and emergency vehicles at all times. Do not use these areas for parking or storage of materials.
 - a. Schedule deliveries to minimize use of driveways and entrances.
 - b. Schedule deliveries to minimize space and time requirements for storage of materials and equipment on-site.

B. Use of Existing Buildings: Maintain existing buildings in a weathertight condition throughout construction period. Repair damage caused by construction operations. Protect building and its systems to remain during construction period.

1.3 OCCUPANCY REQUIREMENTS

A. Architect will prepare a Certificate of Substantial Completion for each specific portion of the Work to be occupied before Owner occupancy.

END OF SECTION 01140

**SECTION 01330
SUBMITTAL PROCEDURES**

PART 1 – GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 1 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes administrative and procedural requirements for submitting Shop Drawings, Product Data, Samples, and other miscellaneous submittals.

1.3 DEFINITIONS

- A. Action Submittals: Written and graphic information that requires Architect's and Owner's responsive action.
- B. Informational Submittals: Written information that does not require Architect's and Owner's approval. Submittals may be rejected for not complying with requirements.

1.4 SUBMITTAL PROCEDURES

- A. General: Electronic copies of CAD Drawings of the Contract Drawings **will not** be provided by Architect for Contractor's use in preparing submittals.
- B. Coordination: Coordinate preparation and processing of submittals with performance of construction activities.
 - 1. Coordinate each submittal with fabrication, purchasing, testing, delivery, other submittals, and related activities that require sequential activity.
 - 2. Coordinate transmittal of different types of submittals for related parts of the Work so processing will not be delayed because of need to review submittals concurrently for coordination.
 - a. Architect reserves the right to withhold action on a submittal requiring coordination with other submittals until related submittals are received.
- C. Submittals Schedule: Comply with requirements in Division 1 Section "Construction Progress Documentation" for list of submittals and time requirements for scheduled performance of related construction activities.
- D. Processing Time: Allow enough time for submittal review, including time for resubmittals, as follows. Time for review shall commence on Architect's receipt of submittal.
 - 1. Initial Review: Allow **10** days for initial review of each submittal. Allow additional time if processing must be delayed to permit coordination with subsequent submittals. Architect will advise Contractor when a submittal being processed must be delayed for coordination.
 - 2. Concurrent Review: Where concurrent review of submittals by Architect's consultants, Owner, or other parties is required, allow **14** days for initial review of each submittal.
 - 3. Direct Transmittal to Consultant: Where the Contract Documents indicate that submittals may be transmitted directly to Architect's consultants, provide duplicate copy of transmittal to Architect. Submittal will be returned to Architect before being returned to Contractor.
 - 4. If intermediate submittal is necessary, process it in same manner as initial submittal.
 - 5. Allow **14** days for processing each resubmittal.
 - 6. No extension of the Contract Time will be authorized because of failure to transmit submittals enough in advance of the Work to permit processing.
- E. Identification: Place a permanent label or title block on each submittal for identification.
 - 1. Indicate name of firm or entity that prepared each submittal on label or title block.
 - 2. Provide a space approximately 4 by 5 inches on label or beside title block to record Contractor's review and approval markings and action taken by Architect
 - 3. Include the following information on label for processing and recording action taken:

- a. Project name.
 - b. Date.
 - c. Name and address of Architect.
 - d. Name and address of Owner.
 - e. Name and address of Contractor.
 - f. Name and address of subcontractor.
 - g. Name and address of supplier.
 - h. Name of manufacturer.
 - i. Number and title of appropriate Specification Section.
 - j. Drawing number and detail references, as appropriate.
 - k. Other necessary identification.
- F. Deviations: Highlight, encircle, or otherwise identify deviations from the Contract Documents on submittals.
- G. Additional Copies: Unless additional copies are required for final submittal, and unless Architect observes noncompliance with provisions of the Contract Documents, initial submittal may serve as final submittal.
1. Submit one copy of submittal to concurrent reviewer in addition to specified number of copies to Architect. **(Six copies to Architect)**
- H. Transmittal: Package each submittal individually and appropriately for transmittal and handling. Transmit each submittal using a transmittal form. Architect will **return submittals, without review**, received from sources other than Contractor.
1. On an attached separate sheet, prepared on Contractor's letterhead, record relevant information, requests for data, revisions other than those requested by Architect on previous submittals, and deviations from requirements of the Contract Documents, including minor variations and limitations. Include the same label information as the related submittal.
 2. Include Contractor's certification stating that information submitted complies with requirements of the Contract Documents.
 3. Transmittal Form: Provide locations on form for the following information:
 - a. Project name.
 - b. Date.
 - c. Destination (To:).
 - d. Source (From:).
 - e. Names of subcontractor, manufacturer, and supplier.
 - f. Category and type of submittal.
 - g. Submittal purpose and description.
 - h. Submittal and transmittal distribution record.
 - i. Remarks.
 - j. Signature of transmitter.
- I. Distribution: Furnish copies of final submittals to manufacturers, subcontractors, suppliers, fabricators, installers, authorities having jurisdiction, and others as necessary for performance of construction activities. Show distribution on transmittal forms.
- J. Use for Construction: Use only final submittals with mark indicating action taken by Architect in connection with construction.

PART 2 – PRODUCTS

2.1 ACTION SUBMITTALS

- A. General: Prepare and submit Action Submittals required by individual Specification Sections.
1. Number of Copies: Submit **six** copies of each submittal, unless otherwise indicated. Architect will return **three** copies. Mark up and retain one returned copy as a Project Record Document.
- B. Product Data: Collect information into a single submittal for each element of construction and type of product or equipment.
1. If information must be specially prepared for submittal because standard printed data are

- not suitable for use, submit as Shop Drawings, not as Product Data.
2. Mark each copy of each submittal to show which products and options are applicable.
 3. Include the following information, as applicable:
 - a. Manufacturer's written recommendations.
 - b. Manufacturer's product specifications.
 - c. Manufacturer's installation instructions.
 - d. Standard color charts.
 - e. Manufacturer's catalog cuts.
 - f. Wiring diagrams showing factory-installed wiring.
 - g. Printed performance curves.
 - h. Operational range diagrams.
 - i. Mill reports.
 - j. Standard product operating and maintenance manuals.
 - k. Compliance with recognized trade association standards.
 - l. Compliance with recognized testing agency standards.
 - m. Application of testing agency labels and seals.
 - n. Notation of coordination requirements.
- C. Shop Drawings: Prepare Project-specific information, drawn accurately to scale. Do not base Shop Drawings on reproductions of the Contract Documents or standard printed data.
1. Preparation: Include the following information, as applicable:
 - a. Dimensions.
 - b. Identification of products.
 - c. Fabrication and installation drawings.
 - d. Roughing-in and setting diagrams.
 - e. Wiring diagrams showing field-installed wiring, including power, signal, and control wiring.
 - f. Shop-work manufacturing instructions.
 - g. Templates and patterns.
 - h. Schedules.
 - i. Design calculations.
 - j. Compliance with specified standards.
 - k. Notation of coordination requirements.
 - l. Notation of dimensions established by field measurement.
 2. Wiring Diagrams: Differentiate between manufacturer-installed and field-installed wiring.
 3. Sheet Size: Except for templates, patterns, and similar full-size drawings, submit Shop Drawings on sheets at least 8-1/2 by 11 inches.
 4. Number of Copies: Submit copies of each submittal, as follows:
 - a. Submittal: Submit **six** blue or black-line prints. Architect will return one print.
- D. Samples: Prepare physical units of materials or products, including the following:
1. Comply with requirements in Division 1 for mockups.
 2. Samples for Initial Selection: Submit manufacturer's color charts consisting of units or sections of units showing the full range of colors, textures, and patterns available.
 3. Samples for Verification: Submit full-size units or Samples of size indicated, prepared from the same material to be used for the Work, cured and finished in manner specified, and physically identical with the product proposed for use, and that show full range of color and texture variations expected. Samples include, but are not limited to, the following: partial sections of manufactured or fabricated components; small cuts or containers of materials; complete units of repetitively used materials; swatches showing color, texture, and pattern; color range sets; and components used for independent testing and inspection.
 4. Preparation: Mount, display, or package Samples in manner specified to facilitate review of qualities indicated. Prepare Samples to match Architect's sample where so indicated. Attach label on unexposed side that includes the following:
 - a. Generic description of Sample.

- b. Product name or name of manufacturer.
 - c. Sample source.
5. Additional Information: On an attached separate sheet, prepared on Contractor's letterhead, provide the following:
 - a. Size limitations.
 - b. Compliance with recognized standards.
 - c. Availability.
 - d. Delivery time.
6. Submit Samples for review of kind, color, pattern, and texture for a final check of these characteristics with other elements and for a comparison of these characteristics between final submittal and actual component as delivered and installed.
 - a. If variation in color, pattern, texture, or other characteristic is inherent in the product represented by a Sample, submit at least **six** sets of paired units that show approximate limits of the variations.
 - b. Refer to individual Specification Sections for requirements for Samples that illustrate workmanship, fabrication techniques, details of assembly, connections, operation, and similar construction characteristics.
7. Disposition: Maintain sets of approved Samples at Project site, available for quality-control comparisons throughout the course of construction activity. Sample sets may be used to determine final acceptance of construction associated with each set.
 - a. Samples that may be incorporated into the Work are indicated in individual Specification Sections. Such Samples must be in an undamaged condition at time of use.
- E. Subcontract List: Prepare a written summary identifying individuals or firms proposed for each portion of the Work, including those who are to furnish products or equipment fabricated to a special design. Include the following information in tabular form:
 1. Name, address, and telephone number of entity performing subcontract or supplying products.
 2. Number and title of related Specification Section(s) covered by subcontract.
 3. Drawing number and detail references, as appropriate, covered by subcontract.
- F. Material Test Reports: Prepare reports written by a qualified testing agency, on testing agency's standard form, indicating and interpreting test results of material for compliance with requirements.

PART 3 – EXECUTION

3.1 CONTRACTOR'S REVIEW

- A. Review each submittal and check for compliance with the Contract Documents. Note corrections and field dimensions. Mark with approval stamp before submitting to Architect
- B. Approval Stamp: Stamp each submittal with a uniform, approval stamp. Include Project name and location, submittal number, Specification Section title and number, name of reviewer, date of Contractor's approval, and statement certifying that submittal has been reviewed, checked, and approved for compliance with the Contract Documents.

3.2 ARCHITECT'S ACTION

- A. General: Architect will not review submittals that do not bear Contractor's approval stamp and will return them without action.
- B. Action Submittals: Architect will review each submittal, make marks to indicate corrections or modifications required, and return it. Architect will stamp each submittal with an action stamp and will mark stamp appropriately to indicate action taken.
- C. Informational Submittals: Architect will review each submittal and will not return it, or will reject and return it if it does not comply with requirements. Architect will forward each submittal to appropriate party.
- D. Submittals not required by the Contract Documents will not be reviewed and may be discarded.

END OF SECTION 01330

**SECTION 01400
QUALITY REQUIREMENTS**

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 1 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes administrative and procedural requirements for quality assurance and quality control.
- B. Testing and inspecting services are required to verify compliance with requirements specified or indicated. These services do not relieve Contractor of responsibility for compliance with the Contract Document requirements.
 - 1. Specific quality-control requirements for individual construction activities are specified in the Sections that specify those activities. Requirements in those Sections may also cover production of standard products.
 - 2. Specified tests, inspections, and related actions do not limit Contractor's quality-control procedures that facilitate compliance with the Contract Document requirements.
 - 3. Requirements for Contractor to provide quality-control services required by Architect, Owner, or authorities having jurisdiction are not limited by provisions of this Section.
- C. Related Sections include the following:
 - 1. Division 1 Section "Construction Progress Documentation" for developing a schedule of required tests and inspections.
 - 2. Division 1 Section "Cutting and Patching" for repair and restoration of construction disturbed by testing and inspecting activities.
 - 3. Divisions 2 through 8 Sections for specific test and inspection requirements.

1.3 DEFINITIONS

- A. Quality-Assurance Services: Activities, actions, and procedures performed before and during execution of the Work to guard against defects and deficiencies and ensure that proposed construction complies with requirements.
- B. Quality-Control Services: Tests, inspections, procedures, and related actions during and after execution of the Work to evaluate that completed construction complies with requirements. Services do not include contract enforcement activities performed by Architect.
- C. Mockups: Full-size, physical example assemblies to illustrate finishes and materials. Mockups are used to verify selections made under Sample submittals, to demonstrate aesthetic effects and, where indicated, qualities of materials and execution, and to review construction, coordination, testing, or operation; they are not Samples. Mockups establish the standard by which the Work will be judged.
- D. Testing Agency: An entity engaged to perform specific tests, inspections, or both. Testing laboratory shall mean the same as testing agency.

1.4 SUBMITTALS

- A. Qualification Data: For testing agencies specified in "Quality Assurance" Article to demonstrate their capabilities and experience. Include proof of qualifications in the form of a recent report on the inspection of the testing agency by a recognized authority.
- B. Schedule of Tests and Inspections: Prepare in tabular form and include the following:
 - 1. Specification Section number and title.
 - 2. Description of test and inspection.
 - 3. Identification of applicable standards.
 - 4. Identification of test and inspection methods.
 - 5. Number of tests and inspections required.
 - 6. Time schedule or time span for tests and inspections.

7. Entity responsible for performing tests and inspections.
 8. Requirements for obtaining samples.
 9. Unique characteristics of each quality-control service.
 - C. Reports: Prepare and submit certified written reports that include the following:
 1. Date of issue.
 2. Project title and number.
 3. Name, address, and telephone number of testing agency.
 4. Dates and locations of samples and tests or inspections.
 5. Names of individuals making tests and inspections.
 6. Description of the Work and test and inspection method.
 7. Identification of product and Specification Section.
 8. Complete test or inspection data.
 9. Test and inspection results and an interpretation of test results.
 10. Ambient conditions at time of sample taking and testing and inspecting.
 11. Name and signature of laboratory inspector.
 12. Recommendations on retesting and re-inspecting.
 - D. Permits, Licenses, and Certificates: For Owner's records, submit copies of permits, licenses, certifications, inspection reports, releases, jurisdictional settlements, notices, receipts for fee payments, judgments, correspondence, records, and similar documents, established for compliance with standards and regulations bearing on performance of the Work.
- 1.5 QUALITY ASSURANCE
- A. Fabricator Qualifications: A firm experienced in producing products similar to those indicated for this Project and with a record of successful in-service performance, as well as sufficient production capacity to produce required units.
 - B. Factory-Authorized Service Representative Qualifications: An authorized representative of manufacturer who is trained and approved by manufacturer to inspect installation of manufacturer's products that are similar in material, design, and extent to those indicated for this Project.
 - C. Installer Qualifications: A firm or individual experienced in installing, erecting, or assembling work similar in material, design, and extent to that indicated for this Project, whose work has resulted in construction with a record of successful in-service performance. Specialists: Certain sections of the Specifications require that specific construction activities shall be performed by entities who are recognized experts in those operations. Specialists shall satisfy qualification requirements indicated and shall be engaged for the activities indicated.
 1. Requirement for specialists shall not supersede building codes and similar regulations governing the Work, nor interfere with local trade-union jurisdictional settlements and similar conventions.
 - D. Testing Agency Qualifications: An agency with the experience and capability to conduct testing and inspecting indicated, as documented by ASTM E 548, and that specializes in types of tests and inspections to be performed.
 - E. Mockups: Before installing portions of the Work requiring mockups, build mockups for each form of construction and finish required to comply with the following requirements, using materials indicated for the completed Work:
 1. Build mockups in location and of size indicated or, if not indicated, as directed by Architect.
 2. Notify Architect **seven** days in advance of dates and times when mockups will be constructed.
 3. Demonstrate the proposed range of aesthetic effects and workmanship.
 4. Obtain Architect's approval of mockups before starting work, fabrication, or construction.
 5. Maintain mockups during construction in an undisturbed condition as a standard for judging the completed Work.
 6. Demolish and remove mockups when directed, unless otherwise indicated.
- 1.6 QUALITY CONTROL
- A. Contractor Responsibilities: Unless otherwise indicated, provide quality-control services specified and required by authorities having jurisdiction.

1. Where services are indicated as Contractor's responsibility, engage a qualified testing agency to perform these quality-control services.
 2. Notify testing agencies at least **24** hours in advance of time when Work that requires testing or inspecting will be performed.
 3. Where quality-control services are indicated as Contractor's responsibility, submit a certified written report, in duplicate, of each quality-control service.
 4. Testing and inspecting requested by Contractor and not required by the Contract Documents are Contractor's responsibility.
 5. Submit additional copies of each written report directly to authorities having jurisdiction, when they so direct.
- B. **Manufacturer's Field Services:** Where indicated, engage a factory-authorized service representative to inspect field-assembled components and equipment installation, including service connections. Report results in writing.
- C. **Retesting/Re-inspecting:** Regardless of whether original tests or inspections were Contractor's responsibility, provide quality-control services, including retesting and re-inspecting, for construction that revised or replaced Work that failed to comply with requirements established by the Contract Documents.
- D. **Testing Agency Responsibilities:** Cooperate with Architect and Contractor in performance of duties. Provide qualified personnel to perform required tests and inspections.
1. Notify Architect and Contractor promptly of irregularities or deficiencies observed in the Work during performance of its services.
 2. Interpret tests and inspections and state in each report whether tested and inspected work complies with or deviates from requirements.
 3. Submit a certified written report, in duplicate, of each test, inspection, and similar quality-control service through Contractor.
 4. Do not release, revoke, alter, or increase requirements of the Contract Documents or approve or accept any portion of the Work.
 5. Do not perform any duties of Contractor.
- E. **Associated Services:** Cooperate with agencies performing required tests, inspections, and similar quality-control services, and provide reasonable auxiliary services as requested. Notify agency sufficiently in advance of operations to permit assignment of personnel. Provide the following:
1. Access to the Work.
 2. Incidental labor and facilities necessary to facilitate tests and inspections.
 3. Adequate quantities of representative samples of materials that require testing and inspecting. Assist agency in obtaining samples.
 4. Facilities for storage and field-curing of test samples.
 5. Delivery of samples to testing agencies.
 6. Preliminary design mix proposed for use for material mixes that require control by testing agency.
 7. Security and protection for samples and for testing and inspecting equipment at Project site.
- F. **Coordination:** Coordinate sequence of activities to accommodate required quality-assurance and quality-control services with a minimum of delay and to avoid necessity of removing and replacing construction to accommodate testing and inspecting.
1. Schedule times for tests, inspections, obtaining samples, and similar activities.
- G. **Schedule of Tests and Inspections:** Prepare a schedule of tests, inspections, and similar quality-control services required by the Contract Documents. Submit schedule within **30** days of date established for the Notice to Proceed.
1. **Distribution:** Distribute schedule to Owner, Architect, testing agencies, and each party involved in performance of portions of the Work where tests and inspections are required.

PART 2 - PRODUCTS - (Not Applicable)

PART 3 - EXECUTION

3.1 REPAIR AND PROTECTION

- A. General: On completion of testing, inspecting, sample taking, and similar services, repair damaged construction and restore substrates and finishes.
 - 1. Provide materials and comply with installation requirements specified in other Sections of these Specifications. Restore patched areas and extend restoration into adjoining areas in a manner that eliminates evidence of patching.
 - 2. Comply with the Contract Document requirements for Division 1 Section "Cutting and Patching."
- B. Protect construction exposed by or for quality-control service activities.
- C. Repair and protection are Contractor's responsibility, regardless of the assignment of responsibility for quality-control services.

END OF SECTION 01400

**SECTION 01600
PRODUCT REQUIREMENTS**

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 1 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes the following administrative and procedural requirements: selection of products for use in Project; product delivery, storage, and handling; manufacturers' standard warranties on products; special warranties; product substitutions; and comparable products.
- B. Related Sections include the following:
 - 1. Division 1 Section "Alternates" for products selected under an alternate.
 - 2. Division 1 Section "References" for applicable industry standards for products specified.
 - 3. Division 1 Section "Closeout Procedures" for submitting warranties for contract closeout.
 - 4. Divisions 2 through 8 Sections for specific requirements for warranties on products and installations specified to be warranted.

1.3 DEFINITIONS

- A. Products: Items purchased for incorporating into the Work, whether purchased for Project or taken from previously purchased stock. The term "product" includes the terms "material," "equipment," "system," and terms of similar intent.
 - 1. Named Products: Items identified by manufacturer's product name, including make or model number or other designation, shown or listed in manufacturer's published product literature, which is current as of date of the Contract Documents.
 - 2. New Products: Items that have not previously been incorporated into another project or facility. Products salvaged or recycled from other projects are not considered new products.
 - 3. Comparable Product: Product that is demonstrated and approved through submittal process, or where indicated as a product substitution, to have the indicated qualities related to type, function, dimension, in-service performance, physical properties, appearance, and other characteristics that equal or exceed those of specified product.
- B. Substitutions: Changes in products, materials, equipment, and methods of construction from those required by the Contract Documents and proposed by Contractor.
- C. Basis-of-Design Product Specification: Where a specific manufacturer's product is named and accompanied by the words "basis of design," including make or model number or other designation, to establish the significant qualities related to type, function, dimension, in-service performance, physical properties, appearance, and other characteristics for purposes of evaluating comparable products of other named manufacturers.
- D. Manufacturer's Warranty: Preprinted written warranty published by individual manufacturer for a particular product and specifically endorsed by manufacturer to Owner.
- E. Special Warranty: Written warranty required by or incorporated into the Contract Documents, either to extend time limit provided by manufacturer's warranty or to provide more rights for Owner.

1.4 SUBMITTALS

- A. Product List: Submit a list, in tabular form, showing specified products. Include generic names of products required. Include manufacturer's name and proprietary product names for each product.
 - 1. Coordinate product list with Contractor's Construction Schedule and the Submittals Schedule.
 - 2. Form: Tabulate information for each product under the following column headings:
 - a. Specification Section number and title.
 - b. Generic name used in the Contract Documents.
 - c. Proprietary name, model number, and similar designations.
 - d. Manufacturer's name and address.
 - e. Supplier's name and address.

- f. Installer's name and address.
 - g. Projected delivery date or time span of delivery period.
 - h. Identification of items that require early submittal approval for scheduled delivery date.
 3. Initial Submittal: Within **21** days after date of commencement of the Work, submit **2** copies of initial product list. Include a written explanation for omissions of data and for variations from Contract requirements.
 - a. At Contractor's option, initial submittal may be limited to product selections and designations that must be established early in Contract period.
 4. Completed List: Within **30** days after date of commencement of the Work, submit **6** copies of completed product list. Include a written explanation for omissions of data and for variations from Contract requirements.
 5. Architect's Action: Architect will respond in writing to Contractor within **15** days of receipt of completed product list. Architect's response will include a list of unacceptable product selections and a brief explanation of reasons for this action. Architect's response, or lack of response, does not constitute a waiver of requirement that products comply with the Contract Documents.
 - B. Requests for Approved Equals: **All requests for materials to be considered as an approved equal must be submitted within 10 days prior to bid. No substitutions shall be considered after this deadline.** Submit three copies of each request for consideration. Identify product or fabrication or installation method to be replaced. Include Specification Section number and title and Drawing numbers and titles.
 1. Documentation: Show compliance with requirements for substitutions and the following, as applicable:
 - a. Detailed comparison of significant qualities of proposed substitution with those of the Work specified. Significant qualities may include attributes such as performance, weight, size, durability, visual effect, and specific features and requirements indicated.
 - b. Product Data, including drawings and descriptions of products and fabrication and installation procedures.
 - c. Samples, where applicable or requested.
 - d. Contractor's certification that proposed substitution complies with requirements in the Contract Documents and is appropriate for applications indicated.
 2. Architect's Action: Architect will issue an Addendum no later than seven days prior to the Bid Date to address all Approved Equals.
 - a. Use product specified if a proposed substitution is not approved by Addendum.
 - C. Basis-of-Design Product Specification Submittal: Comply with requirements in Division 1 Section "Submittal Procedures." Show compliance with requirements.
- 1.5 QUALITY ASSURANCE
 - A. Compatibility of Options: If Contractor is given option of selecting between two or more products for use on Project, product selected shall be compatible with products previously selected, even if previously selected products were also options.
 1. Each contractor is responsible for providing products and construction methods compatible with products and construction methods of other contractors.
 2. If a dispute arises between contractors over concurrently selectable but incompatible products, Architect will determine which products shall be used.
- 1.6 PRODUCT DELIVERY, STORAGE, AND HANDLING
 - A. Deliver, store, and handle products using means and methods that will prevent damage, deterioration, and loss, including theft. Comply with manufacturer's written instructions.
 1. Schedule delivery to minimize long-term storage at Project site and to prevent overcrowding of construction spaces.
 2. Coordinate delivery with installation time to ensure minimum holding time for items that are flammable, hazardous, easily damaged, or sensitive to deterioration, theft, and other losses.
 3. Deliver products to Project site in an undamaged condition in manufacturer's original sealed container or other packaging system, complete with labels and instructions for handling,

- storing, unpacking, protecting, and installing.
 - 4. Inspect products on delivery to ensure compliance with the Contract Documents and to ensure that products are undamaged and properly protected.
 - 5. Store products to allow for inspection and measurement of quantity or counting of units.
 - 6. Store materials in a manner that will not endanger Project structure.
 - 7. Store products that are subject to damage by the elements, under cover in a weathertight enclosure above ground, with ventilation adequate to prevent condensation.
 - 8. Comply with product manufacturer's written instructions for temperature, humidity, ventilation, and weather-protection requirements for storage.
 - 9. Protect stored products from damage.
 - B. Storage: Provide a secure location and enclosure at Project site for storage of materials and equipment by construction forces. Coordinate location with Owner.
- 1.7 PRODUCT WARRANTIES
- A. Warranties specified in other Sections shall be in addition to, and run concurrent with, other warranties required by the Contract Documents. Manufacturer's disclaimers and limitations on product warranties do not relieve Contractor of obligations under requirements of the Contract Documents.
 - B. Special Warranties: Prepare a written document that contains appropriate terms and identification, ready for execution. Submit a draft for approval before final execution.
 - 1. Manufacturer's Standard Form: Modified to include Project-specific information and properly executed.
 - 2. Refer to Divisions 2 through 8 Sections for specific content requirements and particular requirements for submitting special warranties.
 - C. Submittal Time: Comply with requirements in Division 1 Section "Closeout Procedures."

PART 2 - PRODUCTS

2.1 PRODUCT OPTIONS

- A. General Product Requirements: Provide products that comply with the Contract Documents, that are undamaged, and unless otherwise indicated, that are new at time of installation.
 - 1. Provide products complete with accessories, trim, finish, fasteners, and other items needed for a complete installation and indicated use and effect.
 - 2. Standard Products: If available, and unless custom products or nonstandard options are specified, provide standard products of types that have been produced and used successfully in similar situations on other projects.
 - 3. Owner reserves the right to limit selection to products with warranties not in conflict with requirements of the Contract Documents.
 - 4. Where products are accompanied by the term "as selected," Architect will make selection.
 - 5. Where products are accompanied by the term "match sample," sample to be matched is Architect's.
 - 6. Descriptive, performance, and reference standard requirements in the Specifications establish "salient characteristics" of products.
 - 7. Or Equal: Where products are specified by name and accompanied by the term "or equal" or "or approved equal" or "or approved," comply with provisions in "Request for Approved Equals" Article to obtain approval for use of an unnamed product.
- B. Product Selection Procedures: Procedures for product selection include the following:
 - 1. Product: Where Specification paragraphs or subparagraphs titled "Product" name a single product and manufacturer followed by "or approved equal", provide the product named or a substitution that has been approved by Addendum prior to Bid..
 - a. Substitutions will not be considered unless specifically approved by Addendum.
 - 2. Manufacturer/Source: Where Specification paragraphs or subparagraphs titled "Manufacturer" or "Source" name single manufacturers or sources, provide a product by the manufacturer or from the source named that complies with requirements unless other manufacturers or sources have been approved by Addendum prior to Bid.
 - a. Substitutions will not be considered unless specifically approved by Addendum.

3. Products: Where Specification paragraphs or subparagraphs titled "Products" introduce a list of names of both products and manufacturers, provide one of the products listed that complies with requirements.
 - a. Substitutions will not be considered unless specifically approved by Addendum.
4. Manufacturers: Where Specification paragraphs or subparagraphs titled "Manufacturers" introduce a list of manufacturers' names, provide a product by one of the manufacturers listed that complies with requirements.
 - a. Substitutions will not be considered unless specifically approved by Addendum..
5. Visual Matching Specification: Where Specifications require matching an established Sample, select a product (and manufacturer) that complies with requirements and matches Architect's sample. Architect's decision will be final on whether a proposed product matches satisfactorily.
6. Visual Selection Specification: Where Specifications include the phrase "as selected from manufacturer's colors, patterns, textures" or a similar phrase, select a product (and manufacturer) that complies with other specified requirements.
 - a. Standard Range: Where Specifications include the phrase "standard range of colors, patterns, textures" or similar phrase, Architect will select color, pattern, or texture from manufacturer's product line that does not include premium items.
 - b. Full Range: Where Specifications include the phrase "full range of colors, patterns, textures" or similar phrase, Architect will select color, pattern, or texture from manufacturer's product line that includes both standard and premium items.

2.2 PRODUCT SUBSTITUTIONS

- A. Timing: Architect will consider requests for substitution or "approved equals" if received within **10 days prior to the bid date**. Requests received after this time may be considered or rejected at discretion of Architect.
- B. Conditions: Architect will consider Contractor's request for substitution when the following conditions are satisfied. If the following conditions are not satisfied, Architect will return requests without action, except to record noncompliance with these requirements:
 1. Requested substitution does not require extensive revisions to the Contract Documents.
 2. Requested substitution is consistent with the Contract Documents and will produce indicated results.
 3. Substitution request is fully documented and properly submitted.
 4. Requested substitution has been coordinated with other portions of the Work.
 5. Requested substitution provides specified warranty.
 6. If requested substitution involves more than one contractor, requested substitution has been coordinated with other portions of the Work, is uniform and consistent, is compatible with other products, and is acceptable to all contractors involved.
 7. Request is received by the Architect within **10 days prior to the Bid Date**.

2.3 COMPARABLE PRODUCTS

- A. Where products or manufacturers are specified by name, submit the following, in addition to other required submittals, to obtain approval of an unnamed product. **All requests for materials to be considered as an approved equal must be submitted within 10 days prior to bid. No substitutions shall be considered after this deadline.**
 1. Evidence that the proposed product does not require extensive revisions to the Contract Documents, that it is consistent with the Contract Documents, and will produce the indicated results, and that it is compatible with other portions of the Work.
 2. Detailed comparison of significant qualities of proposed product with those named in the Specifications. Significant qualities include attributes such as performance, weight, size, durability, visual effect, and specific features and requirements indicated.
 3. Evidence that proposed product provides specified warranty.
 4. Samples, if requested.

PART 3 - EXECUTION - (Not Applicable)

END OF SECTION 01600

**SECTION 01700
EXECUTION REQUIREMENTS**

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 1 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes general procedural requirements governing execution of the Work including, but not limited to, the following:
 - 1. Construction layout.
 - 2. Field engineering and surveying.
 - 3. General installation of products.
 - 4. Progress cleaning.
 - 5. Starting and adjusting.
 - 6. Protection of installed construction.
 - 7. Correction of the Work.
- B. Related Sections include the following:
 - 1. Division 1 Section "Project Management and Coordination" for procedures for coordinating field engineering with other construction activities.
 - 2. Division 1 Section "Submittal Procedures" for submitting surveys.
 - 3. Division 1 Section "Cutting and Patching" for procedural requirements for cutting and patching necessary for the installation or performance of other components of the Work.

PART 2 - PRODUCTS (Not Used)

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Existing Conditions: The existence and location of site improvements, utilities, and other construction indicated as existing are not guaranteed. Before beginning work, investigate and verify the existence and location of mechanical and electrical systems and other construction affecting the Work.
 - 1. Before construction, verify the location and points of connection of utility services.
- B. Existing Utilities: The existence and location of underground and other utilities and construction indicated as existing are not guaranteed. Before beginning site work, investigate and verify the existence and location of underground utilities and other construction affecting the Work.
 - 1. Before construction, verify the location and invert elevation at points of connection of sanitary sewer, storm sewer, and water-service piping; and underground electrical services.
- C. Acceptance of Conditions: Examine substrates, areas, and conditions, with Installer or Applicator present where indicated, for compliance with requirements for installation tolerances and other conditions affecting performance. Record observations.
 - 1. Verify compatibility with and suitability of substrates, including compatibility with existing finishes or primers.
 - 2. Examine roughing-in for mechanical and electrical systems to verify actual locations of connections before equipment and fixture installation.
 - 3. Examine walls, floors, and roofs for suitable conditions where products and systems are to be installed.
 - 4. Proceed with installation only after unsatisfactory conditions have been corrected. Proceeding with the Work indicates acceptance of surfaces and conditions.

3.2 PREPARATION

- A. Existing Utility Information: Furnish information to Owner that is necessary to adjust, move, or relocate existing utility structures, utility poles, lines, services, or other utility appurtenances located in or affected by construction. Coordinate with authorities having jurisdiction.
- B. Existing Utility Interruptions: Do not interrupt utilities serving facilities occupied by Owner or others unless permitted under the following conditions and then only after arranging to provide temporary utility services according to requirements indicated:
 - 1. Notify Architect and Owner not less than two days in advance of proposed utility interruptions.
 - 2. Do not proceed with utility interruptions without Owner's written permission.
- C. Field Measurements: Take field measurements as required to fit the Work properly. Recheck measurements before installing each product. Where portions of the Work are indicated to fit to other construction, verify dimensions of other construction by field measurements before fabrication. Coordinate fabrication schedule with construction progress to avoid delaying the Work.
- D. Space Requirements: Verify space requirements and dimensions of items shown diagrammatically on Drawings.
- E. Review of Contract Documents and Field Conditions: Immediately on discovery of the need for clarification of the Contract Documents, submit a request for information to Architect. Include a detailed description of problem encountered, together with recommendations for changing the Contract Documents. **Submit requests on CSI Form 13.2A, "Request for Interpretation."**

3.3 CONSTRUCTION LAYOUT

- A. Verification: Before proceeding to lay out the Work, verify layout information shown on Drawings, in relation to the property survey and existing benchmarks. If discrepancies are discovered, notify Architect promptly.
- B. General: Engage a land surveyor (if required) to lay out the Work using accepted surveying practices.
 - 1. Establish benchmarks and control points to set lines and levels at each story of construction and elsewhere as needed to locate each element of Project.
 - 2. Establish dimensions within tolerances indicated. Do not scale Drawings to obtain required dimensions.
 - 3. Inform installers of lines and levels to which they must comply.
 - 4. Check the location, level and plumb, of every major element as the Work progresses.
 - 5. Notify Architect when deviations from required lines and levels exceed allowable tolerances.
 - 6. Close site surveys with an error of closure equal to or less than the standard established by authorities having jurisdiction.
- C. Site Improvements: Locate and lay out site improvements, including pavements, grading, fill and topsoil placement, utility slopes, and invert elevations.
- D. Building Lines and Levels: Locate and lay out control lines and levels for structures, building foundations, column grids, and floor levels, including those required for mechanical and electrical work. Transfer survey markings and elevations for use with control lines and levels. Level foundations and piers from two or more locations.
- E. Record Log: Maintain a log of layout control work. Record deviations from required lines and levels. Include beginning and ending dates and times of surveys, weather conditions, name and duty of each survey party member, and types of instruments and tapes used. Make the log available for reference by Architect.

3.4 FIELD ENGINEERING

- A. Reference Points: Locate existing permanent benchmarks, control points, and similar reference points before beginning the Work. Preserve and protect permanent benchmarks and control points during construction operations.
 - 1. Do not change or relocate existing benchmarks or control points without prior written approval of Architect. Report lost or destroyed permanent benchmarks or control points

promptly. Report the need to relocate permanent benchmarks or control points to Architect before proceeding.

2. Replace lost or destroyed permanent benchmarks and control points promptly. Base replacements on the original survey control points.

3.5 INSTALLATION

- A. General: Locate the Work and components of the Work accurately, in correct alignment and elevation, as indicated.
 1. Make vertical work plumb and make horizontal work level.
 2. Where space is limited, install components to maximize space available for maintenance and ease of removal for replacement.
 3. Conceal pipes, ducts, and wiring in finished areas, unless otherwise indicated.
- B. Comply with manufacturer's written instructions and recommendations for installing products in applications indicated.
- C. Install products at the time and under conditions that will ensure the best possible results. Maintain conditions required for product performance until Substantial Completion.
- D. Conduct construction operations so no part of the Work is subjected to damaging operations or loading in excess of that expected during normal conditions of occupancy.
- E. Tools and Equipment: Do not use tools or equipment that produce harmful noise levels.
- F. Anchors and Fasteners: Provide anchors and fasteners as required to anchor each component securely in place, accurately located and aligned with other portions of the Work.
 1. Mounting Heights: Where mounting heights are not indicated, mount components at heights directed by Architect.
 2. Allow for building movement, including thermal expansion and contraction.
- G. Joints: Make joints of uniform width. Where joint locations in exposed work are not indicated, arrange joints for the best visual effect. Fit exposed connections together to form hairline joints.
- H. Hazardous Materials: Use products, cleaners, and installation materials that are not considered hazardous.

3.6 PROGRESS CLEANING

- A. General: Clean Project site and work areas daily, including common areas. Coordinate progress cleaning for joint-use areas where more than one installer has worked. Enforce requirements strictly. Dispose of materials lawfully.
 1. Comply with requirements in NFPA 241 for removal of combustible waste materials and debris.
 2. Do not hold materials more than 7 days during normal weather or 3 days if the temperature is expected to rise above 80 deg F.
 3. Containerize hazardous and unsanitary waste materials separately from other waste. Mark containers appropriately and dispose of legally, according to regulations.
- B. Site: Maintain Project site free of waste materials and debris.
- C. Work Areas: Clean areas where work is in progress to the level of cleanliness necessary for proper execution of the Work.
 1. Remove liquid spills promptly.
 2. Where dust would impair proper execution of the Work, broom-clean or vacuum the entire work area, as appropriate.
- D. Installed Work: Keep installed work clean. Clean installed surfaces according to written instructions of manufacturer or fabricator of product installed, using only cleaning materials specifically recommended. If specific cleaning materials are not recommended, use cleaning materials that are not hazardous to health or property and that will not damage exposed surfaces.
- E. Concealed Spaces: Remove debris from concealed spaces before enclosing the space.
- F. Exposed Surfaces: Clean exposed surfaces and protect as necessary to ensure freedom from damage and deterioration at time of Substantial Completion.
- G. Cutting and Patching: Clean areas and spaces where cutting and patching are performed. Completely remove paint, mortar, oils, putty, and similar materials.

1. Thoroughly clean piping, conduit, and similar features before applying paint or other finishing materials. Restore damaged pipe covering to its original condition.
 - H. Waste Disposal: Burying or burning waste materials on-site will not be permitted. Washing waste materials down sewers or into waterways will not be permitted.
 - I. During handling and installation, clean and protect construction in progress and adjoining materials already in place. Apply protective covering where required to ensure protection from damage or deterioration at Substantial Completion.
 - J. Clean and provide maintenance on completed construction as frequently as necessary through the remainder of the construction period. Adjust and lubricate operable components to ensure operability without damaging effects.
 - K. Limiting Exposures: Supervise construction operations to assure that no part of the construction, completed or in progress, is subject to harmful, dangerous, damaging, or otherwise deleterious exposure during the construction period.
- 3.7 STARTING AND ADJUSTING
- A. Start equipment and operating components to confirm proper operation. Remove malfunctioning units, replace with new units, and retest.
 - B. Adjust operating components for proper operation without binding. Adjust equipment for proper operation.
 - C. Test each piece of equipment to verify proper operation. Test and adjust controls and safeties. Replace damaged and malfunctioning controls and equipment.
 - D. Manufacturer's Field Service: If a factory-authorized service representative is required to inspect field-assembled components and equipment installation, comply with qualification requirements in Division 1 Section "Quality Requirements."
- 3.8 PROTECTION OF INSTALLED CONSTRUCTION
- A. Provide final protection and maintain conditions that ensure installed Work is without damage or deterioration at time of Substantial Completion.
 - B. Comply with manufacturer's written instructions for temperature and relative humidity.
- 3.9 CORRECTION OF THE WORK
- A. Repair or remove and replace defective construction. Restore damaged substrates and finishes. Comply with requirements in Division 1 Section "Cutting and Patching."
 1. Repairing includes replacing defective parts, refinishing damaged surfaces, touching up with matching materials, and properly adjusting operating equipment.
 - B. Restore permanent facilities used during construction to their specified condition.
 - C. Remove and replace damaged surfaces that are exposed to view if surfaces cannot be repaired without visible evidence of repair.
 - D. Repair components that do not operate properly. Remove and replace operating components that cannot be repaired.
 - E. Remove and replace chipped, scratched, and broken glass or reflective surfaces.

END OF SECTION 01700

**SECTION 01710
PROJECT CLOSEOUT**

PART 1 - GENERAL

1.1 REQUIREMENTS

- A. Drawings and general provisions of contract, including General and Supplementary Conditions and Division 1 Specification sections, apply to work of this section.

1.2 DESCRIPTION OF CLOSEOUT DOCUMENTS

- A. Prior to approval of final payment on this project the following will be required by the Owner:
1. Six (6) "Periodic Estimate for Partial Payment" forms each complete with original signatures and notarized. Type "Final Payment" at the top of the form.
 2. Three (3) copies of "Certificate of Substantial Completion" form.
 3. Three (3) copies of final certification of completion ("Field Observation Report" indicating no non-conformance).
 4. Four (4) original "Guarantees and Warranties" with original signatures in accordance with Contract Specifications.
 5. Four (4) copies of Certificate of Insurance covering the Warranty period.
 6. Four (4) copies of final acceptance by the local inspection department.
 7. Four (4) copies of "Contractors Affidavit of Payment of Debts and Claims" (if applicable).
 8. One (1) notarized original and two (2) copies of the "Certificate and Release".
 9. Three (3) originals of Certified Proof of Advertisement of Completion - each notarized with original signatures.
 10. One (1) blueline print of all "as-built" drawings.
 11. One (1) copies of bound specifications to include all changes and addenda; signed, dated and marked "as-built".

Label the back spine and front cover of the binders with the project name, project number and date. NOTE: These binders are to be supplied within 7 days of the date of Substantial Completion.

Do not submit close-out documents piecemeal. Assemble everything required before forwarding to the Architect.

END OF SECTION 01710

**SECTION 01731
CUTTING AND PATCHING**

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 1 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes procedural requirements for cutting and patching.
- B. Related Sections include the following:
 - 1. Division 1 Section "Selective Demolition" for demolition of selected portions of the building for alterations.
 - 2. Divisions 2 through 16 Sections for specific requirements and limitations applicable to cutting and patching individual parts of the Work.

1.3 DEFINITIONS

- A. Cutting: Removal of existing construction necessary to permit installation or performance of other Work.
- B. Patching: Fitting and repair work required to restore surfaces to original conditions after installation of other Work.

1.4 SUBMITTALS

- A. Cutting and Patching Proposal: Submit a proposal describing procedures at least 10 days before the time cutting and patching will be performed, requesting approval to proceed. Include the following information:
 - 1. Utilities: List utilities that cutting and patching procedures will disturb or affect. List utilities that will be relocated and those that will be temporarily out of service. Indicate how long service will be disrupted.
 - 2. Structural Elements: Where cutting and patching involve adding reinforcement to structural elements, submit details and engineering calculations showing integration of reinforcement with original structure.
 - 3. Architect's Approval: Obtain approval of cutting and patching proposal before cutting and patching. Approval does not waive right to later require removal and replacement of unsatisfactory work.

1.5 QUALITY ASSURANCE

- A. Structural Elements: Do not cut and patch structural elements in a manner that could change their load-carrying capacity or load-deflection ratio.
- B. Visual Requirements: Do not cut and patch construction in a manner that results in visual evidence of cutting and patching. Do not cut and patch construction exposed on the exterior or in occupied spaces in a manner that would, in Architect's opinion, reduce the building's aesthetic qualities. Remove and replace construction that has been cut and patched in a visually unsatisfactory manner.
- C. Cutting and Patching Conference: Before proceeding, meet at Project site with parties involved in cutting and patching, including mechanical and electrical trades. Review areas of potential interference and conflict. Coordinate procedures and resolve potential conflicts before proceeding.

PART 2 - PRODUCTS

2.1 MATERIALS

- A. General: Comply with requirements specified in other Sections of these Specifications.
- B. Existing Materials: Use materials identical to existing materials. For exposed surfaces, use

materials that visually match existing adjacent surfaces to the fullest extent possible.

1. If identical materials are unavailable or cannot be used, use materials that, when installed, will match the visual and functional performance of existing materials.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine surfaces to be cut and patched and conditions under which cutting and patching are to be performed.
 1. Compatibility: Before patching, verify compatibility with and suitability of substrates, including compatibility with existing finishes or primers.
 2. Proceed with installation only after unsafe or unsatisfactory conditions have been corrected.

3.2 PREPARATION

- A. Temporary Support: Provide temporary support of Work to be cut.
- B. Protection: Protect existing construction during cutting and patching to prevent damage. Provide protection from adverse weather conditions for portions of Project that might be exposed during cutting and patching operations.
- C. Adjoining Areas: Avoid interference with use of adjoining areas or interruption of free passage to adjoining areas.
- D. Existing Services: Where existing services are required to be removed, relocated, or abandoned, bypass such services before cutting to avoid interruption of services to occupied units.

3.3 PERFORMANCE

- A. General: Employ skilled workers to perform cutting and patching. Proceed with cutting and patching at the earliest feasible time, and complete without delay.
 1. Cut existing construction to provide for installation of other components or performance of other construction, and subsequently patch as required to restore surfaces to their original condition.
- B. Cutting: Cut existing construction by sawing, drilling, breaking, chipping, grinding, and similar operations, including excavation, using methods least likely to damage elements retained or adjoining construction. If possible, review proposed procedures with original Installer; comply with original Installer's written recommendations.
 1. In general, use hand or small power tools designed for sawing and grinding, not hammering and chopping. Cut holes and slots as small as possible, neatly to size required, and with minimum disturbance of adjacent surfaces. Temporarily cover openings when not in use.
 2. Existing Finished Surfaces: Cut or drill from the exposed or finished side into concealed surfaces.
 3. Concrete and Masonry: Cut using a cutting machine, such as an abrasive saw or a diamond-core drill.
 4. Excavating and Backfilling: Comply with requirements in applicable Division 2 Sections where required by cutting and patching operations.
 5. Mechanical and Electrical Services: Cut off pipe or conduit in walls or partitions to be removed. Cap, valve, or plug and seal remaining portion of pipe or conduit to prevent entrance of moisture or other foreign matter after cutting.
 6. Proceed with patching after construction operations requiring cutting are complete.
- C. Patching: Patch construction by filling, repairing, refinishing, closing up, and similar operations following performance of other Work. Patch with durable seams that are as invisible as possible. Provide materials and comply with installation requirements specified in other Sections of these Specifications.
 1. Inspection: Where feasible, test and inspect patched areas after completion to demonstrate integrity of installation.

2. Exposed Finishes: Restore exposed finishes of patched areas and extend finish restoration into retained adjoining construction in a manner that will eliminate evidence of patching and refinishing.
3. Floors and Walls: Where walls or partitions that are removed extend one finished area into another, patch and repair floor and wall surfaces in the new space. Provide an even surface of uniform finish, color, texture, and appearance. Remove existing floor and wall coverings and replace with new materials, if necessary, to achieve uniform color and appearance.
 - a. Where patching occurs in a painted surface, apply primer and intermediate paint coats over the patch and apply final paint coat over entire unbroken surface containing the patch. Provide additional coats until patch blends with adjacent surfaces.
4. Ceilings: Patch, repair, or re-hang existing ceilings as necessary to provide an even-plane surface of uniform appearance.
5. Exterior Building Enclosure: Patch components in a manner that restores enclosure to a weathertight condition.

END OF SECTION 01731

**SECTION 01732
SELECTIVE DEMOLITION**

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 1 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes the following:
 - 1. Demolition and removal of selected portions of a building or structure.
 - 2. Demolition and removal of selected site elements.
 - 3. Repair procedures for selective demolition operations.
- B. Related Sections include the following:
 - 1. Division 1 Section "Summary" for use of the premises and phasing requirements.
 - 2. Division 1 Section "Work Restrictions" for restrictions on use of the premises due to Owner or tenant occupancy.
 - 3. Division 1 Section "Construction Progress Documentation" for preconstruction photographs taken before selective demolition.
 - 4. Division 1 Section "Temporary Facilities and Controls" for temporary construction and environmental-protection measures for selective demolition operations.
 - 5. Division 1 Section "Cutting and Patching" for cutting and patching procedures for selective demolition operations.
 - 6. Division 2 Section "Asbestos Abatement" for removal of asbestos materials.
 - 7. Division 15 Sections for demolishing, cutting, patching, or relocating mechanical items.
 - 8. Division 16 Sections for demolishing, cutting, patching, or relocating electrical items.

1.3 DEFINITIONS

- A. Remove: Detach items from existing construction and legally dispose of them off-site, unless indicated to be removed and salvaged or removed and reinstalled.
- B. Remove and Salvage: Detach items from existing construction and deliver them to Owner.
- C. Remove and Reinstall: Detach items from existing construction, prepare them for reuse, and reinstall them where indicated.
- D. Existing to Remain: Existing items of construction that are not to be removed and that are not otherwise indicated to be removed, removed and salvaged, or removed and reinstalled.

1.4 MATERIALS OWNERSHIP

- A. Except for items or materials indicated to be reused, salvaged, reinstalled, or otherwise indicated to remain Owner's property, demolished materials shall become Contractor's property and shall be removed from Project site.

1.5 SUBMITTALS

- A. Qualification Data: For firms and persons specified in "Quality Assurance" Article to demonstrate their capabilities and experience. Include lists of completed projects with project names and addresses, names and addresses of architects and owners, and other information specified.
- B. Schedule of Selective Demolition Activities: Indicate the following:
 - 1. Detailed sequence of selective demolition and removal work, with starting and ending dates for each activity. Ensure Owner's on-site operations are uninterrupted.
 - 2. Interruption of utility services.
 - 3. Coordination for shutoff, capping, and continuation of utility services.
- C. Inventory: After selective demolition is complete, submit a list of items that have been removed and salvaged.
- D. Landfill Records: Indicate receipt and acceptance of hazardous wastes by a landfill facility licensed to accept hazardous wastes.

1.6 QUALITY ASSURANCE

- A. Regulatory Requirements: Comply with governing EPA notification regulations before beginning selective demolition. Comply with hauling and disposal regulations of authorities having jurisdiction.
- B. Standards: Comply with ANSI A10.6 and NFPA 241.
- C. Pre-demolition Conference: Conduct conference at Project site to comply with requirements in Division 1 Section "Project Management and Coordination." Review methods and procedures related to selective demolition including, but not limited to, the following:
 - 1. Inspect and discuss condition of construction to be selectively demolished.
 - 2. Review structural load limitations of existing structure.
 - 3. Review and finalize selective demolition schedule and verify availability of materials, demolition personnel, equipment, and facilities needed to make progress and avoid delays.
 - 4. Review requirements of work performed by other trades that rely on substrates exposed by selective demolition operations.

1.7 PROJECT CONDITIONS

- A. Residents will occupy portions of the site immediately adjacent to selective demolition area. Conduct selective demolition so resident's operations will not be disrupted. Provide not less than **48** hours notice to Owner of activities that will affect resident's operations.
- B. Maintain access to existing streets, sidewalks, and other adjacent occupied or used portions of the site.
 - 1. Do not close or obstruct streets, sidewalks, or other occupied or used portions of the site without written permission from authorities having jurisdiction.
- C. Owner assumes no responsibility for condition of areas to be selectively demolished.
 - 1. Conditions existing at time of inspection for bidding purpose will be maintained by Owner as far as practical.
- D. Hazardous Materials: Hazardous materials are present in building to be selectively demolished. A report on the presence of hazardous materials is on file for review and use. Examine report to become aware of locations where hazardous materials are present.
 - 1. Hazardous material remediation is specified elsewhere in the Contract Documents.
 - 2. Do not disturb hazardous materials or items suspected of containing hazardous materials except under procedures specified elsewhere in the Contract Documents.
- E. Storage or sale of removed items or materials on-site will not be permitted.
- F. Utility Service: Maintain existing utilities indicated to remain in service and protect them against damage during selective demolition operations.
 - 1. Maintain fire-protection facilities in service during selective demolition operations.

1.8 WARRANTY

- A. Existing Warranties: Remove, replace, patch, and repair materials and surfaces cut or damaged during selective demolition, by methods and with materials so as not to void existing warranties.

PART 2 - PRODUCTS

2.1 REPAIR MATERIALS

- A. Use repair materials identical to existing materials.
 - 1. If identical materials are unavailable or cannot be used for exposed surfaces, use materials that visually match existing adjacent surfaces to the fullest extent possible.
 - 2. Use materials whose installed performance equals or surpasses that of existing materials.
- B. Comply with material and installation requirements specified in individual Specification Sections.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Verify that utilities have been disconnected and capped.
- B. Survey existing conditions and correlate with requirements indicated to determine extent of selective demolition required.
- C. Inventory and record the condition of items to be removed and reinstalled and items to be removed and salvaged.
- D. When unanticipated mechanical, electrical, or structural elements that conflict with intended function or design are encountered, investigate and measure the nature and extent of conflict. Promptly submit a written report to Architect.
- E. Engage a professional engineer to survey condition of building to determine whether removing any element might result in structural deficiency or unplanned collapse of any portion of structure or adjacent structures during selective demolition operations.
- F. Perform surveys as the Work progresses to detect hazards resulting from selective demolition activities.

3.2 UTILITY SERVICES

- A. Existing Utilities: Maintain services indicated to remain and protect them against damage during selective demolition operations.
- B. Do not interrupt existing utilities serving occupied or operating facilities unless authorized in writing by Owner and authorities having jurisdiction. Provide temporary services during interruptions to existing utilities, as acceptable to Owner and to authorities having jurisdiction.
 - 1. Provide at least **72** hours notice to Owner if shutdown of service is required during changeover.
- C. Utility Requirements: Locate, identify, disconnect, and seal or cap off indicated utilities serving areas to be selectively demolished.
 - 1. Arrange to shut off indicated utilities with utility companies.
 - 2. If utility services are required to be removed, relocated, or abandoned, before proceeding with selective demolition provide temporary utilities that bypass area of selective demolition and that maintain continuity of service to other parts of building.
 - 3. Cut off pipe or conduit in walls or partitions to be removed. Cap, valve, or plug and seal remaining portion of pipe or conduit after bypassing.
- D. Utility Requirements: Refer to Division 15 and 16 Sections for shutting off, disconnecting, removing, and sealing or capping utilities. Do not start selective demolition work until utility disconnecting and sealing have been completed and verified in writing.

3.3 PREPARATION

- A. Pest Control: Employ a certified, licensed exterminator to treat building and to control rodents and vermin before and during selective demolition operations.
- B. Site Access and Temporary Controls: Conduct selective demolition and debris-removal operations to ensure minimum interference with roads, streets, walks, walkways, and other adjacent occupied and used facilities.
 - 1. Do not close or obstruct streets, walks, walkways, or other adjacent occupied or used facilities without permission from Owner and authorities having jurisdiction. Provide alternate routes around closed or obstructed traffic ways if required by governing regulations.
 - 2. Erect temporary protection, such as walks, fences, railings, canopies, and covered passageways, where required by authorities having jurisdiction.
 - 3. Protect existing site improvements, appurtenances, and landscaping to remain.
 - 4. Erect a plainly visible fence around drip line of individual trees or around perimeter drip line of groups of trees to remain.
- C. Temporary Facilities: Provide temporary barricades and other protection required to prevent injury to people and damage to adjacent buildings and facilities to remain.
 - 1. Provide protection to ensure safe passage of people around selective demolition area and to and from occupied portions of building.
 - 2. Provide temporary weather protection, during interval between selective demolition of existing construction on exterior surfaces and new construction, to prevent water leakage and damage to structure and interior areas.

3. Protect walls, ceilings, floors, and other existing finish work that are to remain or that are exposed during selective demolition operations.
 - D. Temporary Enclosures: Provide temporary enclosures for protection of existing building and construction, in progress and completed, from exposure, foul weather, other construction operations, and similar activities. Provide temporary weathertight enclosure for building exterior.
 1. Where heating or cooling is needed and permanent enclosure is not complete, provide insulated temporary enclosures. Coordinate enclosure with ventilating and material drying or curing requirements to avoid dangerous conditions and effects.
 - E. Temporary Shoring: Provide and maintain **interior** or **exterior** shoring, bracing, or structural support to preserve stability and prevent movement, settlement, or collapse of construction to remain, and to prevent unexpected or uncontrolled movement or collapse of construction being demolished.
 1. Strengthen or add new supports when required during progress of selective demolition.
- 3.4 POLLUTION CONTROLS
- A. Disposal: Remove and transport debris in a manner that will prevent spillage on adjacent surfaces and areas.
 1. Remove debris from elevated portions of building by chute, hoist, or other device that will convey debris to grade level in a controlled descent.
 - B. Cleaning: Clean adjacent structures and improvements of dust, dirt, and debris caused by selective demolition operations. Return adjacent areas to condition existing before selective demolition operations began.
- 3.5 SELECTIVE DEMOLITION
- A. General: Demolish and remove existing construction only to the extent required by new construction and as indicated. Use methods required to complete the Work within limitations of governing regulations and as follows:
 1. Proceed with selective demolition systematically, from higher to lower level. Complete selective demolition operations above each floor or tier before disturbing supporting members on the next lower level.
 2. Neatly cut openings and holes plumb, square, and true to dimensions required. Use cutting methods least likely to damage construction to remain or adjoining construction. Use hand tools or small power tools designed for sawing or grinding, not hammering and chopping, to minimize disturbance of adjacent surfaces. Temporarily cover openings to remain.
 3. Cut or drill from the exposed or finished side into concealed surfaces to avoid marring existing finished surfaces.
 4. Do not use cutting torches until work area is cleared of flammable materials. At concealed spaces, such as duct and pipe interiors, verify condition and contents of hidden space before starting flame-cutting operations. Maintain fire watch and portable fire-suppression devices during flame-cutting operations.
 5. Maintain adequate ventilation when using cutting torches.
 6. Remove decayed, vermin-infested, or otherwise dangerous or unsuitable materials and promptly dispose of off-site.
 7. Remove structural framing members and lower to ground by method suitable to avoid free fall and to prevent ground impact or dust generation.
 8. Locate selective demolition equipment and remove debris and materials so as not to impose excessive loads on supporting walls, floors, or framing.
 9. Dispose of demolished items and materials promptly.
 10. Return elements of construction and surfaces that are to remain to condition existing before selective demolition operations began.
 - B. Existing Items to Remain: Protect construction indicated to remain against damage and soiling during selective demolition. When permitted by Architect, items may be removed to a suitable, protected storage location during selective demolition and cleaned and reinstalled in their original locations after selective demolition operations are complete.

- C. Concrete: Demolish in small sections. Cut concrete to a depth of at least 3/4 inch at junctures with construction to remain, using power-driven saw. Dislodge concrete from reinforcement at perimeter of areas being demolished, cut reinforcement, and then remove remainder of concrete indicated for selective demolition. Neatly trim openings to dimensions indicated.
 - D. Concrete: Demolish in sections. Cut concrete full depth at junctures with construction to remain and at regular intervals, using power-driven saw, then remove concrete between saw cuts.
 - E. Masonry: Demolish in small sections. Cut masonry at junctures with construction to remain, using power-driven saw, then remove masonry between saw cuts.
 - F. Concrete Slabs-on-Grade: Saw-cut perimeter of area to be demolished, then break up and remove.
 - G. Resilient Floor Coverings: Remove floor coverings and adhesive according to recommendations in RFCI-WP and its Addendum.
 - 1. Remove residual adhesive and prepare substrate for new floor coverings by one of the methods recommended by RFCI.
 - H. Roofing: Remove no more existing roofing than can be covered in one day by new roofing. Refer to applicable Division 7 Section for new roofing requirements.
- 3.6 PATCHING AND REPAIRS
- A. General: Promptly repair damage to adjacent construction caused by selective demolition operations.
 - B. Patching: Comply with Division 1 Section "Cutting and Patching."
 - C. Repairs: Where repairs to existing surfaces are required, patch to produce surfaces suitable for new materials.
 - 1. Completely fill holes and depressions in existing masonry walls that are to remain with an approved masonry patching material applied according to manufacturer's written recommendations.
 - D. Finishes: Restore exposed finishes of patched areas and extend restoration into adjoining construction in a manner that eliminates evidence of patching and refinishing.
- 3.7 DISPOSAL OF DEMOLISHED MATERIALS
- A. General: Promptly dispose of demolished materials. Do not allow demolished materials to accumulate on-site.
 - B. Burning: Do not burn demolished materials.
 - C. Disposal: Transport demolished materials off Owner's property and legally dispose of them.

END OF SECTION 01732

**SECTION 03300
CAST-IN-PLACE CONCRETE**

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 1 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section specifies cast-in place concrete, including formwork, reinforcement, concrete materials, mix design, placement procedures, and finishes.
- B. Related Sections include the following:
 - 1. Division 2 Section "Earthwork" for drainage fill under slabs-on-grade.
 - 2. Division 2 Section "Concrete Paving" for concrete pavement and walks.

1.3 SUBMITTALS

- A. Product Data: For each type of manufactured material and product indicated.
- B. Design Mixes: For each concrete mix. Include alternate mix designs when characteristics of materials, project conditions, weather, test results, or other circumstances warrant adjustments.
 - 1. Indicate amounts of mix water to be withheld for later addition at Project site.

1.4 QUALITY ASSURANCE

- A. Installer Qualifications: An experienced installer who has completed concrete Work similar in material, design, and extent to that indicated for this Project and whose work has resulted in construction with a record of successful in-service performance.
- B. Manufacturer Qualifications: A firm experienced in manufacturing ready-mixed concrete products complying with ASTM C 94 requirements for production facilities and equipment.
- C. Testing Agency Qualifications: An independent testing agency, acceptable to authorities having jurisdiction, qualified according to ASTM C 1077 and ASTM E 329 to conduct the testing indicated, as documented according to ASTM E 548.
- D. Source Limitations: Obtain each type or class of cementitious material of the same brand from the same manufacturer's plant, each aggregate from one source, and each admixture from the same manufacturer.
- E. ACI Publications: Comply with the following, unless more stringent provisions are indicated:
 - 1. ACI 301, "Specification for Structural Concrete."
 - 2. ACI 117, "Specifications for Tolerances for Concrete Construction and Materials."

1.5 DELIVERY, STORAGE, AND HANDLING

- A. Deliver, store, and handle steel reinforcement to prevent bending and damage.

PART 2 - PRODUCTS

2.1 FORM-FACING MATERIALS

- A. Smooth-Formed Finished Concrete: Form-facing panels that will provide continuous, true, and smooth concrete surfaces. Furnish in largest practicable sizes to minimize number of joints.
 - 1. Plywood, metal, or other approved panel materials.
- B. Rough-Formed Finished Concrete: Plywood, lumber, metal, or another approved material. Provide lumber dressed on at least two edges and one side for tight fit.
- C. Form-Release Agent: Commercially formulated form-release agent that will not bond with, stain, or adversely affect concrete surfaces and will not impair subsequent treatments of concrete surfaces.
 - 1. Formulate form-release agent with rust inhibitor for steel form-facing materials.

2.2 STEEL REINFORCEMENT

- A. Reinforcing Bars: ASTM A 615/A 615M, Grade 60, deformed.
- B. Plain-Steel Welded Wire Fabric: ASTM A 185, fabricated from as-drawn steel wire into flat sheets.

2.3 REINFORCEMENT ACCESSORIES

- A. Bar Supports: Bolsters, chairs, spacers, and other devices for spacing, supporting, and fastening reinforcing bars and welded wire fabric in place. Manufacture bar supports according to CRSI's "Manual of Standard Practice" from steel wire, plastic, or precast concrete or fiber-reinforced concrete of greater compressive strength than concrete, and as follows:
 - 1. For concrete surfaces exposed to view where legs of wire bar supports contact forms, use CRSI Class 1 plastic-protected or CRSI Class 2 stainless-steel bar supports.
- B. Joint Dowel Bars: Plain-steel bars, ASTM A 615/A 615M, Grade 60. Cut bars true to length with ends square and free of burrs.

2.4 CONCRETE MATERIALS

- A. Portland Cement: ASTM C 150, Type as required.
- B. Normal-Weight Aggregate: ASTM C 33, uniformly graded, and as follows:
 - 1. Class: Moderate weathering region, but not less than 3M.
 - 2. Nominal Maximum Aggregate Size: 3/4 inch.
- C. Water: Potable and complying with ASTM C 94.

2.5 ADMIXTURES

- A. General: Admixtures certified by manufacturer to contain not more than 0.1 percent water-soluble chloride ions by mass of cementitious material and to be compatible with other admixtures and cementitious materials. Do not use admixtures containing calcium chloride.
- B. Air-Entraining Admixture: ASTM C 260.
- C. Water-Reducing Admixture: ASTM C 494, type as required to suit project conditions. Only use admixtures which have been tested and accepted in mix designs.

2.6 VAPOR RETARDERS

- A. Vapor Retarder: ASTM E 1745, Class C, polyethylene sheet, ASTM D 4397, not less than 6 mils thick.
- B. Granular Fill: Clean mixture of crushed stone or crushed or uncrushed gravel; ASTM D 448, Size 57, with 100 percent passing a 1-1/2-inch sieve and 0 to 5 percent passing a No. 8 sieve.

2.7 RELATED MATERIALS

- A. Joint-Filler Strips: ASTM D 1751, asphalt-saturated cellulosic fiber.
- B. Bonding Agent: ASTM C 1059, Type II, non-redispersible, acrylic emulsion or styrene butadiene.
 - 1. Types I and II, non-load bearing, for bonding hardened or freshly mixed concrete to hardened concrete.
 - 2. Types IV and V, load bearing, for bonding hardened or freshly mixed concrete to hardened concrete.
- C. Reglets: Fabricate reglets of not less than 0.0217-inch- thick galvanized steel sheet. Temporarily fill or cover face opening of reglet to prevent intrusion of concrete or debris.
- D. Dovetail Anchor Slots: Hot-dip galvanized steel sheet, not less than 0.0336 inch thick, with bent tab anchors. Temporarily fill or cover face opening of slots to prevent intrusion of concrete or debris.

2.8 CONCRETE MIXES

- A. Prepare design mixes for each type and strength of concrete determined by either laboratory trial mix or field test data bases, as follows:
 - 1. Proportion normal-weight concrete according to ACI 211.1 and ACI 301.
- B. Use a qualified independent testing agency for preparing and reporting proposed mix designs for the laboratory trial mix basis.

- C. Footings and Foundation Walls: Proportion normal-weight concrete mix as follows:
 - 1. Compressive Strength (28 Days): 3000 psi.
 - 2. Maximum Slump: 4 inches.
 - D. Slab-on-Grade: Proportion normal-weight concrete mix as follows:
 - 1. Compressive Strength (28 Days): 3000 psi.
 - 2. Maximum Slump: 5 inches.
- 2.9 FABRICATING REINFORCEMENT
- A. Fabricate steel reinforcement according to CRSI's "Manual of Standard Practice."
- 2.10 CONCRETE MIXING
- A. Ready-Mixed Concrete: Measure, batch, mix, and deliver concrete according to ASTM C 94, and furnish batch ticket information.

PART 3 - EXECUTION

3.1 FORMWORK

- A. Design, erect, shore, brace, and maintain formwork, according to ACI 301, to support vertical, lateral, static, and dynamic loads, and construction loads that might be applied, until concrete structure can support such loads.
- B. Construct formwork so concrete members and structures are of size, shape, alignment, elevation, and position indicated, within tolerance limits of ACI 117.
- C. Limit concrete surface irregularities, designated by ACI 347R as abrupt or gradual, as follows:
 - 1. Class B, 1/4 inch.
- D. Construct forms tight enough to prevent loss of concrete mortar.
- E. Fabricate forms for easy removal without hammering or prying against concrete surfaces. Provide crush or wrecking plates where stripping may damage cast concrete surfaces. Provide top forms for inclined surfaces steeper than 1.5 horizontal to 1 vertical. Kerf wood inserts for forming keyways, reglets, recesses, and the like, for easy removal.
 - 1. Do not use rust-stained steel form-facing material.
- F. Set edge forms, bulkheads, and intermediate screed strips for slabs to achieve required elevations and slopes in finished concrete surfaces. Provide and secure units to support screed strips; use strike-off templates or compacting-type screeds.
- G. Provide temporary openings for cleanouts and inspection ports where interior area of formwork is inaccessible. Close openings with panels tightly fitted to forms and securely braced to prevent loss of concrete mortar. Locate temporary openings in forms at inconspicuous locations.
- H. Chamfer exterior corners and edges of permanently exposed concrete.
- I. Form openings, chases, offsets, sinkages, keyways, reglets, blocking, screeds, and bulkheads required in the Work. Determine sizes and locations from trades providing such items.
- J. Clean forms and adjacent surfaces to receive concrete. Remove chips, wood, sawdust, dirt, and other debris just before placing concrete.
- K. Retighten forms and bracing before placing concrete, as required, to prevent mortar leaks and maintain proper alignment.
- L. Coat contact surfaces of forms with form-release agent, according to manufacturer's written instructions, before placing reinforcement.

3.2 EMBEDDED ITEMS

- A. Place and secure anchorage devices and other embedded items required for adjoining work that is attached to or supported by cast-in-place concrete. Use Setting Drawings, templates, diagrams, instructions, and directions furnished with items to be embedded.
 - 1. Install anchor bolts, accurately located, to elevations required.
 - 2. Install reglets to receive top edge of foundation sheet waterproofing and to receive through-wall flashings in outer face of concrete frame at exterior walls, where flashing is shown at lintels, shelf angles, and other conditions.

3. Install dovetail anchor slots in concrete structures as indicated.

3.3 REMOVING AND REUSING FORMS

- A. General: Formwork, for sides of beams, walls, columns, and similar parts of the Work, that does not support weight of concrete may be removed after cumulatively curing at not less than 50 deg F for 24 hours after placing concrete provided concrete is hard enough to not be damaged by form-removal operations and provided curing and protection operations are maintained.
- B. Leave formwork, for beam soffits, joists, slabs, and other structural elements, that supports weight of concrete in place until concrete has achieved the following:
 1. 28-day design compressive strength.
- C. Clean and repair surfaces of forms to be reused in the Work. Split, frayed, delaminated, or otherwise damaged form-facing material will not be acceptable for exposed surfaces. Apply new form-release agent.
- D. When forms are reused, clean surfaces, remove fins and laitance, and tighten to close joints. Align and secure joints to avoid offsets. Do not use patched forms for exposed concrete surfaces unless approved by Architect.

3.4 SHORES AND RESHORES

- A. Comply with ACI 318, ACI 301, and recommendations in ACI 347R for design, installation, and removal of shoring and reshoring.
- B. Plan sequence of removal of shores and reshore to avoid damage to concrete. Locate and provide adequate reshoring to support construction without excessive stress or deflection.

3.5 VAPOR RETARDERS

- A. Vapor Retarder: Place, protect, and repair vapor-retarder sheets according to ASTM E 1643 and manufacturer's written instructions.
- B. Granular Fill: Cover vapor retarder with granular fill, moisten, and compact with mechanical equipment to elevation tolerances of plus 0 inch or minus 3/4 inch.

3.6 STEEL REINFORCEMENT

- A. General: Comply with CRSI's "Manual of Standard Practice" for placing reinforcement.
 1. Do not cut or puncture vapor retarder. Repair damage and reseal vapor retarder before placing concrete.
- B. Clean reinforcement of loose rust and mill scale, earth, ice, and other foreign materials.
- C. Accurately position, support, and secure reinforcement against displacement. Locate and support reinforcement with bar supports to maintain minimum concrete cover. Do not tack weld crossing reinforcing bars.
- D. Set wire ties with ends directed into concrete, not toward exposed concrete surfaces.
- E. Install welded wire fabric in longest practicable lengths on bar supports spaced to minimize sagging. Lap edges and ends of adjoining sheets at least one mesh spacing. Offset laps of adjoining sheet widths to prevent continuous laps in either direction. Lace overlaps with wire.

3.7 JOINTS

- A. General: Construct joints true to line with faces perpendicular to surface plane of concrete.
- B. Construction Joints: Install so strength and appearance of concrete are not impaired, at locations indicated or as approved by Architect.
 1. Place joints perpendicular to main reinforcement. Continue reinforcement across construction joints, unless otherwise indicated. Do not continue reinforcement through sides of strip placements of floors and slabs.
 2. Form from preformed galvanized steel, plastic keyway-section forms, or bulkhead forms with keys, unless otherwise indicated. Embed keys at least 1-1/2 inches into concrete.
 3. Use a bonding agent at locations where fresh concrete is placed against hardened or partially hardened concrete surfaces.
- C. Contraction Joints in Slabs-on-Grade: Form weakened-plane contraction joints, sectioning concrete into areas as indicated. Construct contraction joints for a depth equal to at least one-

fourth of concrete thickness, as follows:

1. Sawed Joints: Form contraction joints with power saws equipped with shatterproof abrasive or diamond-rimmed blades. Cut 1/8-inch- wide joints into concrete when cutting action will not tear, abrade, or otherwise damage surface and before concrete develops random contraction cracks.
- D. Isolation Joints in Slabs-on-Grade: After removing formwork, install joint-filler strips at slab junctions with vertical surfaces, such as column pedestals, foundation walls, grade beams, and other locations, as indicated.
 1. Extend joint-filler strips full width and depth of joint, terminating flush with finished concrete surface, unless otherwise indicated.
 2. Install joint-filler strips in lengths as long as practicable. Where more than one length is required, lace or clip sections together.

3.8 WATERSTOPS

- A. Flexible Waterstops: Install in construction joints as indicated to form a continuous diaphragm. Install in longest lengths practicable. Support and protect exposed waterstops during progress of Work. Field-fabricate joints in waterstops according to manufacturer's written instructions.

3.9 CONCRETE PLACEMENT

- A. Before placing concrete, verify that installation of formwork, reinforcement, and embedded items is complete and that required inspections have been performed.
- B. Before placing concrete, water may be added at Project site, subject to limitations of ACI 301.
 1. Do not add water to concrete after adding high-range water-reducing admixtures to mix.
- C. Deposit concrete continuously or in layers of such thickness that no new concrete will be placed on concrete that has hardened enough to cause seams or planes of weakness. If a section cannot be placed continuously, provide construction joints as specified. Deposit concrete to avoid segregation.
- D. Deposit concrete in forms in horizontal layers no deeper than 24 inches and in a manner to avoid inclined construction joints. Place each layer while preceding layer is still plastic, to avoid cold joints.
 1. Consolidate placed concrete with mechanical vibrating equipment. Use equipment and procedures for consolidating concrete recommended by ACI 309R.
 2. Do not use vibrators to transport concrete inside forms. Insert and withdraw vibrators vertically at uniformly spaced locations no farther than the visible effectiveness of the vibrator. Place vibrators to rapidly penetrate placed layer and at least 6 inches into preceding layer. Do not insert vibrators into lower layers of concrete that have begun to lose plasticity. At each insertion, limit duration of vibration to time necessary to consolidate concrete and complete embedment of reinforcement and other embedded items without causing mix constituents to segregate.
- E. Deposit and consolidate concrete for floors and slabs in a continuous operation, within limits of construction joints, until placement of a panel or section is complete.
 1. Consolidate concrete during placement operations so concrete is thoroughly worked around reinforcement and other embedded items and into corners.
 2. Maintain reinforcement in position on chairs during concrete placement.
 3. Screed slab surfaces with a straightedge and strike off to correct elevations.
 4. Slope surfaces uniformly to drains where required.
 5. Begin initial floating using bull floats or darbies to form a uniform and open-textured surface plane, free of humps or hollows, before excess moisture or bleedwater appears on the surface. Do not further disturb slab surfaces before starting finishing operations.
- F. Cold-Weather Placement: Comply with ACI 306.1 and as follows. Protect concrete work from physical damage or reduced strength that could be caused by frost, freezing actions, or low temperatures.
 1. When air temperature has fallen to or is expected to fall below 40 deg F, uniformly heat water and aggregates before mixing to obtain a concrete mixture temperature of not less than 50 deg F and not more than 80 deg F at point of placement.
 2. Do not use frozen materials or materials containing ice or snow. Do not place concrete on

frozen subgrade or on subgrade containing frozen materials.

3. Do not use calcium chloride, salt, or other materials containing antifreeze agents or chemical accelerators, unless otherwise specified and approved in mix designs.
- G. Hot-Weather Placement: Place concrete according to recommendations in ACI 305R and as follows, when hot-weather conditions exist:
1. Cool ingredients before mixing to maintain concrete temperature below 90 deg F at time of placement. Chilled mixing water or chopped ice may be used to control temperature, provided water equivalent of ice is calculated to total amount of mixing water. Using liquid nitrogen to cool concrete is Contractor's option.
 2. Cover steel reinforcement with water-soaked burlap so steel temperature will not exceed ambient air temperature immediately before embedding in concrete.
 3. Fog-spray forms, steel reinforcement, and subgrade just before placing concrete. Keep subgrade moisture uniform without standing water, soft spots, or dry areas.

3.10 FINISHING FORMED SURFACES

- A. Rough-Formed Finish: As-cast concrete texture imparted by form-facing material with tie holes and defective areas repaired and patched. Remove fins and other projections exceeding ACI 347R limits for class of surface specified.
- B. Smooth-Formed Finish: As-cast concrete texture imparted by form-facing material, arranged in an orderly and symmetrical manner with a minimum of seams. Repair and patch tie holes and defective areas. Remove fins and other projections exceeding 1/8 inch in height.
1. Apply to concrete surfaces exposed to public view or to be covered with a coating or covering material applied directly to concrete, such as waterproofing, dampproofing, veneer plaster, or painting.
 2. Do not apply rubbed finish to smooth-formed finish.

3.11 FINISHING FLOORS AND SLABS

- A. General: Comply with recommendations in ACI 302.1R for screeding, restraighening, and finishing operations for concrete surfaces. Do not wet concrete surfaces.
- B. Float Finish: Consolidate surface with power-driven floats or by hand floating if area is small or inaccessible to power driven floats. Restraighten, cut down high spots, and fill low spots. Repeat float passes and restraighening until surface is left with a uniform, smooth, granular texture.
1. Apply float finish to slabs-on-grade.
- C. Trowel Finish: After applying float finish, apply first trowel finish and consolidate concrete by hand or power-driven trowel. Continue troweling passes and restraighten until surface is free of trowel marks and uniform in texture and appearance. Grind smooth any surface defects that would telegraph through applied coatings or floor coverings.
1. Apply a trowel finish to surfaces indicated and to floor and slab surfaces exposed to view or to be covered with resilient flooring, carpet, ceramic or quarry tile set over a cleavage membrane, paint, or another thin film-finish coating system
- D. Broom Finish: Apply a broom finish to exterior concrete platforms, steps, and ramps, and elsewhere as indicated.
1. Immediately after float finishing, slightly roughen trafficked surface by brooming with fiber-bristle broom perpendicular to main traffic route. Coordinate required final finish with Architect before application.

3.12 MISCELLANEOUS CONCRETE ITEMS

- A. Filling In: Fill in holes and openings left in concrete structures, unless otherwise indicated, after work of other trades is in place. Mix, place, and cure concrete, as specified, to blend with in-place construction. Provide other miscellaneous concrete filling indicated or required to complete Work.
- B. Equipment Bases and Foundations: Provide machine and equipment bases and foundations as shown on Drawings.

3.13 CONCRETE PROTECTION AND CURING

- A. General: Protect freshly placed concrete from premature drying and excessive cold or hot temperatures. Comply with ACI 306.1 for cold-weather protection and with recommendations in ACI 305R for hot-weather protection during curing.
- B. Evaporation Retarder: Apply evaporation retarder to unformed concrete surfaces if hot, dry, or windy conditions cause moisture loss approaching 0.2 lb/sq. Ft. x h before and during finishing operations. Apply according to manufacturer's written instructions after placing, screeding, and bull floating or darbying concrete, but before float finishing.

3.14 CONCRETE SURFACE REPAIRS

- A. Defective Concrete: Repair and patch defective areas when approved by Architect. Remove and replace concrete that cannot be repaired and patched to Architect's approval.
- B. Patching Mortar: Mix dry-pack patching mortar, consisting of one part portland cement to two and one-half parts fine aggregate passing a No. 16 sieve, using only enough water for handling and placing.
- C. Repairing Formed Surfaces: Surface defects include color and texture irregularities, cracks, spalls, air bubbles, honeycombs, rock pockets, fins and other projections on the surface, and stains and other discolorations that cannot be removed by cleaning.
 - 1. Immediately after form removal, cut out honeycombs, rock pockets, and voids more than ½ inch in any dimension in solid concrete but not less than 1 inch in depth. Make edges of cuts perpendicular to concrete surface. Clean, dampen with water, and brush-coat holes and voids with bonding agent. Fill and compact with patching mortar before bonding agent has dried. Fill form-tie voids with patching mortar or cone plugs secured in place with bonding agent.
 - 2. Repair defects on surfaces exposed to view by blending white portland cement and standard portland cement so that, when dry, patching mortar will match surrounding color. Patch a test area at inconspicuous locations to verify mixture and color match before proceeding with patching. Compact mortar in place and strike off slightly higher than surrounding surface.
 - 3. Repair defects on concealed formed surfaces that affect concrete's durability and structural performance as determined by Architect.
- D. Repairing Unformed Surfaces: Test unformed surfaces, such as floors and slabs, for finish and verify surface tolerances specified for each surface. Correct low and high areas. Test surfaces sloped to drain for trueness of slope and smoothness; use a sloped template.
 - 1. Repair finished surfaces containing defects. Surface defects include spalls, popouts, honeycombs, rock pockets, crazing and cracks in excess of 0.01 inch wide or that penetrate to reinforcement or completely through unreinforced sections regardless of width, and other objectionable conditions.
 - 2. After concrete has cured at least 14 days, correct high areas by grinding.
 - 3. Correct localized low areas during or immediately after completing surface finishing operations by cutting out low areas and replacing with patching mortar. Finish repaired areas to blend into adjacent concrete.
 - 4. Correct other low areas scheduled to receive floor coverings with a repair underlayment. Prepare, mix, and apply repair underlayment and primer according to manufacturer's written instructions to produce a smooth, uniform, plane, and level surface. Feather edges to match adjacent floor elevations.
 - 5. Repair defective areas, except random cracks and single holes 1 inch or less in diameter, by cutting out and replacing with fresh concrete. Remove defective areas with clean, square cuts and expose steel reinforcement with at least 3/4 inch clearance all around. Dampen concrete surfaces in contact with patching concrete and apply bonding agent. Mix patching concrete of same materials and mix as original concrete except without coarse aggregate. Place, compact, and finish to blend with adjacent finished concrete. Cure in same manner as adjacent concrete.
 - 6. Repair random cracks and single holes 1 inch or less in diameter with patching mortar. Groove top of cracks and cut out holes to sound concrete and clean off dust, dirt, and loose particles. Dampen cleaned concrete surfaces and apply bonding agent. Place patching mortar before bonding agent has dried. Compact patching mortar and finish to match

adjacent concrete. Keep patched area continuously moist for at least 72 hours.

- E. Repair materials and installation not specified above may be used, subject to Architect's approval.

3.15 FIELD QUALITY CONTROL

- A. Testing Agency: Engage a qualified independent testing and inspecting agency to sample materials, perform tests, and submit test reports during concrete placement according to requirements specified in this Article.
- B. Testing Services: Testing of composite samples of fresh concrete obtained according to ASTM C 172 shall be performed according to the following requirements:
 - 1. Testing Frequency: Obtain at least one composite sample for each 50 cu. yd. or fraction thereof of each concrete mix placed each day.
 - a. When frequency of testing will provide fewer than five compressive-strength tests for each concrete mix, testing shall be conducted from at least five randomly selected batches or from each batch if fewer than five are used.
 - 2. Slump: ASTM C 143; one test at point of placement for each composite sample, but not less than one test for each day's pour of each concrete mix. Perform additional tests when concrete consistency appears to change.
 - 3. Air Content: ASTM C 231, pressure method, for normal-weight concrete; ASTM C 173, volumetric method, for structural lightweight concrete; one test for each composite sample, but not less than one test for each day's pour of each concrete mix.
 - 4. Concrete Temperature: ASTM C 1064; one test hourly when air temperature is 40 deg F and below and when 80 deg F and above, and one test for each composite sample.
 - 5. Compression Test Specimens: ASTM C 31/C 31M; cast and laboratory cure one set of four standard cylinder specimens for each composite sample.
 - 6. Compressive-Strength Tests: ASTM C 39; test two laboratory-cured specimens at 7 days and two at 28 days.
 - a. A compressive-strength test shall be the average compressive strength from two specimens obtained from same composite sample and tested at age indicated.
- C. Strength of each concrete mix will be satisfactory if every average of any three consecutive compressive-strength tests equals or exceeds specified compressive strength and no compressive-strength test value falls below specified compressive strength by more than 500 psi.
- D. Test results shall be reported in writing to Architect, concrete manufacturer, and Contractor within 48 hours of testing. Reports of compressive-strength tests shall contain Project identification name and number, date of concrete placement, name of concrete testing and inspecting agency, location of concrete batch in Work, design compressive strength at 28 days, concrete mix proportions and materials, compressive breaking strength, and type of break for both 7-and 28-day tests.
- E. Nondestructive Testing: Impact hammer, sonoscope, or other nondestructive device may be permitted by Architect but will not be used as sole basis for approval or rejection of concrete.
- F. Additional Tests: Testing and inspecting agency shall make additional tests of concrete when test results indicate that slump, air entrainment, compressive strengths, or other requirements have not been met, as directed by Architect. Testing and inspecting agency may conduct tests to determine adequacy of concrete by cored cylinders complying with ASTM C 42 or by other methods as directed by Architect.

END OF SECTION 03300

**SECTION 06100
ROUGH CARPENTRY**

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 1 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes the following:
 - 1. Framing with dimension lumber.
 - 2. Framing with engineered wood products.
 - 3. Wood furring, grounds, nailers, and blocking.
 - 4. Sheathing.
 - 5. Subflooring.
 - 6. Underlayment.
- B. Related Sections: The following Sections contain requirements that relate to this Section:
 - 1. Division 6 Section "Finish Carpentry" for nonstructural carpentry items exposed to view and not specified in another Section.

1.3 DEFINITIONS

- A. Rough Carpentry: Carpentry work not specified in other Sections and not exposed, unless otherwise specified.

1.4 SUBMITTALS

- A. General: Submit each item in this Article according to the Conditions of the Contract and Division 1 Specification Sections.
- B. Product Data for the following products:
 - 1. Engineered wood products.
 - 2. Underlayment.
 - 3. Insulating sheathing.
 - 4. Air-infiltration barriers.
 - 5. Construction adhesives.
- C. Material certificates for dimension lumber specified to comply with minimum allowable unit stresses. Indicate species and grade selected for each use and design values approved by the American Lumber Standards Committee's (ALSC) Board of Review.
- D. Wood treatment data as follows, including chemical treatment manufacturer's instructions for handling, storing, installing, and finishing treated materials:
 - 1. For each type of preservative-treated wood product, include certification by treating plant stating type of preservative solution and pressure process used, net amount of preservative retained, and compliance with applicable standards.
 - 2. For waterborne-treated products, include statement that moisture content of treated materials was reduced to levels indicated before shipment to Project site.
 - 3. For fire-retardant-treated wood products, include certification by treating plant that treated materials comply with specified standard and other requirements as well as data relative to bending strength, stiffness, and fastener-holding capacities of treated materials.
- E. Material test reports from a qualified independent testing agency indicating and interpreting test results relative to compliance of fire-retardant-treated wood products with requirements indicated.
- F. Warranty of chemical treatment manufacturer for each type of treatment.
- G. Research or evaluation reports of the Southern Standard Building Code Congress acceptable to authorities having jurisdiction that evidence the following products' compliance with building code in effect for Project.
 - 1. Engineered wood products.
 - 2. Foam-plastic sheathing.

3. Air-infiltration barriers.
4. Power-driven fasteners.
5. Fire-retardant-treated wood.

1.5 QUALITY ASSURANCE

- A. Single-Source Responsibility for Engineered Wood Products: Obtain each type of engineered wood product from one source and by a single manufacturer.
- B. Single-Source Responsibility for Fire-Retardant-Treated Wood: Obtain each type of fire-retardant-treated wood product from one source and by a single producer.

1.6 DELIVERY, STORAGE, AND HANDLING

- A. Keep materials under cover and dry. Protect from weather and contact with damp or wet surfaces. Stack lumber, plywood, and other panels. Provide for air circulation within and around stacks and under temporary coverings.
 1. For lumber and plywood pressure treated with waterborne chemicals, place spacers between each bundle to provide air circulation.

PART 2 - PRODUCTS

2.1 MANUFACTURERS

- A. Available Manufacturers: Subject to compliance with requirements, manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:

2.2 LUMBER, GENERAL

- A. Lumber Standards: Comply with DOC PS 20, "American Softwood Lumber Standard," and with applicable grading rules of inspection agencies certified by ALSC's Board of Review.
- B. Inspection Agencies: Inspection agencies, and the abbreviations used to reference them, include the following:
 1. SPIB - Southern Pine Inspection Bureau.
- C. Grade Stamps: Provide lumber with each piece factory marked with grade stamp of inspection agency evidencing compliance with grading rule requirements and identifying grading agency, grade, species, moisture content at time of surfacing, and mill.
 1. For exposed lumber, furnish pieces with grade stamps applied to ends or back of each piece, or omit grade stamps and provide grade-compliance certificates issued by inspection agency.
- D. Where nominal sizes are indicated, provide actual sizes required by DOC PS 20 for moisture content specified. Where actual sizes are indicated, they are minimum dressed sizes for dry lumber.
 1. Provide dressed lumber, S4S, unless otherwise indicated.
 2. Provide dry lumber with 19 percent maximum moisture content at time of dressing for 2-inch nominal thickness or less, unless otherwise indicated.

2.3 WOOD-PRESERVATIVE-TREATED MATERIALS

- A. General: Where lumber or plywood is indicated as preservative treated or is specified to be treated, comply with applicable requirements of AWWA C2 (lumber) and AWWA C9 (plywood). Mark each treated item with the Quality Mark Requirements of an inspection agency approved by ALSC's Board of Review.
 1. Do not use chemicals containing chromium or arsenic.
- B. Pressure treat aboveground items with waterborne preservatives to a minimum retention of 0.25 lb/cu. Ft.. After treatment, kiln-dry lumber and plywood to a maximum moisture content of 19 and 15 percent, respectively. Treat indicated items and the following:
 1. Wood cants, nailers, curbs, equipment support bases, blocking, stripping, and similar members in connection with roofing, flashing, vapor barriers, and waterproofing.
 2. Wood sills, sleepers, blocking, furring, stripping, and similar concealed members in contact with masonry or concrete.
 3. Wood framing members less than 18 inches above grade.

4. Wood floor plates installed over concrete slabs directly in contact with earth.
- C. Complete fabrication of treated items before treatment, where possible. If cut after treatment, apply field treatment complying with AWPA M4 to cut surfaces. Inspect each piece of lumber or plywood after drying and discard damaged or defective pieces.

2.4 FIRE-RETARDANT-TREATED MATERIALS

- A. General: Where fire-retardant-treated wood is indicated, comply with applicable requirements of AWPA C20 (lumber) and AWPA C27 (plywood). Identify fire-retardant-treated wood with appropriate classification marking of UL; U.S. Testing; Timber Products Inspection, Inc.; or another testing and inspecting agency acceptable to authorities having jurisdiction.
 1. Research or Evaluation Reports: Provide fire-retardant-treated wood acceptable to authorities having jurisdiction and for which a current model code research or evaluation report exists that evidences compliance of fire-retardant-treated wood for application indicated.
- B. Interior Type A: For interior locations, use chemical formulation that produces treated lumber and plywood with the following properties under conditions present after installation:
 1. Bending strength, stiffness, and fastener-holding capacities are not reduced below values published by manufacturer of chemical formulation under elevated temperature and humidity conditions simulating installed conditions when tested by a qualified independent testing agency.
 2. No form of degradation occurs due to acid hydrolysis or other causes related to treatment.
 3. Contact with treated wood does not promote corrosion of metal fasteners.
- C. Exterior Type: Use for exterior locations and where indicated.
- D. Inspect each piece of treated lumber or plywood after drying and discard damaged or defective pieces.

2.5 DIMENSION LUMBER

- A. General: Provide dimension lumber of grades indicated according to the ALSC National Grading Rule (NGR) provisions of the inspection agency indicated.
- B. Non-Load-Bearing Interior Partitions: Provide framing of the following grade and species:
 1. Grade: Standard, Stud, or No. 3.
 2. Species: Southern pine; SPIB.
- C. Exterior and Load-Bearing Walls: Provide framing of the following grade and species:
 1. Grade: Construction or No. 2.
 2. Species: Southern pine; SPIB.
- D. Ceilings (Non-Load-Bearing): For ceiling framing that does not support a floor, roof, or attic, provide the following grade and species:
 1. Grade: Construction or No. 2.
 2. Species: Southern pine; SPIB.
- E. Other Framing Not Listed Above: Provide the following grades and species:
 1. Grade: Construction or No. 2.
 2. Species: Southern pine; SPIB.

2.6 MISCELLANEOUS LUMBER

- A. General: Provide lumber for support or attachment of other construction, including cant strips, bucks, nailers, blocking, furring, grounds, stripping, and similar members.
- B. Fabricate miscellaneous lumber from dimension lumber of sizes indicated and into shapes shown.
- C. Moisture Content: 19 percent maximum for lumber items not specified to receive wood preservative treatment.
- D. Grade: For dimension lumber sizes, provide No. 3 or Standard grade lumber per ALSC's NGRs of any species. For board-size lumber, provide No. 3 Common grade per NELMA, NLGA, or WWPA; No. 2 grade per SPIB; or Standard grade per NLGA, WCLIB or WWPA of any species.

2.7 WOOD-BASED STRUCTURAL-USE PANELS, GENERAL

- A. Structural-Use Panel Standards: Provide either all-veneer, mat-formed, or composite panels

complying with DOC PS 2, "Performance Standard for Wood-Based Structural-Use Panels," unless otherwise indicated. Provide plywood panels complying with DOC PS 1, "U.S. Product Standard for Construction and Industrial Plywood," where plywood is indicated.

- B. Trademark: Factory mark structural-use panels with APA trademark evidencing compliance with grade requirements.

2.8 CONCEALED, PERFORMANCE-RATED STRUCTURAL-USE PANELS

- A. General: Where structural-use panels are indicated for the following concealed types of applications, provide APA-performance-rated panels complying with requirements designated under each application for grade, span rating, exposure durability classification, and edge detail (where applicable).
 - 1. Thickness: Provide panels meeting requirements specified but not less than thickness indicated.
 - 2. Span Ratings: Provide panels with span ratings required to meet "Code Plus" provisions of APA Form No. E30, "APA Design/Construction Guide: Residential & Commercial."
- B. Subflooring: APA-rated sheathing.
 - 1. Exposure Durability Classification: Exterior.
 - 2. Span Rating: As required to suit joist spacing indicated.
- C. Wall Sheathing: APA-rated sheathing.
- D. Roof Sheathing: APA-rated sheathing.
- E. Roof Sheathing: APA-rated Structural I sheathing.

2.9 STRUCTURAL-USE PANELS FOR BACKING

- A. Plywood Backing Panels: For mounting electrical or telephone equipment, provide fire-retardant-treated plywood panels with grade, C-D Plugged Exposure 1, in thickness indicated or, if not otherwise indicated, not less than 15/32 inch thick.

2.10 STRUCTURAL-USE PANELS FOR UNDERLAYMENT

- A. Plywood Underlayment for Resilient Flooring: For underlayment 19/32 inch thick, provide plywood panels with fully sanded face and as follows:
 - 1. Grade: APA A-C Underlayment Exterior.

2.11 GYPSUM SHEATHING

- A. Gypsum Sheathing Board: Water-resistant-core gypsum sheathing board complying with ASTM C 79 with long edges surfaced with water-repellent paper and as follows:
 - 1. Type: X.
 - 2. Edge Configuration: Square, for vertical application.
 - 3. Thickness: 5/8 inch.

2.12 FOAM-PLASTIC SHEATHING

- A. Extruded Cellular Polystyrene Sheathing: ASTM C 578, Type IV, in manufacturer's standard lengths and widths with T & G or shiplap long edges as standard with manufacturer.
 - 1. Thickness: 1 inch.
- B. Polyisocyanurate Foam Sheathing: Rigid, closed-cell foam board; formed by expanding polyisocyanurate resin using hydrochlorofluorocarbons (HCFCs); with aluminum foil facings laminated to both sides; complying with FS HH-I-1972/1, Class 1 or 2; with a thermal resistance (R-value) for 1-inch thickness of 7.2 deg F x h x sq. ft./Btu at 75 deg F; in thicknesses indicated. Foam-plastic core, 4-1/4 inches thick or less, and facings shall have flame spread of 25 or less, when tested individually.

2.13 AIR-INFILTRATION BARRIER

- A. Asphalt-saturated organic felt complying with ASTM D 226, Type I (No. 15 asphalt felt), unperforated.
- B. Air retarder complying with ASTM E 1677; made from polyolefins; either cross-laminated films, woven strands, or spunbonded fibers; coated or uncoated; with or without perforations to transmit water vapor but not liquid water; and as follows:

1. Minimum Thickness: 3 mils.
2. Minimum Water-Vapor Transmission: 10 perms when tested according to ASTM E 96, Procedure A.
3. Maximum Flame Spread: 25 per ASTM E 84.
4. Minimum Allowable Exposure Time: 3 months.

2.14 FASTENERS

- A. General: Provide fasteners of size and type indicated that comply with requirements specified in this Article for material and manufacture.
 1. Where rough carpentry is exposed to weather, in ground contact, or in area of high relative humidity, provide fasteners with a hot-dip zinc coating per ASTM A 153 or of Type 304 stainless steel.
- B. Nails, Wire, Brads, and Staples: FS FF-N-105.
- C. Power-Driven Fasteners: CABO NER-272.
- D. Wood Screws: ASME B18.6.1.
- E. Lag Bolts: ASME B18.2.1.
- F. Bolts: Steel bolts complying with ASTM A 307, Grade A; with ASTM A 563 hex nuts and, where indicated, flat washers.

2.16 MISCELLANEOUS MATERIALS

- A. Sill-Sealer Gaskets: Glass-fiber-resilient insulation, fabricated in strip form, for use as a sill sealer; 1-inch nominal thickness, compressible to 1/32 inch; selected from manufacturer's standard widths to suit width of sill members indicated.
- B. Adhesives for Field Gluing Panels to Framing: Formulation complying with APA AFG-01 that is approved for use with type of construction panel indicated by both adhesive and panel manufacturers.
- C. Water-Repellent Preservative: NWWDA-tested and -accepted formulation containing 3-iodo-2-propynyl butyl carbonate (IPBC) as its active ingredient.

PART 3 – EXECUTION

3.1 INSTALLATION, GENERAL

- A. Discard units of material with defects that impair quality of rough carpentry and that are too small to use with minimum number of joints or optimum joint arrangement.
- B. Set rough carpentry to required levels and lines, with members plumb, true to line, cut, and fitted.
- C. Fit rough carpentry to other construction; scribe and cope as required for accurate fit. Correlate location of furring, nailers, blocking, grounds, and similar supports to allow attachment of other construction.
- D. Apply field treatment complying with AWPA M4 to cut surfaces of preservative-treated lumber and plywood.
- E. Securely attach rough carpentry work to substrate by anchoring and fastening as indicated, complying with the following:
 1. "Table 1705.1--Fastening Schedule," of the Standard Building Code.
- F. Use common wire nails, unless otherwise indicated. Use finishing nails for finish work. Select fasteners of size that will not fully penetrate members where opposite side will be exposed to view or will receive finish materials. Make tight connections between members. Install fasteners without splitting wood; predrill as required.
- G. Use hot-dip galvanized or stainless-steel nails where rough carpentry is exposed to weather, in ground contact, or in area of high relative humidity.
- H. Countersink nail heads on exposed carpentry work and fill holes with wood filler.

3.2 WOOD GROUNDS, NAILERS, BLOCKING, AND SLEEPERS

- A. Install wood grounds, nailers, blocking, and sleepers where shown and where required for screeding or attaching other work. Form to shapes shown and cut as required for true line and level of attached work. Coordinate locations with other work involved.

- B. Attach to substrates to support applied loading. Recess bolts and nuts flush with surfaces, unless otherwise indicated. Build into masonry during installation of masonry work. Where possible, anchor to formwork before concrete placement.

3.3 WOOD FURRING

- A. Install plumb and level with closure strips at edges and openings. Shim with wood as required for tolerance of finish work.
 - 1. Firestop furred spaces of walls at each floor level and at ceiling with wood blocking or noncombustible materials, accurately fitted to close furred spaces.
- B. Furring to Receive Plywood Paneling: Install 1-by-3-inch nominal- size furring at 24 inches o.c., horizontally and vertically. Select furring with no knots capable of producing bent-over nails and damage to paneling.
- C. Furring to Receive Gypsum Board: Install 1-by-2-inch nominal- size furring at 16 inches o.c., vertically.
- D. Furring to Receive Plaster Lath: Install 1-by-2-inch nominal- size furring at 16 inches o.c., vertically.

3.4 WOOD FRAMING, GENERAL

- A. Framing Standard: Comply with AFPA's "Manual for Wood Frame Construction," unless otherwise indicated.
- B. Install framing members of size and at spacing indicated.
- C. Do not splice structural members between supports.
- D. Firestop concealed spaces of wood-framed walls and partitions at each floor level and at ceiling line of top story. Where firestopping is not inherent in framing system used, provide closely fitted wood blocks of 2-inch nominal- thickness lumber of same width as framing members.

3.5 WALL AND PARTITION FRAMING

- A. General: Arrange studs so that wide face of stud is perpendicular to direction of wall or partition and narrow face is parallel. Provide single bottom plate and double top plates using members of 2-inch nominal thickness whose widths equal that of studs; except single top plate may be used for non-load-bearing partitions. Nail or anchor plates to supporting construction, unless otherwise indicated.
 - 1. For exterior walls, provide 2-by-4-inch nominal- size wood studs spaced 16 inches o.c., except where otherwise indicated or required.
 - 2. For interior partitions and walls, provide 2-by-4-inch nominal- size wood studs spaced 16 inches o.c., except where otherwise indicated or required.
- B. Construct corners and intersections with 3 or more studs. Provide miscellaneous blocking and framing as shown and as required to support facing materials, fixtures, specialty items, and trim.
 - 1. Provide continuous horizontal blocking at midheight of single-story partitions over 96 inches high and multistory partitions, using members of 2-inch nominal thickness and of same width as wall or partitions.
- C. Frame openings with multiple studs and headers. Provide nailed header members of thickness equal to width of studs. Set headers on edge and support on jamb studs.
 - 1. For non-load-bearing partitions, provide double-jamb studs with headers not less than 4-inch nominal depth for openings 36 inches and less in width, and not less than 6-inch nominal depth for wider openings.
 - 2. For load-bearing walls, provide double-jamb studs for openings 72 inches and less in width, and triple-jamb studs for wider openings. Provide headers of depth shown or, if not shown, as recommended by AFPA's "Manual for Wood Frame Construction."
- D. Provide bracing in exterior walls, at both walls of each external corner, full-story height, unless otherwise indicated.

3.6 INSTALLATION OF STRUCTURAL-USE PANELS

- A. General: Comply with applicable recommendations contained in APA Form No. E30, "APA Design/Construction Guide: Residential & Commercial," for types of structural-use panels and applications indicated.

1. Comply with "Code Plus" provisions of above-referenced guide.
 - B. Fastening Methods: Fasten panels as indicated below:
 1. Subflooring: Glue and nail to framing throughout (see plans).
 - a. Space panels 1/8 inch at edges and ends.
 2. Sheathing: Nail to framing.
 - a. Space panels 1/8 inch at edges and ends.
 3. Underlayment: Nail to subflooring.
 - a. Space panels 1/32 inch at edges and ends.
 - b. Fill and sand edge joints of underlayment receiving resilient flooring just before installing flooring.
 4. Plywood Backing Panels: Nail or screw to supports.
- 3.7 FOAM-PLASTIC SHEATHING
- A. Comply with manufacturer's written instructions for applying sheathing. Install vapor relief strips or equivalent for permitting escape of moisture vapor that otherwise would be trapped in stud cavity behind sheathing.
- 3.8 FIBERBOARD SHEATHING
- A. Fasten fiberboard sheathing panels to intermediate supports and then at edges and ends. Use galvanized roofing nails or galvanized staples. Nail or staple to comply with manufacturer's recommended spacing and referenced fastening schedule. Drive fasteners flush with surface of sheathing and locate perimeter fasteners at least 3/8 inch from edges and ends.
 - B. Install 48-by-96-inch or longer sheathing vertically with long edges parallel to, and centered over, studs. Install solid wood blocking where end joints do not occur over framing. Allow 1/8-inch open space between edges and ends of adjacent units. Stagger horizontal joints, if any.
 - C. Apply air-infiltration barrier over sheathing as soon as practical after installation to prevent deterioration from wetting.
- 3.9 AIR-INFILTRATION BARRIER
- A. Cover sheathing with air-infiltration barrier as follows:
 1. Apply air-infiltration barrier to cover upstanding flashing with 4-inch overlap.

END OF SECTION 06100

**SECTION 06200
FINISH CARPENTRY**

PART 1 - GENERAL

1.1 RELATED DOCUMENTS:

- A. Drawings and general provisions of Contract, including General and Supplementary Conditions and Division-1 Specification sections, apply to work of this section.

1.2 DESCRIPTION OF WORK:

- A. Definition: Finish carpentry includes carpentry work which is exposed to view, is non-structural, and which is not specified as part of other sections.
- B. Types of finish carpentry work in the section include:
 - 1. Interior and exterior running and standing trim.

1.3 SUBMITTALS:

- A. Samples: Submit the following samples for each species and cut or pattern of finish carpentry.
 - 1. Interior and exterior standing and running trim.

1.4 PRODUCT DELIVERY, STORAGE AND HANDLING:

- A. Protect finish carpentry materials during transit, delivery, storage and handling to prevent damage, soiling and deterioration.
- B. Do not deliver finish carpentry materials, until painting, wet work, grinding and similar operations which could damage, soil or deteriorate woodwork have been completed in installation areas. If, due to unforeseen circumstances, finish carpentry materials must be stored in other than installation areas, store only in areas meeting requirements specified for installation areas.

1.5 JOB CONDITIONS:

- A. Conditioning: Installer shall advise Contractor of temperature and humidity requirements for finish carpentry installation areas. Do not install finish carpentry until required temperature and relative humidity have been stabilized and will be maintained in installation areas.
- B. Maintain temperature and humidity in installation area as required to maintain moisture content of installed finish carpentry within a 1.0 percent tolerance of optimum moisture content, from date of installation through remainder of construction period. The fabricator of woodwork shall determine optimum moisture content and required temperature and humidity conditions.

PART 2 - PRODUCTS

2.1 WOOD PRODUCT QUALITY STANDARDS:

- A. Softwood Lumber Standards: Comply with PS 20 and with applicable grading rules of the respective grading and inspecting agency for the species and product indicated.
- B. Hardwood Lumber Standard: Comply with National Hardwood Lumber Association (NHLA) rules.
- C. Woodworking Standard: Where indicated for a specific product comply with specified provision of the following:
 - 1. Architectural Woodwork Institute (AWI) "Quality Standards".

2.2 MATERIALS:

- A. General:
 - 1. Nominal sizes are indicated, except as shown by detailed dimensions. Provide dressed or worked and dressed lumber, as applicable, manufactured to the actual sizes as required by PS 20 or to actual sizes and patterns as shown, unless otherwise indicated.

2. Moisture Content of Softwood Lumber: Provide seasoned (KD) lumber having a moisture content from time of manufacture until time of installation not greater than values required by the applicable grading rules of the respective grading and inspecting agency for the species and product indicated.
 3. Moisture Content of Hardwood Lumber: Provide kiln-dried (KD) lumber having a moisture content from time of manufacture until time of installation within the ranges required in the referenced woodworking standard.
 4. Lumber for Painted Finish: At Contractor's option, use pieces which are either glued-up lumber or made of solid lumber stock.
- B. Interior Finish Carpentry:
1. Standing and Running Trim for Painted Finish: Any Western soft- wood or Southern Yellow Pine species graded and inspected by WWPA complying with following requirements.
 - a. Grade for Standard Sizes and Patterns: "C Select"
- C. Miscellaneous Materials:
1. Fasteners and Anchorages: Provide nails, screws and other anchoring devices of the type, size, material and finish required for application indicated to provide secure attachment, concealed where possible, and complying with applicable Federal Specifications.

PART 3 - EXECUTION

3.1 PREPARATION:

- A. Condition wood materials to average prevailing humidity conditions in installation areas prior to installing.
- B. Pre-Installation Meeting: Meet at project site prior to delivery of finish carpentry materials and review coordination and environmental controls required for proper installation and ambient conditioning in areas to receive work. Include in meeting the Contractor, Architect and Owner Representatives (If any), Installers of finish carpentry, wet work including plastering, other finishes, painting, mechanical work and electrical work, and firms and persons responsible for continued operation (whether temporary or permanent) of HVAC system as required to maintain temperature and humidity conditions. Proceed with finish carpentry on interior only when everyone concerned agrees that required ambient conditions can be properly maintained.

3.2 INSTALLATION:

- A. Discard units of material which are unsound, warped, bowed twisted, improperly treated, not adequately seasoned or too small to fabricate work with minimum of joints or optimum jointing arrangements, or which are of defective manufacturer with respect to surfaces, sizes or patterns.
- B. Install the work plumb, level, true and straight with no distortions. Shim as required using concealed shims. Install to a tolerance of 1/8" in 8'-0" for plumb and level countertops; and with 1/16" maximum offset in flush adjoining 1/8" maximum offsets in revealed adjoining surfaces.
- C. Scribe and cut work to fit adjoining work, and refinish cut surfaces or repair damaged finish at cuts.
- D. Standing and Running Trim: Install with minimum number of joints possible, using full-length pieces (from maximum lengths of lumber available) to the greatest extent possible. Stagger joints in adjacent and related members. Cope at returns, miter at corners, to produce tight fitting joints with full surface contact throughout length of joint. Use scarf joints for end-to-end joints.
- E. Anchor finish carpentry work to anchorage devices or blocking built-in directly attached to substrates. Secure to grounds, stripping and blocking with countersunk, concealed fasteners and blind nailing as required for a complete installation. Except where prefinished matching fasteners heads are required, use fine finishing nail for exposed nailings, countersunk and filled flush with finished surface, and matching final finish where transparent is indicated.

3.3 ADJUSTMENT, CLEANING, FINISHING AND PROTECTION:

- A. Repair damaged and defective finish carpentry work wherever possible to eliminate defects functionally and visually; where not possible to repair properly, replace woodwork. Adjust joinery for uniform appearance.
- B. Refer to Division-9 sections for final finishing of installed finish carpentry work.
- C. Protection: Installer of finish carpentry work shall advise Contractor of final protection and maintained conditions necessary to ensure that work will be without damage or deterioration at time of acceptance.

END OF SECTION 06200

**SECTION 07311
ASPHALT SHINGLES**

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 1 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes asphalt shingles for roofs.
- B. Related Sections: The following Sections contain requirements that relate to this Section:
 - 1. Division 6 Section "Rough Carpentry" for wood sheathing and framing.
 - 2. Division 7 Section "Flashing and Sheet Metal" for metal valley flashing, step flashing, drip edges, and other sheet metal work.

1.3 SUBMITTALS

- A. General: Submit each item in this Article according to the Conditions of the Contract and Division 1 Specification Sections.
- B. Product data for each type of product specified, including details of construction relative to materials, dimensions of individual components, profiles, textures, and colors.
- C. Samples for initial selections in the form of manufacturer's sample finishes showing the full range of colors and profiles available for each type of asphalt shingle indicated.
- D. Samples for verification in the form of 2 full-size units of each type of asphalt shingle indicated showing the full range of variations expected in these characteristics.

1.4 DELIVERY, STORAGE, AND HANDLING

- A. Deliver materials to Project site in manufacturer's unopened bundles or containers with labels intact.
- B. Handle and store materials at Project site to prevent water damage, staining, or other physical damage. Store roll goods on end. Comply with manufacturer's recommendations for job-site storage, handling, and protection.

1.5 PROJECT CONDITIONS

- A. Weather Limitations: Proceed with installing asphalt shingles only when existing and forecasted weather conditions will permit work to be performed according to manufacturers' recommendations and warranty requirements, and when substrate is completely dry.

1.6 WARRANTY

- A. General Warranty: The special warranty specified in this Article shall not deprive the Owner of other rights the Owner may have under other provisions of the Contract Documents and shall be in addition to, and run concurrent with, other warranties made by the Contractor under requirements of the Contract Documents.
- B. Special Warranty: Submit a written warranty signed by manufacturer agreeing to repair or replace asphalt shingles that fail in materials or workmanship within the specified warranty period. Failures include, but are not limited to, deformation or deterioration of asphalt shingles beyond normal weathering.
 - 1. Warranty Period: Manufacturer's standard but not less than 30 years after date of Substantial Completion.

1.7 EXTRA MATERIALS

- A. Furnish extra materials described below that match products installed, are packaged with protective covering for storage, and are identified with labels clearly describing contents.
 - 1. Furnish 1 square coverage for each color of asphalt shingles, identical to those to be installed, in unbroken bundles.

PART 2 - PRODUCTS

2.1 MANUFACTURERS

- A. Manufacturers: Subject to compliance with requirements, provide asphalt shingles produced by one of the following (or approved equal):
 - 1. Atlas Roofing Corp.
 - 2. CertainTeed Corporation.
 - 3. GAF Building Materials Corporation.
 - 4. Owens-Corning Fiberglas Corp.
 - 5. Tamko Asphalt Products, Inc.
- B. Available Products: Subject to compliance with requirements, products that to be incorporated in the Work include the following (or approved equal):
 - 1. Nail Over Ridge Vents:
 - a. Ridge Filter Shinglevent; Air Vent, Inc.
 - b. Cobra Ridge Vent; GAF Building Materials Corporation.
 - c. Roll Vent; Obdyke: Benjamin Obdyke, Inc.
 - d. Ventsure rigid roll: Owens-Corning Fiberglas Corp.

2.2 ASPHALT SHINGLES

- A. Colors, Blends, and Patterns: Where manufacturer's standard products are indicated, provide asphalt shingles with the following requirements:
 - 1. Provide Architect's selections from manufacturer's full range of colors, textures, and patterns for asphalt shingles of type indicated. Four colors shall be selected for use.
- B. Dimensional /30 Shake FRS, class A rating. Fiberglass, Laminated Strip Shingles: Mineral-surfaced, self-sealing, laminated, multi-ply overlay construction, fiberglass-based, strip asphalt shingles, complying with both ASTM D 3018, Type I, and ASTM D 3462. FRS.
- C. Ridge Shingles: Manufacturer's standard, factory-precut units to match asphalt shingles.

2.3 METAL TRIM AND FLASHING

- A. Sheet Metal Materials: Furnish the following sheet metal materials:
 - 1. Prefinished aluminum Sheets: ASTM B 209, alloy 3003 H14, minimum 0.024 inch thick, unless otherwise indicated.
- B. Metal Drip Edge: Brake-formed sheet metal with at least a 3-inch roof deck flange and a 1-1/2-inch fascia flange with a 3/8-inch drip at lower edge. Furnish the following material in lengths of 10 feet.
 - 1. Material: Prefinished aluminum sheets. The finish shall be a two-coat acrylic in a two-phase operation that includes corrosion-inhibiting primer and a baked-on, high-performance acrylic topcoat.
- C. Metal Flashing: Job-cut to sizes and configurations required.
 - 1. Material: Prefinished aluminum sheets. The finish shall be a two-coat acrylic in a two-phase operation that includes corrosion-inhibiting primer and a baked-on, high-performance acrylic topcoat.
- D. Vent Pipe Flashing: Lead conforming to ASTM B 749, Type L51121, at least 1/16 inch thick, unless otherwise indicated. Provide lead sleeve sized to slip over and turn down into pipe, soldered to skirt at slope of roof extending at least 4 inches from pipe onto roof.

2.4 ACCESSORIES

- A. Felt Underlayment: 1-layer, Type I, 36-inch- wide, asphalt-saturated organic felt, complying with ASTM D 226 (No. 15) or ASTM D 4869.
- B. Ridge Vent: High-density polypropylene, nonwoven modified polyester, or other UV-stabilized plastic designed to be installed under asphalt shingles at ridge.
- C. Nails: Aluminum or hot-dip galvanized steel, 0.120-inch- diameter barbed shank, sharp-pointed, conventional roofing nails with a minimum 3/8-inch- diameter head and of sufficient length to penetrate 3/4 inch into solid decking or at least 1/4 inch through plywood sheathing.
 - 1. Where nails are in contact with flashing, prevent galvanic action by providing nails made from the same metal as that of the flashing.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine substrate for compliance with requirements for substrates, installation tolerances, and other conditions affecting performance of asphalt shingles. Do not proceed with installation until unsatisfactory conditions have been corrected.

3.2 PREPARATION

- A. Clean substrates of projections and substances detrimental to application. Cover knotholes or other minor voids in substrate with sheet metal flashing secured with noncorrosive roofing nails.
- B. Coordinate installation with flashings and other adjoining work to ensure proper sequencing. Do not install roofing materials until all vent stacks and other penetrations through roof sheathing have been installed and are securely fastened against movement.

3.3 INSTALLATION

- A. General: Comply with manufacturer's instructions and recommendations but not less than those recommended by ARMA's "Residential Asphalt Roofing Manual" or "The NRCA Steep Roofing Manual."
 - 1. Fasten asphalt shingles to roof sheathing with nails.
- B. Felt Underlayment: Apply 1 layer of felt underlayment horizontally over entire surface to receive asphalt shingles, lapping succeeding courses a minimum of 2 inches, end laps a minimum of 4 inches, and hips and valleys a minimum of 6 inches. Fasten felt with sufficient number of roofing nails to hold underlayment in place until asphalt shingle installation.
- C. Underlayment at Closed Valleys: Center a 36-inch- wide felt underlayment in valley and secure with only enough nails to hold in place until asphalt shingles are installed. Lap roof underlayment over valley underlayment at least 6 inches.
- D. Flashing: Install metal flashing and trim as indicated and according to details and recommendations of the "Asphalt Roofing" section of "The NRCA Steep Roofing Manual" and ARMA's "Residential Asphalt Roofing Manual."
- E. Install asphalt shingles, beginning at roof's lower edge, with a starter strip of roll roofing or inverted asphalt shingles with tabs removed. Fasten asphalt shingles in the desired weather exposure pattern; use number of fasteners per shingle as recommended by manufacturer. Use vertical and horizontal chalk lines to ensure straight coursing.
 - 1. Cut and fit asphalt shingles at valleys, ridges, and edges to provide maximum weather protection. Provide same weather exposure at ridges as specified for roof. Lap asphalt shingles at ridges to shed water away from direction of prevailing wind.
 - 2. Use fasteners at ridges of sufficient length to penetrate sheathing as specified.
- F. Ridge Vents: Install ridge vents according to manufacturer's instructions.

3.4 ADJUSTING

- A. Replace any damaged materials installed under this Section with new materials that meet specified requirements.

END OF SECTION 07311

**SECTION 07460
VINYL SIDING AND ALUMINUM TRIM**

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of contract, including General and Supplementary Conditions and Division 1 Specification sections, apply to work of this section.

1.2 DESCRIPTION OF WORK

- A. Extent of siding is indicated on drawings. Extent of aluminum fascia, soffit and drip edge system is indicated on the drawings.
- B. Types of siding specified in this section include the following:
 - 1. Aluminum fascia/soffit/drip edge system.
 - 2. Horizontal vinyl siding.

1.3 SUBMITTALS

- A. Product Data: Submit specifications, installation instructions, and general recommendations from siding and trim manufactures, including data that materials comply with requirements.
- B. Samples: Full range of samples for color and texture selection; 2-12" lengths or 2-12" square pieces for verification of each color/style/texture selected.
- C. Provide manufacturer's standard warranty on installed work, agreeing to inspect, repair and replace defective work.

1.4 JOB CONDITIONS

- A. Substrate: Proceed with siding accessory work only after substrate construction and penetrating work have been completed.
- B. Weather Conditions: Proceed with siding accessory work only when substrate is completely dry.
- C. Store materials at site to prevent warping and weather damage, elevating above ground on level blocking and covering to prevent water damage and to permit adequate ventilation within bundles.

PART 2 - PRODUCTS

2.1 MATERIAL

- A. Provide products from a single manufacturer. Color for vinyl siding, fascia, soffit and accessories to be selected from manufacturer's standard colors by Architect. Provide four colors as selected by the Architect.
- B. Items specified are manufactured by companies shown below; products of other manufacturers are acceptable if equal to those specified in appearance, performance and physical qualities. Submit substitutions in accordance with Section 01330.
- C. Vinyl Siding: "Liberty Elite" Siding.
 - 1. Product Description: Double 4 profile, 8 inches exposure; nominal 0.048 inch material thickness; nominal 12 feet 6 inch piece length.
 - 2. Nailing Hem: Single-row, with elongated nailing holes 1-1/4 inches long at 1-5/8 inches on center.
 - 3. Finish: Wood grain texture.
 - 4. Color: As selected from manufacturer's full range of available colors. Provide four colors as selected by the Architect.
- D. Aluminum Soffit Panels: Envoy V-Groove Series Soffit.
 - 1. Style: 12 inch (304.8 mm) wide panels, 3/8 inch (9.5 mm) deep, with double 5.5 inch (139.7 mm) wide faces forming V-grooves at 6 inches (152.4 mm) on center.
 - 2. Thickness: Nominal 0.019 inch (0.5 mm); aluminum alloy 3105-H26P:

- a. Minimum Tensile Strength: 28,000 psi (1,968,596 g/sq cm).
 - b. Minimum Yield Strength: 25,000 psi (1,757,675 g/sq cm).
 3. Interlocking edges and elongated nailing hems.
 4. Finish: Alupalure 2000; two-phase operation including corrosion-inhibiting primer and baked-on high-performance acrylic topcoat.
 5. Color as selected by Architect from manufacturer's full line. Provide four colors to be selected by the Architect.
 6. Supply non-ventilating type soffit material (at porch ceilings only).
 7. Supply ventilating type soffit material having perforations: 1/16 inch (1.58 mm) diameter holes on 5/32 inch (3.9 mm) staggered centers in a uniform 5 inch (127 mm) wide pattern along entire panel length.
 - a. 12-Inch Wide Panel: 15 square inches per linear foot (2.94 square m per linear m) net free area.
- E. Fascia:
1. 1" Butt Wood grain, .024 nominal thick aluminum preformed fascia with Alupalure 2000 finish. Aluminum fascia panel size indicated on the drawing, 12'-1" lengths.
 2. Manufacturer: Alcoa Building Products.
 3. Provide four colors to be selected by the Architect.
- F. Accessories (Aluminum):
1. 1/2" F-Channel Frieze.
 2. "H" Divider Bar.
 3. Other accessories as needed for a complete finished installation.
 4. Manufacturer: Alcoa Building Products.
- G. Miscellaneous Materials:
1. Sealants: Comply with requirements of Division-7 Section on caulking and sealants for materials required for siding work. Sealant color to match soffit and fascia color.
 2. Fasteners: Noncorrosive aluminum nails, in sufficient length to penetrate minimum of 1-inch into substrate. Provide prefinished fasteners in color to match soffit and fascia where face nailing is unavailable.

PART 3 - EXECUTION

3.1 INSTALLATION

- A. General: Before starting work, verify governing dimensions at building; examine, clean and repair, if necessary, any adjoining work on which this work in any way is dependent for its proper installation. Comply with instructions and recommendations of manufacture, except to extent more stringent requirements are indicated.
- B. Vinyl Siding: Install in accordance with the "Alcoa Building Products Vinyl Siding, Soffit and Designer Accessories Installation Manual" published by the Society of the Plastics Industry, Inc. Alcoa accessory trim shall be used along with the siding.
- C. Aluminum Soffit and Fascia: Install accessories, soffit panels and fascia panels as recommended by manufacturer. Install with tolerances and fasteners spacing as per manufacturer instructions. Install with concealed fasteners. No face nailing is allowed.
- D. Leave in clean condition, free of dirt, dust and finger marks. Replace any poorly fitting, dented or damaged portions of the work.

END OF SECTION 07460

SECTION 07620
SHEET METAL FLASHING AND TRIM

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 1 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes sheet metal flashing and trim in the following categories:
 - 1. Metal flashing.
 - 2. Reglets.
- B. Related Sections: The following Sections contain requirements that relate to this Section:
 - 1. Division 4 Sections for through-wall flashing and other integral masonry flashings specified as part of masonry work.
 - 2. Division 7 Section "Roof Accessories" for set-on-type curbs, equipment supports, roof hatches, vents, and other manufactured roof accessory units.
 - 3. Division 7 Section "Joint Sealants" for elastomeric sealants.
 - 4. Division 7 Roofing Sections for flashing and roofing accessories installed integral with asphalt shingle roofing as part of roofing-system work.

1.3 PERFORMANCE REQUIREMENTS

- A. General: Install sheet metal flashing and trim to withstand wind loads, structural movement, thermally induced movement, and exposure to weather without failing.

1.4 SUBMITTALS

- A. General: Submit each item in this Article according to the Conditions of the Contract and Division 1 Specification Sections.
- B. Product Data including manufacturer's material and finish data, installation instructions, and general recommendations for each specified flashing material and fabricated product.
- C. Shop Drawings of each item specified showing layout, profiles, methods of joining, and anchorage details.
- D. Samples of sheet metal flashing, trim, and accessory items, in the specified finish. Where finish involves normal color and texture variations, include Sample sets composed of 2 or more units showing the full range of variations expected.
 - 1. 8-inch- square Samples of specified sheet materials to be exposed as finished surfaces.
- E. Qualification data for firms and persons specified in the "Quality Assurance" Article to demonstrate their capabilities and experience. Include lists of completed projects with project names and addresses, names and addresses of architects and owners, and other information specified.

1.5 QUALITY ASSURANCE

- A. Installer Qualifications: Engage an experience Installer who has completed sheet metal flashing and trim work similar in material, design, and extent to that indicated for this Project and with a record of successful in-service performance.

1.6 PROJECT CONDITIONS

- A. Coordinate Work of this Section with interfacing and adjoining Work for proper sequencing of each installation. Ensure best possible weather resistance, durability of Work, and protection of materials and finishes.

PART 2 - PRODUCTS

2.1 METALS

- A. Aluminum: Alloy and temper recommended by aluminum producer and finisher for type of use and finish indicated and with not less than the strength and durability of alloy and temper designated below:
 - 1. Factory-Painted Aluminum Sheet: ASTM B 209, 3003-H14, with a minimum thickness of 0.040 inch, unless otherwise indicated.

2.2 REGLETS

- A. General: Units of type, material, and profile indicated, formed to provide secure interlocking of separate reglet and counterflashing pieces and compatible with flashing indicated.
- B. Surface-Mounted Type: Provide with slotted holes for fastening to substrate, with neoprene or other suitable weatherproofing washers, and with channel for sealant at top edge.
- C. Masonry Type: Provide with offset top flange for embedment in masonry mortar joint.
- D. Flexible Flashing Retainer: Provide resilient plastic or rubber accessory to secure flexible flashing in reglet where clearance does not permit use of standard metal counterflashing or where Drawings show reglet without metal counterflashing.
- E. Counterflashing Wind-Restraint Clips: Provide clips to be installed before counterflashing to prevent wind uplift of the counterflashing lower edge.
 - 1. Material: Aluminum, 0.024 inch thick.
- F. Available Manufacturers: Subject to compliance with requirements, manufacturers offering products that may be incorporated in the Work include, but are not limited to, the following:
- G. Manufacturers: Subject to compliance with requirements, provide products by one of the following (or approved equal):
 - 1. Fry Reglet Corporation.
 - 2. Hickman: W.P. Hickman Co.
 - 3. Keystone Flashing Company.

2.3 MISCELLANEOUS MATERIALS AND ACCESSORIES

- A. Fasteners: Same metal as sheet metal flashing or other noncorrosive metal as recommended by sheet metal manufacturer. Match finish of exposed heads with material being fastened.
- B. Asphalt Mastic: SSPC-Paint 12, solvent-type asphalt mastic, nominally free of sulfur and containing no asbestos fibers, compounded for 15-mil dry film thickness per coat.
- C. Elastomeric Sealant: Generic type recommended by sheet metal manufacturer and fabricator of components being sealed and complying with requirements for joint sealants as specified in Division 7 Section "Joint Sealants."
- D. Epoxy Seam Sealer: 2-part, noncorrosive, aluminum seam-cementing compound, recommended by aluminum manufacturer for exterior and interior nonmoving joints, including riveted joints.
- E. Adhesives: Type recommended by flashing sheet metal manufacturer for waterproof and weather-resistant seaming and adhesive application of flashing sheet metal.
- F. Paper Slip Sheet: 5-lb/square red rosin, sized building paper conforming to FS UU-B-790, Type I, Style 1b.
- G. Polyethylene Underlayment: ASTM D 4397, minimum 6-mil- thick black polyethylene film, resistant to decay when tested according to ASTM E 154.
- H. Metal Accessories: Provide sheet metal clips, straps, anchoring devices, and similar accessory units as required for installation of Work, matching or compatible with material being installed; noncorrosive; size and thickness required for performance.
- I. Roofing Cement: ASTM D 4586, Type I, asbestos free, asphalt based.

2.4 FABRICATION, GENERAL

- A. Sheet Metal Fabrication Standard: Fabricate sheet metal flashing and trim to comply with recommendations of SMACNA's "Architectural Sheet Metal Manual" that apply to the design, dimensions, metal, and other characteristics of the item indicated.
- B. Comply with details shown to fabricate sheet metal flashing and trim that fit substrates and

result in waterproof and weather-resistant performance once installed. Verify shapes and dimensions of surfaces to be covered before fabricating sheet metal.

- C. Form exposed sheet metal Work that is without excessive oil canning, buckling, and tool marks and that is true to line and levels indicated, with exposed edges folded back to form hems.
- D. Seams: Fabricate nonmoving seams in aluminum with flat-lock seams. Form seams and seal with epoxy seam sealer. Rivet joints for additional strength.
- E. Expansion Provisions: Space movement joints at maximum of 10 feet with no joints allowed within 24 inches of corner or intersection. Where lapped or bayonet-type expansion provisions in Work cannot be used or would not be sufficiently weatherproof and waterproof, form expansion joints of intermeshing hooked flanges, not less than 1 inch deep, filled with mastic sealant (concealed within joints).
- F. Sealed Joints: Form nonexpansion, but movable, joints in metal to accommodate elastomeric sealant to comply with SMACNA standards.
- G. Separate metal from noncompatible metal or corrosive substrates by coating concealed surfaces at locations of contact with asphalt mastic or other permanent separation as recommended by manufacturer.
- H. Conceal fasteners and expansion provisions where possible. Exposed fasteners are not allowed on faces of sheet metal exposed to public view.
- I. Fabricate cleats and attachment devices from same material as sheet metal component being anchored or from compatible, noncorrosive metal recommended by sheet metal manufacturer.
 - 1. Size: As recommended by SMACNA manual or sheet metal manufacturer for application but never less than thickness of metal being secured.

2.5 SHEET METAL FABRICATIONS

- A. General: Fabricate sheet metal items in thickness or weight needed to comply with performance requirements but not less than that listed below for each application and metal.
- B. Base Flashing: Fabricate from the following material:
 - 1. Aluminum: 0.040 inch thick.
- C. Counterflashing: Fabricate from the following material:
 - 1. Aluminum: 0.0320 inch thick.
- D. Flashing Receivers: Fabricate from the following material:
 - 1. Aluminum: 0.0320 inch thick.
- E. Drip Edges: Fabricate from the following material:
 - 1. Aluminum: 0.0320 inch thick.
- F. Eave Flashing: Fabricate from the following material:
 - 1. Aluminum: 0.0320 inch thick.
- G. Roof-Penetration Flashing: Fabricate from the following material:
 - 1. Lead: 4.0 lb/sq. Ft., hard tempered.

2.6 ALUMINUM EXTRUSION FABRICATIONS

- A. Aluminum Extrusion Units: Fabricate extruded-aluminum running units with formed or extruded-aluminum joint covers for installation behind main members where possible. Fabricate mitered and welded corner units.

2.7 ALUMINUM FINISHES

- A. General: Comply with Aluminum Association's (AA) "Designation System for Aluminum Finishes" for finish designations and application recommendations.
- B. High-Performance Organic Coating Finish: AA-C12C42R1x (Chemical Finish: cleaned with inhibited chemicals; Chemical Finish: acid chromate-fluoride-phosphate conversion coating; Organic Coating: as specified below). Prepare, pretreat, and apply coating to exposed metal surfaces to comply with coating and resin manufacturer's instructions.
 - 1. Fluoropolymer 2-Coat Coating System: Manufacturer's standard 2-coat, thermocured system composed of specially formulated inhibitive primer and fluoropolymer color topcoat containing not less than 70 percent polyvinylidene fluoride resin by weight; complying with AAMA 605.2.
 - a. Color and Gloss: As selected by Architect from manufacturer's full range of choices

for color and gloss.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine substrates and conditions under which sheet metal flashing and trim are to be installed and verify that Work may properly commence. Do not proceed with installation until unsatisfactory conditions have been corrected.

3.2 INSTALLATION

- A. General: Unless otherwise indicated, install sheet metal flashing and trim to comply with performance requirements, manufacturer's installation instructions, and SMACNA's "Architectural Sheet Metal Manual." Anchor units of Work securely in place by methods indicated, providing for thermal expansion of metal units; conceal fasteners where possible, and set units true to line and level as indicated. Install Work with laps, joints, and seams that will be permanently watertight and weatherproof.
- B. Install exposed sheet metal Work that is without excessive oil canning, buckling, and tool marks and that is true to line and levels indicated, with exposed edges folded back to form hems. Install sheet metal flashing and trim to fit substrates and to result in waterproof and weather-resistant performance. Verify shapes and dimensions of surfaces to be covered before fabricating sheet metal.
- C. Expansion Provisions: Provide for thermal expansion of exposed sheet metal Work. Space movement joints at maximum of 10 feet with no joints allowed within 24 inches of corner or intersection. Where lapped or bayonet-type expansion provisions in Work cannot be used or would not be sufficiently weatherproof and waterproof, form expansion joints of intermeshing hooked flanges, not less than 1 inch deep, filled with mastic sealant (concealed within joints).
- D. Soldered Joints: Clean surfaces to be soldered, removing oils and foreign matter. Pre-tin edges of sheets to be soldered to a width of 1-1/2 inches, except where pre-tinned surface would show in finished Work.
 - 1. Do not solder the following metals:
 - a. Aluminum.
 - 2. Do not use torches for soldering. Heat surfaces to receive solder and flow solder into joint. Fill joint completely. Completely remove flux and spatter from exposed surfaces.
- E. Sealed Joints: Form nonexpansion, but movable, joints in metal to accommodate elastomeric sealant to comply with SMACNA standards. Fill joint with sealant and form metal to completely conceal sealant.
 - 1. Use joint adhesive for nonmoving joints specified not to be soldered.
- F. Seams: Fabricate nonmoving seams in aluminum with flat-lock seams. Form seams and seal with epoxy seam sealer. Rivet joints for additional strength.
- G. Separations: Separate metal from noncompatible metal or corrosive substrates by coating concealed surfaces, at locations of contact, with asphalt mastic or other permanent separation as recommended by manufacturer.
 - 1. Underlayment: Where installing stainless steel or aluminum directly on cementitious or wood substrates, install a slip sheet of red-rosin paper and a course of polyethylene underlayment.
 - 2. Bed flanges of Work in a thick coat of roofing cement where required for waterproof performance.
- H. Install reglets to receive counterflashing according to the following requirements:
 - 1. Where reglets are shown in masonry, furnish reglets for installation under Division 4 Section "Unit Masonry."
- I. Counterflashings: Coordinate installation of counterflashings with installation of assemblies to be protected by counterflashing. Install counterflashings in reglets or receivers. Secure in a waterproof manner by means of snap-in installation and sealant, lead wedges and sealant, interlocking folded seam, or blind rivets and sealant. Lap counterflashing joints a minimum of 2 inches and bed with sealant.

- J. Roof-Penetration Flashing: Coordinate roof-penetration flashing installation with roofing and installation of items penetrating roof. Install flashing as follows:
 - 1. Turn lead flashing down inside vent piping, being careful not to block vent piping with flashing.
 - 2. Seal and clamp flashing to pipes penetrating roof, other than lead flashing on vent piping.

- 3.3 CLEANING AND PROTECTION
 - A. Clean exposed metal surfaces, removing substances that might cause corrosion of metal or deterioration of finishes.
 - B. Provide final protection and maintain conditions that ensure sheet metal flashing and trim Work during construction is without damage or deterioration other than natural weathering at the time of Substantial Completion.

END OF SECTION 07620

**SECTION 07900
JOINT SEALERS**

PART 1 - GENERAL

1.01 WORK DESCRIPTION

- A. This Section and related Drawings describe the requirements pertaining to Sealants and Caulking.
- B. Do all caulking except where specifically noted otherwise on the drawings.
- C. General Performance: Except as otherwise indicated, joint sealers are required to establish and maintain airtight and waterproof continuous seals on a permanent basis within recognized limitations of wear and aging as indicated for each application. Failures of installed sealers to comply with this requirement will be recognized as failures of materials and workmanship.

1.02 EXAMINATION OF SURFACES

- A. Report any surfaces unsatisfactory to receive sealants and caulking to the General Contractor and the Architect in writing.

1.03 MANUFACTURERS

- A. Tremco; Bostick; Pecora, Inc.; Sonneborn; or approved equal.
- B. Polysulfide base sealants shall bear the Thiokol Chemical Corporation's "Tested and Approved" seal.
- C. Submit Manufacturer's product specifications, handling installation, caring instructions, and performance test data sheets for each elastomeric product required.

PART 2 - PRODUCTS

2.01 SEALANTS

- A. Exterior sealant shall be "Thiokol" polysulfide sealant that meets Fed. Spec. TT-S00230C, Type II requirements. Sealant shall be one part non-staining and non-sag. Standard color as selected by Architect shall be used. Pecora "Synthacalk GC-9", Sonneborn "Sonolastic" (One part, 970 Series), Bostik "Chem-calk 100", or approved equal shall be used.
- B. Primers shall be used as recommended by the manufacturer and must be non-staining.
- C. Backup materials and preformed joint fillers shall be non-staining and compatible with the primer and sealant used, and shall be resilient such as closed cell foam, sponge rubber, or of a supporting type such as closed cell rigid foam. Sandel "Poly-tite" or Sonneborn "Sonnefoam" or approved equal shall be used.
- D. Bond breakers, where required, shall be polyethylene tape or as recommended by the sealant manufacturer.
- E. Solvents, cleaning agents, etc. shall be as recommended by the sealant manufacturer.
- F. Bathtub Caulk: Dow Corning silicone rubber bathtub caulk (No. 8640) or approved equal.
- G. Base sealant: Tremco Butyl Sealant.

PART 3 - EXECUTION

3.01 WORKMANSHIP

- A. Follow manufacturer's instructions for mixing, preparation of surfaces, priming, application life, and procedure.
- B. Applicator shall have been continuously engaged in this type work for a period of at least 5 years. The mechanics shall have a minimum of 3 years experience in this type work.

3.02 JOINTS

- A. Joints shall be a minimum of 1/4 inch wide x 1/4 inch deep unless otherwise approved or shown.
- B. Joints in concrete and masonry shall have sealant depth equal to width of joints up to 1/2 inch wide.
- C. Joints in non-porous surfaces shall have sealant depth of 1/2 the applied sealant width.

3.03 PREPARATION

- A. Clean all joints. All surfaces to be free of oil, grease, wax or any other foreign residue.
- B. Porous materials shall be cleaned by grinding, sand blast, acid wash or combination where necessary.
- C. Non-porous materials shall be cleaned either mechanically or chemically. Remove protective coatings. DO NOT allow solvent to air dry.
- D. Clean metal surfaces with a clean cloth moistened with oil free naphtha, methylethyl Ketone or chlorothene. Cleaners shall be applied outside the building, only.

3.04 APPLICATION

- A. Surface preparation, mixing equipment and methods, application procedures and proper use of primers shall be in accordance with manufacturers printed instructions.
- B. Install backup material or joint filler at proper depth to provide sealant dimension detailed. Size and shape of backup shall be such that when compressed 25 to 50 percent it will fit the joint. Roll rod type stock into joint to avoid lengthwise stretching. DO NOT twist or braid. Use bond breaker strip between sealant and supporting type backup. Bond breaker strips shall be used in all joints where sufficient room for backup does not exist.
- C. Apply masking tape where required in continuous strips in alignment with joint edge. Remove immediately after joints have been sealed and tooled.
- D. Prime surfaces as recommended by the manufacturer.
- E. Apply sealant under pressure with hand or power actuated gun with proper size nozzle. Point or tool all joints to provide contour indicated on the drawings.
- F. Do not apply when air temperature is under 40 degrees F, unless directed by the manufacturer.

3.05 SURFACES TO BE CAULKED

- A. The following openings, surfaces, etc., are required to be caulked:
 - 1. All fixed wood to wood connections.
 - 2. All fixed metal to metal connections.
 - 3. All fixed wood or metal to masonry connections.
 - 4. Metal and concrete.
 - 5. Wood and concrete.
 - 6. Countertops and wall.
 - 7. Lavatories and wall.
 - 8. Bathtubs and wall.
 - 9. Surface-mounted raceways and walls.
 - 10. Resilient floor and base.
 - 11. Door frames and walls.
 - 12. Baseboard and walls.
- B. The above list is intended as a guide only and is not intended to limit the extent of sealing or caulking in any way.

3.06 CLEANING

- A. Clean adjacent surfaces free of sealant as work progresses. Use solvent or cleaning agent only as recommended by the manufacturer of the sealant.
- B. Leave work in clean condition.
- C. Cure sealants and caulking compounds in compliance with manufacturer's instructions and recommendations, to obtain high early bond strength internal cohesive strength and surface durability. Advise Contractor of procedures required for cure and protection of joint sealers during construction period, so that they will be without deterioration or damage (other than normal wear and weathering) at time of substantial completion. Cure and protect sealants in a manner which will minimize increase in modulus of elasticity and other accelerated aging effects. Replace or restore sealants which are damaged or deteriorated during construction period.

END OF SECTION 07900

**SECTION 09900
PAINTING**

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 1 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes surface preparation and field painting of the following:
1. Exposed exterior items and surfaces.
 2. Exposed interior items and surfaces.
 3. Surface preparation, priming, and finish coats specified in this Section are in addition to shop priming and surface treatment specified in other Sections.
- B. Paint exposed surfaces, except where the paint schedules indicate that a surface or material is not to be painted or is to remain natural. If the paint schedules do not specifically mention an item or a surface, paint the item or surface the same as similar adjacent materials or surfaces whether or not schedules indicate colors. If the schedules do not indicate color or finish, the Architect will select from standard colors and finishes available.
1. Painting includes field painting of exposed bare and covered pipes and ducts (including color coding), hangers, exposed steel and iron work, and primed metal surfaces of mechanical and electrical equipment.
- C. Do not paint prefinished items, concealed surfaces, finished metal surfaces, operating parts, and labels.
1. Prefinished items include the following factory-finished components:
 - a. Architectural woodwork and casework.
 - b. Kitchen cabinets
 - c. Metal toilet enclosures.
 - d. Metal lockers.
 - e. Finished mechanical and electrical equipment.
 - f. Light fixtures.
 - g. Distribution cabinets.
 2. Concealed surfaces include walls or ceilings in the following generally inaccessible spaces:
 - a. Furred areas.
 - b. Ceiling plenums.
 - c. Pipe spaces.
 - d. Duct shafts.
 3. Finished metal surfaces include the following:
 - a. Anodized aluminum.
 - b. Stainless steel.
 - c. Chromium plate.
 - d. Bronze and brass.
 4. Labels: Do not paint over Underwriters Laboratories (UL), Factory Mutual (FM), or other code-required labels or equipment name, identification, performance rating, or nomenclature plates.
- D. Related Sections include the following:
1. Division 2 Section "Hot-Mix Asphalt Paving" for traffic-marking paint.
 2. Division 2 Section "Portland Cement Concrete Paving" for traffic-marking paint.
 3. Division 5 Section "Metal Fabrications" for shop priming ferrous metal.
 4. Division 8 Section "Steel Doors and Frames" for shop priming steel doors and frames.
 5. Division 9 Section "Gypsum Board" for surface preparation for gypsum board.
 6. Divisions 15 and 16: Painting of mechanical and electrical work is specified in Divisions 15 and 16, respectively.

1.3 DEFINITIONS

- A. General: Standard coating terms defined in ASTM D 16 apply to this Section.
 - 1. Flat refers to a lusterless or matte finish with a gloss range below 15 when measured at an 85-degree meter.
 - 2. Eggshell refers to low-sheen finish with a gloss range between 5 and 20 when measured at a 60-degree meter.
 - 3. Satin refers to low-sheen finish with a gloss range between 15 and 35 when measured at a 60-degree meter.
 - 4. Semi-gloss refers to medium-sheen finish with a gloss range between 30 and 65 when measured at a 60-degree meter.

1.4 SUBMITTALS

- A. Product Data: For each paint system specified. Include block fillers and primers.
 - 1. Material List: Provide an inclusive list of required coating materials. Indicate each material and cross-reference specific coating, finish system, and application. Identify each material by manufacturer's catalog number and general classification.
 - 2. Manufacturer's Information: Provide manufacturer's technical information, including label analysis and instructions for handling, storing, and applying each coating material proposed for use.
 - 3. Certification by the manufacturer that products supplied comply with local regulations controlling use of volatile organic compounds (VOCs).
- B. Samples for Initial Selection: Manufacturer's color charts showing the full range of colors available for each type of finish-coat material indicated.
 - 1. After color selection, the Architect will furnish color chips for surfaces to be coated.
- C. Qualification Data: For firms and persons specified in the "Quality Assurance" Article to demonstrate their capabilities and experience. Include lists of completed projects with project names and addresses, names and addresses of architects and owners, and other information specified.

1.5 QUALITY ASSURANCE

- A. Applicator Qualifications: Engage an experienced applicator who has completed painting system applications similar in material and extent to that indicated for this Project with a record of successful in-service performance.
- B. Source Limitations: Obtain block fillers, primers, and undercoat materials for each coating system from the same manufacturer as the finish coats.

1.6 DELIVERY, STORAGE, AND HANDLING

- A. Deliver materials to the Project Site in manufacturer's original, unopened packages and containers bearing manufacturer's name and label, and the following information:
 - 1. Product name or title of material.
 - 2. Product description (generic classification or binder type).
 - 3. Manufacturer's stock number and date of manufacture.
 - 4. Contents by volume, for pigment and vehicle constituents.
 - 5. Thinning instructions.
 - 6. Application instructions.
 - 7. Color name and number.
 - 8. VOC content.
- B. Store materials not in use in tightly covered containers in a well-ventilated area at a minimum ambient temperature of 45 deg F. Maintain containers used in storage in a clean condition, free of foreign materials and residue.
 - 1. Protect from freezing. Keep storage area neat and orderly. Remove oily rags and waste daily. Take necessary measures to ensure that workers and work areas are protected from fire and health hazards resulting from handling, mixing, and application.

1.7 PROJECT CONDITIONS

- A. Apply water-based paints only when the temperature of surfaces to be painted and surrounding

air temperatures are between 50 and 90 deg F.

- B. Apply solvent-thinned paints only when the temperature of surfaces to be painted and surrounding air temperatures are between 45 and 95 deg F.
- C. Do not apply paint in snow, rain, fog, or mist; or when the relative humidity exceeds 85 percent; or at temperatures less than 5 deg F above the dew point; or to damp or wet surfaces.
 - 1. Painting may continue during inclement weather if surfaces and areas to be painted are enclosed and heated within temperature limits specified by manufacturer during application and drying periods.

1.8 EXTRA MATERIALS

- A. Furnish extra paint materials from the same production run as the materials applied in the quantities described below. Package paint materials in unopened, factory-sealed containers for storage and identify with labels describing contents. Deliver extra materials to the Owner.
 - 1. Quantity: At the completion of work, provide 20 gallons of the color and type used in each coating material used. Cans shall be clearly identified.

PART 2 - PRODUCTS

2.1 MANUFACTURERS

- A. Products: Subject to compliance with requirements, provide one of the products in the paint schedules (or approved equal).
- B. Manufacturers Names: The following manufacturers are referred to in the paint schedules by use of shortened versions of their names, which are shown in parentheses:
 - 1. Devoe & Raynolds Co. (Devoe).
 - 2. Glidden Co. (The) (Glidden).
 - 3. Sherwin-Williams Co. (S-W).

2.2 PAINT MATERIALS, GENERAL

- A. Material Compatibility: Provide block fillers, primers, undercoats, and finish-coat materials that are compatible with one another and the substrates indicated under conditions of service and application, as demonstrated by manufacturer based on testing and field experience.
- B. Material Quality: Provide manufacturer's best-quality paint material of the various coating types specified. Paint-material containers not displaying manufacturer's product identification will not be acceptable.
- C. Colors: Color selections will be made by the Architect from manufacturer's standard colors.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine substrates, areas, and conditions, with the Applicator present, under which painting will be performed for compliance with paint application requirements.
 - 1. Do not begin to apply paint until unsatisfactory conditions have been corrected and surfaces receiving paint are thoroughly dry.
 - 2. Start of painting will be construed as the Applicator's acceptance of surfaces and conditions within a particular area.
- B. Coordination of Work: Review other Sections in which primers are provided to ensure compatibility of the total system for various substrates. On request, furnish information on characteristics of finish materials to ensure use of compatible primers.
 - 1. Notify the Architect about anticipated problems using the materials specified over substrates primed by others.

3.2 PREPARATION

- A. General: Remove hardware and hardware accessories, plates, machined surfaces, lighting fixtures, and similar items already installed that are not to be painted. If removal is impractical

or impossible because of the size or weight of the item, provide surface-applied protection before surface preparation and painting.

1. After completing painting operations in each space or area, reinstall items removed using workers skilled in the trades involved.
- B. Cleaning: Before applying paint or other surface treatments, clean the substrates of substances that could impair the bond of the various coatings. Remove oil and grease before cleaning.
 1. Schedule cleaning and painting so dust and other contaminants from the cleaning process will not fall on wet, newly painted surfaces.
- C. Surface Preparation: Clean and prepare surfaces to be painted according to manufacturer's written instructions for each particular substrate condition and as specified. Seal all penetrations in wall, ceiling or floor prior to painting.
 1. Provide barrier coats over incompatible primers or remove and re-prime.
 2. Cementitious Materials: Prepare concrete, concrete masonry block, cement plaster, and mineral-fiber-reinforced cement panel surfaces to be painted. Remove efflorescence, chalk, dust, dirt, grease, oils, and release agents. Roughen as required to remove glaze. If hardeners or sealers have been used to improve curing, use mechanical methods of surface preparation.
 - a. Use abrasive blast-cleaning methods if recommended by paint manufacturer.
 - b. Determine alkalinity and moisture content of surfaces by performing appropriate tests. If surfaces are sufficiently alkaline to cause the finish paint to blister and burn, correct this condition before application. Do not paint surfaces where moisture content exceeds that permitted in manufacturer's written instructions.
 - c. Clean concrete floors to be painted with a 5 percent solution of muriatic acid or other etching cleaner. Flush the floor with clean water to remove acid, neutralize with ammonia, rinse, allow to dry, and vacuum before painting.
 3. Wood: Clean surfaces of dirt, oil, and other foreign substances with scrapers, mineral spirits, and sandpaper, as required. Sand surfaces exposed to view smooth and dust off.
 - a. Scrape and clean small, dry, seasoned knots, and apply a thin coat of white shellac or other recommended knot sealer before applying primer. After priming, fill holes and imperfections in finish surfaces with putty or plastic wood filler. Sand smooth when dried.
 - b. Prime, stain, or seal wood to be painted immediately on delivery. Prime edges, ends, faces, undersides, and backsides of wood, including cabinets, counters, cases, and paneling.
 - c. When transparent finish is required, backprime with spar varnish.
 - d. Seal tops, bottoms, and cutouts of unprimed wood doors with a heavy coat of varnish or sealer immediately on delivery.
 4. Ferrous Metals: Clean ungalvanized ferrous-metal surfaces that have not been shop coated; remove oil, grease, dirt, loose mill scale, and other foreign substances. Use solvent or mechanical cleaning methods that comply with the Steel Structures Painting Council's (SSPC) recommendations.
 - a. Touch up bare areas and shop-applied prime coats that have been damaged. Wire-brush, clean with solvents recommended by paint manufacturer, and touch up with the same primer as the shop coat.
 5. Galvanized Surfaces: Clean galvanized surfaces with nonpetroleum-based solvents so surface is free of oil and surface contaminants. Remove pretreatment from galvanized sheet metal fabricated from coil stock by mechanical methods.
- D. Materials Preparation: Mix and prepare paint materials according to manufacturer's written instructions.
 1. Maintain containers used in mixing and applying paint in a clean condition, free of foreign materials and residue.
 2. Stir material before application to produce a mixture of uniform density. Stir as required during application. Do not stir surface film into material. If necessary, remove surface film and strain material before using.
 3. Use only thinners approved by paint manufacturer and only within recommended limits.

3.3 APPLICATION

- A. General: Apply paint according to manufacturer's written instructions. Use applicators and techniques best suited for substrate and type of material being applied.
 - 1. Paint colors, surface treatments, and finishes are indicated in the schedules.
 - 2. Do not paint over dirt, rust, scale, grease, moisture, scuffed surfaces, or conditions detrimental to formation of a durable paint film.
 - 3. Provide finish coats that are compatible with primers used.
 - 4. The term "exposed surfaces" includes areas visible when permanent or built-in fixtures, convector covers, covers for finned-tube radiation, grilles, and similar components are in place. Extend coatings in these areas, as required, to maintain the system integrity and provide desired protection.
 - 5. Paint surfaces behind movable equipment and furniture the same as similar exposed surfaces. Before the final installation of equipment, paint surfaces behind permanently fixed equipment or furniture with prime coat only.
 - 6. Paint back sides of access panels and removable or hinged covers to match exposed surfaces.
 - 7. Finish exterior doors on tops, bottoms, and side edges the same as exterior faces.
 - 8. Sand lightly between each succeeding enamel or varnish coat.
- B. Scheduling Painting: Apply first coat to surfaces that have been cleaned, pretreated, or otherwise prepared for painting as soon as practicable after preparation and before subsequent surface deterioration.
 - 1. The number of coats and the film thickness required are the same regardless of application method. Do not apply succeeding coats until the previous coat has cured as recommended by the manufacturer. If sanding is required to produce a smooth, even surface according to manufacturer's written instructions, sand between applications.
 - 2. Omit primer on metal surfaces that have been shop primed and touchup painted.
 - 3. If undercoats, stains, or other conditions show through final coat of paint, apply additional coats until paint film is of uniform finish, color, and appearance. Give special attention to ensure edges, corners, crevices, welds, and exposed fasteners receive a dry film thickness equivalent to that of flat surfaces.
 - 4. Allow sufficient time between successive coats to permit proper drying. Do not recoat surfaces until paint has dried to where it feels firm, does not deform or feel sticky under moderate thumb pressure, and where application of another coat of paint does not cause the undercoat to lift or lose adhesion.
- C. Application Procedures: Apply paints and coatings by brush, roller, spray, or other applicators according to manufacturer's written instructions.
 - 1. Brushes: Use brushes best suited for the type of material applied. Use brush of appropriate size for the surface or item being painted.
 - 2. Rollers: Use rollers of carpet, velvet back, or high-pile sheep's wool as recommended by the manufacturer for the material and texture required.
 - 3. Spray Equipment: Use airless spray equipment with orifice size as recommended by the manufacturer for the material and texture required.
- D. Minimum Coating Thickness: Apply paint materials no thinner than manufacturer's recommended spreading rate. Provide the total dry film thickness of the entire system as recommended by the manufacturer.
- E. Electrical items to be painted include, but are not limited to, the following:
 - 1. Conduit and fittings.
 - 2. Switchgear.
 - 3. Panelboards.
- F. Block Fillers: Apply block fillers to concrete masonry block at a rate to ensure complete coverage with pores filled.
- G. Prime Coats: Before applying finish coats, apply a prime coat of material, as recommended by the manufacturer, to material that is required to be painted or finished and that has not been prime coated by others. Recoat primed and sealed surfaces where evidence of suction spots or unsealed areas in first coat appears, to ensure a finish coat with no burn through or other defects due to insufficient sealing.

- H. Pigmented (Opaque) Finishes: Completely cover surfaces as necessary to provide a smooth, opaque surface of uniform finish, color, appearance, and coverage. Cloudiness, spotting, holidays, laps, brush marks, runs, sags, ropiness, or other surface imperfections will not be acceptable.
- I. Transparent (Clear) Finishes: Use multiple coats to produce a glass-smooth surface film of even luster. Provide a finish free of laps, runs, cloudiness, color irregularity, brush marks, orange peel, nail holes, or other surface imperfections.
 - 1. Provide satin finish for final coats.
- J. Completed Work: Match approved samples for color, texture, and coverage. Remove, refinish, or repaint work not complying with requirements.

3.4 FIELD QUALITY CONTROL

- A. The Owner reserves the right to invoke the following test procedure at any time and as often as the Owner deems necessary during the period when paint is being applied:
 - 1. The Owner will engage the services of an independent testing agency to sample the paint material being used. Samples of material delivered to the Project will be taken, identified, sealed, and certified in the presence of the Contractor.
 - 2. The testing agency will perform appropriate tests for the following characteristics as required by the Owner:
 - a. Quantitative material analysis.
 - b. Abrasion resistance.
 - c. Apparent reflectivity.
 - d. Flexibility.
 - e. Washability.
 - f. Absorption.
 - g. Accelerated weathering.
 - h. Dry opacity.
 - i. Accelerated yellowness.
 - j. Recoating.
 - k. Skinning.
 - l. Color retention.
 - m. Alkali and mildew resistance.
 - 3. The Owner may direct the Contractor to stop painting if test results show material being used does not comply with specified requirements. The Contractor shall remove noncomplying paint from the site, pay for testing, and repaint surfaces previously coated with the rejected paint. If necessary, the Contractor may be required to remove rejected paint from previously painted surfaces if, on repainting with specified paint, the 2 coatings are incompatible.

3.5 CLEANING

- A. Cleanup: At the end of each workday, remove empty cans, rags, rubbish, and other discarded paint materials from the site.
 - 1. After completing painting, clean glass and paint-spattered surfaces. Remove spattered paint by washing and scraping. Be careful not to scratch or damage adjacent finished surfaces.

3.6 PROTECTION

- A. Protect work of other trades, whether being painted or not, against damage by painting. Correct damage by cleaning, repairing or replacing, and repainting, as approved by Architect.
- B. Provide "Wet Paint" signs to protect newly painted finishes. Remove temporary protective wrappings provided by others to protect their work after completing painting operations.
 - 1. At completion of construction activities of other trades, touch up and restore damaged or defaced painted surfaces. Comply with procedures specified in PDCA P1.

3.7 EXTERIOR PAINT SCHEDULE

- A. Concrete Masonry Units: Provide the following finish systems over exterior concrete masonry

units:

1. Low-Luster Acrylic Finish: 2 finish coats over a block filler.
 - a. Block Filler: High-performance, latex block filler applied at spreading rate recommended by the manufacturer to achieve a total dry mill thickness of not less than 4.0 mils.
 - 1) Devoe: 52902 Bloxfil 200 Interior/Exterior Latex Block Filler.
 - 2) Glidden: 5317 Ultra-Hide Block Filler Latex Interior-Exterior.
 - b. First and Second Coats: Low-luster (eggshell or satin), exterior, acrylic-latex paint applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 2.3 mils.
 - 1) Devoe: 16XX Wonder-Shield Exterior Acrylic Latex Satin House and Trim Paint.
 - 2) Glidden: 6700 Series Spred Ultra Exterior Satin Latex House and Trim Paint.
- B. Exterior Gypsum Soffit Board: Provide the following finish systems over exterior gypsum soffit board:
 1. Flat Acrylic Finish: 2 finish coats over an exterior, alkyd- or alkali-resistant primer, as recommended by the manufacturer.
 - a. Primer: Exterior, alkyd- or alkali-resistant, acrylic-latex primer, as recommended by the manufacturer for this substrate, applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 1.5 mils.
 - 1) Devoe: 1102 All-Weather Exterior Alkyd House Paint Primer.
 - 2) Glidden: Primer not required over this substrate.
 - b. First and Second Coats: Flat, exterior, acrylic-emulsion paint applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 2.4 mils.
 - 1) Devoe: 15XX Wonder-Shield Exterior Acrylic Latex Flat House Paint.
 - 2) Glidden: 3525 Series Spred House Masonry & Stucco Finish.
- C. Wood Trim: Provide the following finish systems over exterior wood trim:
 1. Medium-Shade, Semigloss, Acrylic-Enamel Finish: 2 finish coats over a primer.
 - a. Primer: Exterior, acrylic-latex primer applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 1.4 mils.
 - 1) Devoe: 1102 All-Weather Exterior Alkyd House Paint Primer.
 - 2) Glidden: UH 790 Ultra-Hide Exterior Latex Prime Coat.
 - b. First and Second Coats: Semigloss, waterborne, exterior, acrylic-latex enamel applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 2.4 mils.
 - 1) Devoe: 17XX Wonder-Shield Semi-Gloss Exterior Acrylic Latex House and Trim Paint.
 - 2) Glidden: 6600 Series Spred Ultra Exterior Gloss Latex House & Trim Paint.
- D. Ferrous Metal: Provide the following finish systems over exterior ferrous metal. Primer is not required on shop-primed items.
 1. Full-Gloss, Alkyd-Enamel Finish: 2 finish coats over a rust-inhibitive primer.
 - a. Primer: Rust-inhibitive metal primer applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 1.3 mils.
 - 1) Devoe: 13101 Mirrolac Rust Penetrating Metal Primer.
 - 2) Glidden: 5205 Glid-Guard Tank & Structural Primer, Red.
 - 3) S-W: Kem Kromik Metal Primer B50N2/B50W1.
 - b. First and Second Coats: Full-gloss, exterior, alkyd enamel applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 3.0 mils.
 - 1) Devoe: 70XX Mirrolac Interior/Exterior Alkyd-Urethane Gloss Enamel.
 - 2) Glidden: 4500 Series Glid-Guard Alkyd Industrial Enamel.
 - 3) S-W: Industrial Enamel B-54 Series.
- E. Zinc-Coated Metal: Provide the following finish systems over exterior zinc-coated (galvanized) metal surfaces:

1. Full-Gloss, Alkyd-Enamel Finish: 2 finish coats over a galvanized metal primer.
 - a. Primer: Galvanized metal primer applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 1.2 mils.
 - 1) Devoe: 8502/8520 Mirrolac-WB Interior/Exterior Waterborne Flat DTM Primer and Finish.
 - 2) Glidden: 5205 Glid-Guard Tank & Structural Primer, Red.
 - 3) S-W: Galvite Paint B50W3.
 - b. First and Second Coats: Full-gloss, exterior, alkyd enamel applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 2.6 mils.
 - 1) Devoe: 70XX Mirrolac Interior/Exterior Alkyd-Urethane Gloss Enamel.
 - 2) Glidden: 4500 Series Glid-Guard Alkyd Industrial Enamel.
 - 3) S-W: Industrial Enamel B-54 Series.

3.8 INTERIOR PAINT SCHEDULE

- A. Concrete Masonry Units: Provide the following finish systems over interior concrete masonry block units:
 1. Semigloss, Alkyd-Enamel Finish: 2 finish coats over an undercoat and a filled surface.
 - a. Block Filler: High-performance, latex-based, block filler applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 5.0 mils.
 - 1) Devoe: 52902 Bloxfil 200 Interior/Exterior Latex Block Filler.
 - 2) Glidden: 5317 Ultra-Hide Block Filler, Latex Interior-Exterior.
 - 3) S-W: Heavy-Duty Block Filler B42W46.
 - b. Undercoat: Interior, alkyd- or latex-based, enamel undercoater, as recommended by the manufacturer for this substrate, applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 1.2 mils.
 - 1) Devoe: 26XX Velour Interior Alkyd Semi-Gloss Enamel.
 - 2) Glidden: UH 400 Ultra-Hide Alkyd Interior Enamel Undercoater.
 - 3) S-W: Classic 99 Interior/Exterior Semi-Gloss Alkyd Enamel A-40 Series.
 - c. Finish Coat: Odorless, semigloss, alkyd, interior enamel applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 1.5 mils.
 - 1) Devoe: 26XX Velour Interior Alkyd Semi-Gloss Enamel.
 - 2) Glidden: UH 8400 Ultra Traditional Alkyd Semi-Gloss Enamel.
 - 3) S-W: Classic 99 Interior/Exterior Semi-Gloss Alkyd Enamel A-40 Series.
- B. Gypsum Board: Provide the following finish systems over interior gypsum board surfaces:
 1. Ceilings - Flat Acrylic Finish: 2 finish coats over a primer.
 - a. Primer: Latex-based, interior primer applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 1.2 mils.
 - 1) Devoe: 50801 Wonder-Tones Interior Vinyl Latex Primer-Sealer.
 - 2) Glidden: 5111 Spred Ultra Latex Primer-Sealer.
 - b. First and Second Coats: Flat, acrylic-latex-based, interior paint applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 2.5 mils.
 - 1) Devoe: 36XX Wonder-Tones Interior Latex Flat Wall Paint.
 - 2) Glidden: 4000 Series Spred Ultra Flat Latex Wall and Trim Paint.
 2. Walls - Low-Luster, Acrylic-Enamel Finish: 2 finish coats over a primer.
 - a. Primer: Latex-based, interior primer applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 1.2 mils.
 - 1) Devoe: 50801 Wonder-Tones Interior Vinyl Latex Primer-Sealer.
 - 2) Glidden: 5111 Spred Ultra Latex Primer-Sealer.
 - b. First and Second Coats: Low-luster (eggshell or satin), acrylic-latex, interior enamel applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 2.8 mils.
 - 1) Devoe: 34XX Wonder-Tones Interior Latex Eggshell Enamel.

- 2) Glidden: 4100 Series Spred Ultra Eggshell Latex Wall & Trim Paint.
3. Frames - Semigloss, Acrylic-Enamel Finish: 2 finish coats over a primer.
 - a. Primer: Latex-based, interior primer applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 1.2 mils.
 - 1) Devoe: 50801 Wonder-Tones Interior Vinyl Latex Primer-Sealer.
 - 2) Glidden: 5111 Spred Ultra Latex Primer-Sealer.
 - b. First and Second Coats: Semigloss, acrylic-latex, interior enamel applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 2.6 mils.
 - 1) Devoe: 39XX Wonder-Tones Semi-Gloss Interior Latex Enamel.
 - 2) Glidden: 8200 Series Spred Ultra Latex Semi-Gloss Enamel.
- C. Woodwork and Hardboard: Provide the following paint finish systems over new, interior wood surfaces:
 1. Semigloss, Acrylic-Enamel Finish: 2 finish coats over a wood undercoater.
 - a. Undercoat: Alkyd- or acrylic-latex-based, interior wood undercoater, as recommended by the manufacturer for this substrate, applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 1.2 mils.
 - 1) Devoe: 51701 Wonder-Prime All-Purpose Latex Primer Sealer & Vapor Barrier.
 - 2) Glidden: UH 400 Ultra-Hide Alkyd Interior Enamel Undercoater.
 - b. First and Second Coats: Semigloss, acrylic-latex, interior enamel applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 2.6 mils.
 - 1) Devoe: 39XX Wonder-Tones Semi-Gloss Interior Latex Enamel.
 - 2) Glidden: 8200 Series Spred Ultra Latex Semi-Gloss Enamel.
- D. Stained Woodwork: Provide the following stained finishes over new, interior woodwork:
 1. Alkyd-Based, Satin-Varnish Finish: 2 finish coats of an alkyd-based, clear-satin varnish over a sealer coat and an alkyd-based, interior wood stain. Wipe wood filler before applying stain.
 - a. Filler Coat: Paste-wood filler applied at spreading rate recommended by the manufacturer.
 - 1) Devoe: None required.
 - 2) Glidden: Glidden Paste Wood Filler.
 - 3) S-W: Sher-Wood Fast-Dry Filler.
 - b. Stain Coat: Alkyd-based, interior wood stain applied at spreading rate recommended by the manufacturer.
 - 1) Devoe: 96XX WoodWorks Alkyd Interior Stain.
 - 2) Glidden: 1600 Series Woodmaster Oil Wood Stain.
 - 3) S-W: Oil Stain A-48 Series.
 - c. Sealer Coat: Clear sanding sealer applied at spreading rate recommended by the manufacturer.
 - 1) Devoe: 4900 WoodWorks Quick-Dry Clear Sealer.
 - 2) Glidden: 5035 Ultra-Hide Quick-Dry Sanding Sealer, Clear.
 - 3) S-W: ProMar Varnish Sanding Sealer B26V3.
 - d. First and Second Finish Coats: Alkyd-based or polyurethane varnish, as recommended by the manufacturer, applied at spreading rate recommended by the manufacturer.
 - 1) Devoe: 4600 WoodWorks Alkyd Satin Varnish.
 - 2) Glidden: 82 Satin Sheen Woodmaster Polyurethane Clear Finishes Varnish.
 - 3) S-W: Oil Base Varnish, Gloss A66V91.
- E. Natural-Finish Woodwork: Provide the following natural finishes over new, interior woodwork:
 1. Alkyd-Based, Satin-Varnish Finish: 2 finish coats of an alkyd-based, clear-satin varnish over a sanding sealer. Provide wood filler on open-grain wood before applying first varnish coat.

- a. Filler Coat: Paste-wood filler applied at spreading rate recommended by the manufacturer.
 - 1) Devoe: None required.
 - 2) Glidden: Glidden Paste Wood Filler.
 - 3) S-W: Sher-Wood Fast-Dry Filler.
 - b. Sealer Coat: Clear sanding sealer applied at spreading rate recommended by the manufacturer.
 - 1) Devoe: 4900 WoodWorks Quick-Dry Clear Sealer.
 - 2) Glidden: 5035 Ultra-Hide Quick-Dry Sanding Sealer, Clear.
 - 3) S-W: ProMar Varnish Sanding Sealer B26V3.
 - c. First and Second Finish Coats: Alkyd-based or polyurethane varnish, as recommended by the manufacturer, applied at spreading rate recommended by the manufacturer.
 - 1) Devoe: 4600 WoodWorks Alkyd Satin Varnish.
 - 2) Glidden: 82 Satin Sheen Woodmaster Polyurethane Clear Finishes Varnish.
 - 3) S-W: Oil Base Varnish, Gloss A66V91.
- F. Ferrous Metal: Provide the following finish systems over ferrous metal:
- 1. Semigloss, Alkyd-Enamel Finish: One finish coat over an enamel undercoater and a primer.
 - a. Primer: Quick-drying, rust-inhibitive, alkyd-based or epoxy-metal primer, as recommended by the manufacturer for this substrate, applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 1.5 mils.
 - 1) Devoe: 13101 Mirrolac Rust Penetrating Metal Primer.
 - 2) Glidden: 5207 Glid-Guard Tank & Structural Primer, White.
 - 3) S-W: Kem Kromik Metal Primer B50N2/B50W1.
 - b. Undercoat: Alkyd, interior enamel undercoat or semigloss, interior, alkyd-enamel finish coat, as recommended by the manufacturer for this substrate, applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 1.2 mils.
 - 1) Devoe: 26XX Velour Interior Alkyd Semi-Gloss Enamel.
 - 2) Glidden: UH 8400 Ultra Traditional Alkyd Semi-Gloss Enamel.
 - 3) S-W: ProMar 200 Interior Alkyd Semi-Gloss Enamel B34W200.
 - c. Finish Coat: Odorless, semigloss, alkyd, interior enamel applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 1.4 mils.
 - 1) Devoe: 26XX Velour Interior Alkyd Semi-Gloss Enamel.
 - 2) Glidden: UH 8400 Ultra Traditional Alkyd Semi-Gloss Enamel.
 - 3) S-W: Classic 99 Interior/Exterior Semi-Gloss Alkyd Enamel A-40 Series.
- G. Zinc-Coated Metal: Provide the following finish systems over zinc-coated metal:
- 1. Semigloss, Alkyd-Enamel Finish: One finish coat over an undercoat and a primer.
 - a. Primer: Galvanized metal primer applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 1.2 mils.
 - 1) Devoe: 13201 Mirrolac Galvanized Metal Primer.
 - 2) Glidden: 5207 Glid-Guard Tank & Structural Primer, White.
 - 3) S-W: Galvite Paint B50W3.
 - b. Undercoat: Alkyd, interior enamel undercoat or semigloss, interior, alkyd-enamel finish coat, as recommended by the manufacturer for this substrate, applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less than 1.2 mils.
 - 1) Devoe: 26XX Velour Interior Alkyd Semi-Gloss Enamel.
 - 2) Glidden: UH 8400 Series Spred Ultra Traditional Alkyd Semi-Gloss Enamel.
 - 3) S-W: ProMar 200 Interior Alkyd Semi-Gloss Enamel B34W200.
 - c. Finish Coat: Odorless, semigloss, alkyd, interior enamel applied at spreading rate recommended by the manufacturer to achieve a total dry film thickness of not less

than 1.4 mils.

- 1) Devoe: 26XX Velour Interior Alkyd Semi-Gloss Enamel.
- 2) Glidden: UH 8400 Ultra Traditional Alkyd Semi-Gloss Enamel.
- 3) S-W: Classic 99 Interior Alkyd Semi-Gloss Enamel A-40 Series.

END OF SECTION 09900